

SACB-6/12-10,0PUR - Distributor box



1680911

<https://www.phoenixcontact.com/pc/products/1680911>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Distributor box, connection method: M12 socket Plastic, number of slots: 6, number of positions: 5, coding: A, slot assignment: Double, status display: No, Universal; master cable connection: Fixed connection 180°, PUR/PVC, cable length: 10 m, shielding: no

Your advantages

- Safety in the field, thanks to robust housing and high degree of protection
- Save space: distributor box with double occupancy for two sensors in one slot

Commercial data

Item number	1680911
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	02
Product key	BF3CBA
Catalog page	Page 114 (PC-2009)
GTIN	4017918171216
Weight per piece (including packing)	1,641.3 g
Weight per piece (excluding packing)	1,641.3 g
Customs tariff number	85444290
Country of origin	PL

SACB-6/12-10,0PUR - Distributor box



1680911

<https://www.phoenixcontact.com/pc/products/1680911>

Technical data

Product properties

Product type	Distributor box
Number of positions	5
Number of slots	6
Coding	A
LED	no

Electrical properties

Max. operating voltage U_{max}	135 V
Nominal voltage U_N	120 V
Rated current, total	12 A
Max. current carrying capacity per path	2 A
Current carrying capacity per slot	4 A

Connection data

Conductor connection

Sensor/actuator connection system	M12 socket
Tightening torque slot sensor/actuator cable	0.4 Nm

Pin assignment

Slot/position = Wire color or connection	1 / 4 (A) = WH
	1 / 2 (B) = GYPK
	2 / 4 (A) = GN
	2 / 2 (B) = RDBU
	3 / 4 (A) = YE
	3 / 2 (B) = WHGN
	4 / 4 (A) = GY
	4 / 2 (B) = BNGN
	5 / 4 (A) = PK
	5 / 2 (B) = WHYE
	6 / 4 (A) = RD
	6 / 2 (B) = YEBN
	1-6 / 1 (+ 120 V) = BN
	1-6 / 3 (0 V) = BU
	1-6 / 5 (PE) = GNYE

Signaling

Status display present	No
------------------------	----

Dimensions

SACB-6/12-10,0PUR - Distributor box

1680911

<https://www.phoenixcontact.com/pc/products/1680911>



Dimensional drawing	
Width	54 mm
Height	19 mm
Length	129 mm

Material specifications

Material Threaded sleeve	PA
Material Housing	PA
Flammability rating according to UL 94	V0
Seal material O-ring	NBR
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	PA

Cable/line

Cable length	10 m
--------------	------

PUR/PVC black [PUR]

Dimensional drawing	
Cable weight	150.9 kg/km
UL AWM Style	20549
Number of positions	15
Shielded	no
Cable type	PUR/PVC black [PUR]
Conductor structure signal line	28x 0.15 mm
AWG signal line	20
Conductor cross section	12x 0.5 mm² (Signal line)
	3x 1 mm² (power line)
Wire diameter incl. insulation	1.5 mm ±0.1 mm (Signal line)
	2.1 mm ±0.1 mm (power line)

SACB-6/12-10,0PUR - Distributor box



1680911

<https://www.phoenixcontact.com/pc/products/1680911>

External cable diameter	9.40 mm $\pm$ 0.2 mm
Outer sheath, material	PUR
External sheath, color	black RAL 9005
Conductor material	Bare Cu litz wires
Material wire insulation	PVC
Single wire, color	brown, blue, green/yellow, white, green, yellow, gray, pink, red, gray/pink, red/blue, white/green, brown/green, white/yellow, yellow/brown
Thickness, insulation	$\geq$ 0.15 mm (Inner sheath)
	$\geq$ 0.76 mm (Outer cable sheath)
Overall twist	Wires twisted in layers
Nominal voltage, cable	300 V
Test voltage	2000 V
Minimum bending radius, fixed installation	7.5 x D
Minimum bending radius, flexible installation	10 x D
Smallest bending radius, fixed installation	71 mm
Smallest bending radius, movable installation	94 mm
Dynamic load capacity (bending)	Max. bending cycles: 1500000, Bending radius: 94 mm, Traversing path: 2 m, Traversing rate: 2 m/s
Flame resistance	DIN EN 50265
Resistance to oil	according to VDE 0472 Part 803
Other resistance	Highly resistant to acids, alkaline solutions and solvents
Special properties	Silicone-free
Ambient temperature (operation)	-40 °C ... 90 °C (cable, fixed installation)
	-5 °C ... 80 °C (Cable, flexible installation)
	80 °C (in acc. with UL)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
	IP67
Ambient temperature (operation)	-25 °C ... 75 °C

SACB-6/12-10,0PUR - Distributor box


1680911

<https://www.phoenixcontact.com/pc/products/1680911>



Drawings

Schematic diagram




M12 slot, socket, 5-pos.

SACB-6/12-10,0PUR - Distributor box

1680911

<https://www.phoenixcontact.com/pc/products/1680911>

Circuit diagram




SACB-6/12-10,0PUR - Distributor box

1680911

<https://www.phoenixcontact.com/pc/products/1680911>

Dimensional drawing



SACB-6/12-10,0PUR - Distributor box



1680911

<https://www.phoenixcontact.com/pc/products/1680911>

Classifications

ECLASS

ECLASS-11.0	27440108
ECLASS-13.0	27440108

SACB-6/12-10,0PUR - Distributor box



1680911

<https://www.phoenixcontact.com/pc/products/1680911>

Environmental product compliance

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com