

# Specifications



Photo is representative

## Eaton 168455

Eaton Moeller series NZM - Molded Case Circuit Breaker. Circuit-breaker, 3p, 400A, plug-in module, C3-S400-SVE

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller series NZM molded case circuit breaker magnetic
<b>CATALOG NUMBER</b>	168455
<b>MODEL CODE</b>	NZMC3-S400-SVE
<b>EAN</b>	4015081649389
<b>PRODUCT LENGTH/DEPTH</b>	335 mm
<b>PRODUCT HEIGHT</b>	215.2 mm
<b>PRODUCT WIDTH</b>	140 mm
<b>PRODUCT WEIGHT</b>	6.38 kg
<b>COMPLIANCES</b>	RoHS conform

## Product specifications

<b>AMPERAGE RATING</b>	400 A
<b>VOLTAGE RATING</b>	690 V - 690 V
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF</b>	Does not apply, since the

## Resources

### BROCHURES

[eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf](#)

[eaton-digital-nzm-brochure-br013003en-en-us.pdf](#)

### CATALOGUES

[eaton-digital-nzm-catalog-ca013003en-en-us.pdf](#)

### CHARACTERISTIC CURVE

[eaton-circuit-breaker-nzm-mccb-characteristic-curve-035.eps](#)

### DECLARATIONS OF CONFORMITY

[eaton-molded-case-circuit-breaker-declaration-of-conformity-eu250292en.pdf](#)

### ECAD MODEL

[DA-CE-ETN.NZMC3-S400-SVE](#)

### INSTALLATION INSTRUCTIONS

[eaton-circuit-breaker-plug-in-adapter-nzm2-il01219023z.pdf](#)

### INSTALLATION VIDEOS

[The new digital NZM Range](#)

[Introduction of the new digital circuit breaker NZM](#)

### MCAD MODEL

[nzmh3\\_me220\\_sve.dwg](#)  
[nzmh3\\_me220\\_sve.stp](#)

### PEP ECO-PASSPORT

[eaton-molded-case-switches-pep-eato-00231-v0101-en.pdf](#)

### TECHNICAL DATA SHEETS

[eaton-nzm-technical-information-sheet](#)

<b>PROTECTION OF ASSEMBLIES</b>	entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>MOUNTING METHOD</b>	Built-in device plug-in technique
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT</b>	72.48 W
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	70 °C
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>AMBIENT STORAGE TEMPERATURE - MAX</b>	70 °C
<b>AMBIENT STORAGE TEMPERATURE - MIN</b>	40 °C
<b>RATED OPERATING POWER AT AC-3, 230 V</b>	132 kW
<b>RATED OPERATING POWER AT AC-3, 400 V</b>	200 kW
<b>SWITCH OFF TECHNIQUE</b>	Magnetic
<b>DEGREE OF PROTECTION</b>	IP20
<b>DIRECTION OF INCOMING SUPPLY</b>	As required
<b>ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT</b>	Screw connection
<b>RATED OPERATIONAL</b>	349 A (400 V AC-3)

<b>CURRENT</b>	
<b>NUMBER OF POLES</b>	Three-pole
<b>TYPE</b>	Circuit breaker

**SPECIAL FEATURES**

- Motor protection in conjunction with overload relay
- With short-circuit release
- Without overload release  $I_r$
- IEC/EN 60947-4-1, IEC/EN 60947-2
- The circuit-breaker fulfills all requirements for AC-3 switching category.
- Rated current = rated uninterrupted current: 400 A

<b>SHORT-CIRCUIT RELEASE</b>	
<b>NON-DELAYED SETTING -</b>	5000 A
<b>MAX</b>	

<b>SHORT-CIRCUIT RELEASE</b>	
<b>NON-DELAYED SETTING -</b>	2800 A
<b>MIN</b>	

<b>HANDLE TYPE</b>	Rocker lever
--------------------	--------------

<b>INSTANTANEOUS</b>	
<b>CURRENT SETTING (II) -</b>	44328 A
<b>MAX</b>	

<b>INSTANTANEOUS</b>	
<b>CURRENT SETTING (II) -</b>	7 A
<b>MIN</b>	

<b>OVERLOAD CURRENT</b>	
<b>SETTING (IR) - MAX</b>	0 A

<b>OVERLOAD CURRENT</b>	
<b>SETTING (IR) - MIN</b>	0 A

<b>RATED SHORT-CIRCUIT</b>	
<b>BREAKING CAPACITY ICS</b>	
<b>(IEC/EN 60947) AT</b>	36 kA
<b>400/415 V, 50/60 Hz</b>	

<b>RATED SHORT-CIRCUIT</b>	
<b>BREAKING CAPACITY ICS</b>	
<b>(IEC/EN 60947) AT 440 V,</b>	36 kA
<b>50/60 Hz</b>	

<b>RATED SHORT-CIRCUIT</b>	
<b>BREAKING CAPACITY ICU</b>	
<b>(IEC/EN 60947) AT</b>	36 kA
<b>400/415 V, 50/60 Hz</b>	

---

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

---



**Eaton Corporation plc**

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

