

Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation at <http://www.download.phoenixcontact.com>. The General Terms and Conditions of Use apply to Internet downloads.

► Extract from the online catalog



Male contact inserts, with PCB and
9x0,5 - screw connections

Order No.	1688379
Ord designation	VS-09-ST-DSUB/9-MPT-0,5
EAN	4017918817527
Pack	10 Pcs.
Customs tariff	85369010
Catalog page information	Page 14 (PC-2005)

► Technical data

Mechanical characteristics

Insertion force per signal contact	<=
Extraction force per signal contact	<= 2.2 Nm
Insertion/withdrawal cycles	>= 200

Material data

Material contact surface	Ni/Au
--------------------------	-------

Electrical characteristics

Maximum load current	1 A
Operating voltage	63 V
Contact resistance per contact pair	$\leq 2.5 \text{ m}\Omega$
Insulation resistance	$\geq 5.E+03 \text{ M}\Omega$
Conductor cross section, rigid min.	0.14 mm ²
Conductor cross section, rigid max.	0.5 mm ²
Conductor cross section AWG/kcmil min.	26
Conductor cross section AWG/kcmil max	20

► **Address**

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057
USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>
Phoenix Contact
Technical modifications reserved;