

VS-09-ST-DSUB-ER - Contact insert



1688382

<https://www.phoenixcontact.com/us/products/1688382>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

D-SUB contact insert, shell size 1, with 9 signal contacts, type of contact pin, for PCB mounting, angled, fixing with M3 thread and solder pins, for panel mounting frame VS-09-...



Your advantages

- D-SUB 9 connection
- Compatible with IP67 sleeve housing and panel-mount frame
- Easy assembly

Commercial data

Item number	1688382
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	AB19
Product key	ABNCAA
Catalog page	Page 211 (C-2-2013)
GTIN	4017918818333
Weight per piece (including packing)	15.3 g
Weight per piece (excluding packing)	11.49 g
Customs tariff number	85366990
Country of origin	DE

VS-09-ST-DSUB-ER - Contact insert

1688382

<https://www.phoenixcontact.com/us/products/1688382>



Technical data

Product properties

Product type	Male insert
Type	D-SUB
Number of positions	9
Connection profile	D-SUB 9
Type	Male
Shielded	no

Insulation characteristics

Overvoltage category	III
Degree of pollution	2


Electrical properties

Rated voltage in acc. with IEC 61076-2-101	400 V
Rated voltage (III/3)	125 V
Rated surge voltage	1 kV
Rated current	5 A (at 20 °C)
Test voltage	1200 V
Transmission medium	Copper

Connection data

Connection method	PCB connection
-------------------	----------------

Dimensions

Dimensional drawing	
Width	21.5 mm
Height	17.8 mm
Length	31.19 mm

Material specifications

Flammability rating according to UL 94	V0
Housing material	Steel, tin-plated
Contact material	Copper alloy
Contact surface material	Hard gold-plated over nickel
Contact carrier material	PBT-GF

VS-09-ST-DSUB-ER - Contact insert



1688382

<https://www.phoenixcontact.com/us/products/1688382>

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 50
Insertion force per signal contact	$\leq 3.40 \text{ N}$

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-55 °C ... 125 °C

Mounting

Mounting type	Threads and solder pins
---------------	-------------------------

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com