

VS-15-ST-DSUB-EG - Contact insert



1688874

<https://www.phoenixcontact.com/pc/products/1688874>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

D-SUB contact insert, shell size 2, with 15 signal contacts, type of contact pin, with solder cup, straight, fixing with a 3 mm hole, for panel mounting frame and sleeve housing VS-15-...



Your advantages

- D-SUB 15 connection
- Easy assembly
- Compatible with IP67 sleeve housing and panel-mount frame

Commercial data

Item number	1688874
Packing unit	10 pc
Minimum order quantity	1 pc
Product key	ABNCAA
Catalog page	Page 210 (C-2-2013)
GTIN	4017918823023
Weight per piece (including packing)	12.99 g
Weight per piece (excluding packing)	7.43 g
Customs tariff number	85366990
Country of origin	DE

VS-15-ST-DSUB-EG - Contact insert

1688874

<https://www.phoenixcontact.com/pc/products/1688874>



Technical data

Product properties

Product type	Male insert
Type	D-SUB
Number of positions	15
Connection profile	D-SUB 15
Type	Male
Shielded	no

Data management status

Article revision	02
------------------	----

Insulation characteristics

Overvoltage category	III
Degree of pollution	2


Electrical properties

Rated voltage in acc. with IEC 61076-2-101	400 V
Rated voltage (III/3)	125 V
Rated surge voltage	1 kV
Rated current	5 A (at 20 °C)
Test voltage	1200 V
Transmission medium	Copper

Connection data

Connection method	Solder cup
-------------------	------------

Dimensions

Dimensional drawing	
Width	14.4 mm
Height	39.5 mm
Length	12.9 mm

Material specifications

Flammability rating according to UL 94	V0
Housing material	Steel, tin-plated
Contact material	Copper alloy
Contact surface material	Hard gold-plated over nickel

VS-15-ST-DSUB-EG - Contact insert



1688874

<https://www.phoenixcontact.com/pc/products/1688874>

Contact carrier material	PBT-GF
--------------------------	--------

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 50
Insertion force per signal contact	≤ 3.40 N

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-55 °C ... 125 °C

Mounting

Mounting type	Hole
---------------	------


VS-15-ST-DSUB-EG - Contact insert

1688874


<https://www.phoenixcontact.com/pc/products/1688874>

Drawings

Schematic diagram



Dimensional drawing



D-SUB contact insert

VS-15-ST-DSUB-EG - Contact insert



1688874

<https://www.phoenixcontact.com/pc/products/1688874>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1688874>



UL Recognized

Approval ID: FILE E 118976

VS-15-ST-DSUB-EG - Contact insert



1688874

<https://www.phoenixcontact.com/pc/products/1688874>

Classifications

ECLASS

ECLASS-11.0	27440223
ECLASS-12.0	27440223
ECLASS-13.0	27440223

ETIM

ETIM 9.0	EC003557
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

VS-15-ST-DSUB-EG - Contact insert



1688874

<https://www.phoenixcontact.com/pc/products/1688874>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	c30472e6-5c56-46a0-a450-62f6874c6344

VS-15-ST-DSUB-EG - Contact insert

1688874

<https://www.phoenixcontact.com/pc/products/1688874>



Accessories

CUC-DST-GPME-S/DSSC15 - D-SUB sleeve housings

1419710

<https://www.phoenixcontact.com/pc/products/1419710>



D-SUB sleeve housings, degree of protection: IP20, material: ABS, metal-plated, cable outlet: straight, housing size: 2, color: Bare metallic

CUC-DST-GPME-A/DSSC15 - D-SUB sleeve housings

1419718

<https://www.phoenixcontact.com/pc/products/1419718>



D-SUB sleeve housings, degree of protection: IP20, material: ABS, metal-plated, cable outlet: angled, housing size: 2, color: Bare metallic

VS-15-ST-DSUB-EG - Contact insert

1688874

<https://www.phoenixcontact.com/pc/products/1688874>



CUC-DST-GZNI-S/DSSC15 - D-SUB sleeve housings

1419724

<https://www.phoenixcontact.com/pc/products/1419724>



D-SUB sleeve housings, degree of protection: IP20, material: Zinc die-cast, cable outlet: straight, housing size: 2, color: Bare metallic

CUC-DST-GZNI-A/DSSC15 - D-SUB sleeve housings

1419725

<https://www.phoenixcontact.com/pc/products/1419725>



D-SUB sleeve housings, degree of protection: IP20, material: Zinc die-cast, cable outlet: angled, housing size: 2, color: Bare metallic

VS-15-ST-DSUB-EG - Contact insert

1688874

<https://www.phoenixcontact.com/pc/products/1688874>



VS-15-A - Panel-mount frame

1688036

<https://www.phoenixcontact.com/pc/products/1688036>

D-SUB panel mounting frame, shell size 2, IP67 degree of protection



VS-15-T-2PG11 - D-SUB sleeve housings

1688052

<https://www.phoenixcontact.com/pc/products/1688052>

D-SUB sleeve housing, shell size 2, IP67 degree of protection



VS-15-ST-DSUB-EG - Contact insert

1688874

<https://www.phoenixcontact.com/pc/products/1688874>



CUC-SCHRAUBE-5,5:360 - Screw

1421711

<https://www.phoenixcontact.com/pc/products/1421711>

Screw, design: Hexagonal, color: Bare metallic



VS-15-BU-DSUB-EG - Contact insert

1688887

<https://www.phoenixcontact.com/pc/products/1688887>

D-SUB contact insert, shell size 2, with 15 signal contacts, type of contact socket, with solder cup, straight, fixing with a 3 mm hole, for panel mounting frame and sleeve housing VS-15-...



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com