

VS-25-ST-DSUB-FK - D-SUB contact insert



1689912

<https://www.phoenixcontact.com/us/products/1689912>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

D-SUB contact insert, shell size 3, with 25 signal contacts, type of contact pin, flat-ribbon cable connection, angled, fixing with a 3 mm hole, for panel mounting frame VS-25-...



Your advantages

- D-SUB 25 connection
- Compatible with IP67 sleeve housing and panel-mount frame
- Easy assembly

Commercial data

Item number	1689912
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	AB19
Product key	ABNCAA
Catalog page	Page 213 (C-2-2013)
GTIN	4017918914318
Weight per piece (including packing)	16.81 g
Weight per piece (excluding packing)	11.33 g
Customs tariff number	85366990
Country of origin	DE

VS-25-ST-DSUB-FK - D-SUB contact insert



1689912

<https://www.phoenixcontact.com/us/products/1689912>

Technical data

Product properties

Product type	Male insert
Type	D-SUB
Number of positions	25
Connection profile	D-SUB 25
Type	Male
Shielded	no

Insulation characteristics

Overvoltage category	III
Degree of pollution	2

Electrical properties

Rated voltage (III/3)	125 V
Rated surge voltage	1 kV
Rated current	1.5 A (at 20 °C)
Test voltage	1000 V
Transmission medium	Copper

Connection data

Connection method	Flat-ribbon cable connection
-------------------	------------------------------

Material specifications

Flammability rating according to UL 94	V0
Housing material	Steel, tin-plated
Contact material	Copper alloy
Contact surface material	Hard gold-plated over nickel
Contact carrier material	Polyester GF

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 50
-----------------------------	------

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-55 °C ... 125 °C
---------------------------------	-------------------

Mounting

Mounting type	Hole
---------------	------

VS-25-ST-DSUB-FK - D-SUB contact insert

1689912

<https://www.phoenixcontact.com/us/products/1689912>



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com