

SACC-M12MR-5CON-PG 7-SH - Connector



1693429

<https://www.phoenixcontact.com/pc/products/1693429>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Connector, Universal, 5-position, shielded, Plug angled M12, coding: A, Screw connection, knurl material: Brass, nickel-plated, cable gland Pg7, external cable diameter 4 mm ... 6 mm



Your advantages

- Safe use in the field, thanks to a high degree of protection
- Screw connection: proven connection technology for a large selection of different conductors
- Reliable signal transmission – 360° shielding in environments with electromagnetic interference

Commercial data

Item number	1693429
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	02
Product key	BF2CBA
Catalog page	Page 24 (C-2-2019)
GTIN	4017918173524
Weight per piece (including packing)	68.9 g
Weight per piece (excluding packing)	71.9 g
Customs tariff number	85366990
Country of origin	CN

SACC-M12MR-5CON-PG 7-SH - Connector



1693429

<https://www.phoenixcontact.com/pc/products/1693429>

Technical data

Notes

Assembly note	NOTE: Observe the permissible bending radii when routing cables, since the degree of protection may be at risk if the bending forces are too high. Reduce mechanical loads upstream of the connector, e.g., by using cable ties.
---------------	---

Mounting

Assembly note	The connector pin assignment can be rotated 90° to the cable outlet
---------------	---

Product properties

Product type	Circular connector (cable-side)
Sensor type	Universal
Number of positions	5
No. of cable outlets	1
Shielded	yes
Coding	A
Cable outlet	angled
Pg screw connection	Pg7


Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Data management status

Article revision	04
------------------	----

Dimensions

Dimensional drawing	
Length	48.3 mm
External dimensions	
Outside diameter	4 mm ... 6 mm
Housing	
Diameter housing	20 mm

Material specifications

Flammability rating according to UL 94	HB
--	----

SACC-M12MR-5CON-PG 7-SH - Connector



1693429

<https://www.phoenixcontact.com/pc/products/1693429>

Seal material	NBR
Material of grip body	Brass, nickel-plated
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PA
Material for screw connection	Brass, nickel-plated

Connection data

Conductor connection

Connection method	Screw connection
Connection cross section	0.25 mm ² ... 0.75 mm ² (without ferrule)
	0.14 mm ² ... 0.5 mm ² (with ferrule)
	0.25 mm ² ... 0.75 mm ² (solid)
Connection cross section AWG	24 ... 18 (without ferrule)
	26 ... 20 (with ferrule)
Stripping length of the individual wire	5 mm
Tightening torque	0.4 Nm (M12 knurl)
	0.2 Nm (Screw terminal blocks)
	1 Nm (Pressure nut with coupling sleeve)

Electrical properties

Rated surge voltage	1.5 kV
Contact resistance	≤ 3 mΩ
Insulation resistance	≥ 100 MΩ
Nominal voltage U _N	48 V AC
	60 V DC
Nominal current I _N	4 A

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 100
-----------------------------	-------

Connector

Connection 1

Head design	Plug
Head cable outlet	angled
Head thread type	M12
Coding	A

Cable/line

Signal type/category	Universal
Stripping length of the individual wire	5 mm

SACC-M12MR-5CON-PG 7-SH - Connector



1693429

<https://www.phoenixcontact.com/pc/products/1693429>

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67
Ambient temperature (operation)	-40 °C ... 85 °C (Plug / socket)

Standards and regulations

M12

Standard designation	M12 connector
Standards/specifications	IEC 61076-2-101

SACC-M12MR-5CON-PG 7-SH - Connector


1693429

<https://www.phoenixcontact.com/pc/products/1693429>



Drawings

Schematic diagram



Pin assignment M12 male connector, 5-pos., A-coded, male side


SACC-M12MR-5CON-PG 7-SH - Connector

1693429

<https://www.phoenixcontact.com/pc/products/1693429>



Dimensional drawing



M12 x 1 male plug, angled, shielded

SACC-M12MR-5CON-PG 7-SH - Connector





1693429

<https://www.phoenixcontact.com/pc/products/1693429>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1693429>

 cUL Recognized Approval ID: FILE E 221474				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	60 V	4 A	-	-

 UL Recognized Approval ID: FILE E 221474				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	60 V	4 A	-	-

cULus Recognized				
-------------------------	--	--	--	--

SACC-M12MR-5CON-PG 7-SH - Connector



1693429

<https://www.phoenixcontact.com/pc/products/1693429>

Classifications

ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116

ETIM

ETIM 9.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

SACC-M12MR-5CON-PG 7-SH - Connector



1693429

<https://www.phoenixcontact.com/pc/products/1693429>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)

China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	a09a9485-3bb8-41c1-aa31-3621eabfec29

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com