

1696112

https://www.phoenixcontact.com/us/products/1696112

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 4-position, PUR/PVC, yellow, Plug angled M12, coding: A, on Socket straight M12, coding: A, cable length: 1.5 m, DESINA

### Your advantages

• Easy and safe: 100 % electrically tested plug-in components

#### Commercial data

Item number	1696112
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF03
Product key	BF1CCA
Catalog page	Page 105 (PC-2002)
GTIN	4017918181086
Weight per piece (including packing)	76.1 g
Weight per piece (excluding packing)	70.8 g
Customs tariff number	85444290
Country of origin	DE



1696112

https://www.phoenixcontact.com/us/products/1696112

## Technical data

#### Product properties

Product type	Sensor/actuator cable
Application	DESINA
Number of positions	4
No. of cable outlets	1
Shielded	no
Coding	A
Insulation characteristics	
Overvoltage category	II
Degree of pollution	3

#### Material specifications

Flammability rating according to UL 94	НВ
Seal material	NBR
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material for screw connection	Zinc die-cast, nickel-plated

### Electrical properties

Insulation resistance	≥ 100 MΩ
Nominal voltage U <sub>N</sub>	250 V AC
	250 V DC
Nominal current I <sub>N</sub>	4 A

### Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 100

### Signaling

Status display	No
Status display present	No

### Connection data

Conductor connection

Tightening torque	0.4 Nm

#### Connector

Connection 1



1696112

https://www.phoenixcontact.com/us/products/1696112

Туре	Plug angled M12
Number of positions	4
Coding type	A
Connection 2	
Type	Socket straight M12
Number of positions	4
Coding type	A
3 4,72	
able/line	
Cable length	1.5 m
DUD/DVC valley (440)	
PUR/PVC yellow [140]  Dimensional drawing	
Cable weight	39 kg/km
UL AWM Style	20549
Number of positions	4
Shielded	no
Cable type	PUR/PVC yellow [140]
Conductor structure signal line	42x 0.10 mm
AWG signal line	22
Conductor cross section	4x 0.34 mm² (Signal line)
Wire diameter incl. insulation	1.5 mm ±0.05 mm
External cable diameter	5.20 mm ±0.2 mm
Outer sheath, material	PUR
External sheath, color	yellow
Conductor material	Bare Cu litz wires
Material wire insulation	PVC
Single wire, color	brown, white, blue, black
Thickness, insulation	approx. 0.30 mm (Core insulation)
	≥ 0.38 mm (Outer cable sheath)
	approx. 0.35 mm (Inner sheath)
Overall twist	4 wires, twisted
Max. conductor resistance	max. 58 Ω/km (at 20 °C)
Insulation resistance	≥ 1 GΩ*km (at 20 °C)
Nominal voltage, cable	≤ 300 V
Test voltage	≥ 3000 V
Smallest bending radius, fixed installation	52 mm



1696112

https://www.phoenixcontact.com/us/products/1696112

Smallest bending radius, movable installation	52 mm
Max. bending cycles	2000000
Flame resistance	in accordance with DIN UL-Style 20549
Ambient temperature (operation)	-25 °C 80 °C (cable, fixed installation)
	-5 °C 80 °C (Cable, flexible installation)

#### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP65
	IP67
	IP68
Ambient temperature (operation)	-25 °C 90 °C (Plug / socket)
	-25 °C 80 °C (cable, fixed installation)
	-5 °C 80 °C (Cable, flexible installation)

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com