

Specifications

Eaton 171298

Eaton Moeller® series SL4 Base module;250-mm aluminum tube and foot

General specifications

PRODUCT NAME	Eaton Moeller® series SL4 Base module
CATALOG NUMBER	171298
EAN	4015081678419
PRODUCT LENGTH/DEPTH	72 mm
PRODUCT HEIGHT	302 mm
PRODUCT WIDTH	72 mm
PRODUCT WEIGHT	0.167 kg
CERTIFICATIONS	UL File No.: E29184 IEC/EN 60529 UL CE UL report applies to both US and Canada CSA Class No.: NKCR7 UL 508 UL Category Control No.: NKCR IEC/EN 60947-5-1 CSA-C22.2 No. 14-10 Certified by UL for use in Canada CSA-C22.2 No. 94-91
MODEL CODE	SL4-PIB-250

Features & Functions

COLOR	Other
FITTED WITH:	Cover Aluminum tube Plastic foot
NUMBER OF MODULES	Max. 5 (with standard base) Max. 5 Max. 10 (with base for mounting on both sides)

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MIN	-30 °C
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Electrical rating

RATED INSULATION VOLTAGE (UI)	250 V
RATED OPERATIONAL VOLTAGE	24 V AC/DC ± 10 % 230/240 V AC ± 10 % 110/120 V AC ± 10 %

General

CONNECTION TO SMARTWIRE-DT	No
DEGREE OF PROTECTION	NEMA 4 IP66 NEMA 4X NEMA 13
MOUNTING METHOD	Bracket Floor Horizontal
MOUNTING POSITION	As required
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	SL signal towers
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4000 V AC
SHOCK RESISTANCE	Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
TUBE LENGTH	250 mm
TYPE	Base module

Terminal capacities

TERMINAL CAPACITY (AWG)	24 - 16
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE AND PLASTIC COLLAR)	0.25 - 0.75 mm ²
TERMINAL CAPACITY (SOLID/FLEXIBLE)	0.2 - 1.5 mm ²
TERMINAL CAPACITY (SOLID/FLEXIBLE WITH FERRULE)	0.25 - 1.5 mm ²

Resources

CATALOGUES	eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf
-------------------	--

	eaton-rmq-titan-brochure-br047004en-en-us.pdf
DECLARATIONS OF CONFORMITY	DA-DC-00004257.pdf DA-DC-00004253.pdf
DRAWINGS	eaton-operating-sl4-base-module-dimensions-009.eps eaton-operating-button-sl7-base-module-symbol.eps eaton-operating-sl4-base-module-3d-drawing.eps
ECAD MODEL	DA-CE-ETN.SL4-PIB-250
INSTALLATION INSTRUCTIONS	IL047001ZU IL047002ZU
INSTALLATION VIDEOS	Signal towers SL4 and SL7
MCAD MODEL	DA-CD-sl4_pib_250 DA-CS-sl4_pib_250

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

