Specifications

Photo is representative

Eaton 171322

Eaton Moeller® series SL4 Continuous light module, white, LED, 120 V

General specifications		
PRODUCT NAME	Eaton Moeller® series SL4 Continuous light module	
CATALOG NUMBER	171322	
EAN	4015081678617	
PRODUCT LENGTH/DEPTH	43 mm	
PRODUCT HEIGHT	75 mm	
PRODUCT WIDTH	43 mm	
PRODUCT WEIGHT	0.043 kg	
CERTIFICATIONS	CE UL Category Control No.: NKCR UL report applies to both US and Canada UL UL 508 CSA-C22.2 No. 94-91 Certified by UL for use in Canada UL File No.: E29184 IEC/EN 60529 CSA-C22.2 No. 14-10 IEC/EN 60947-5-1 CSA Class No.: NKCR7	
MODEL CODE	SL4-L120-W	



Features & Functions		
COLOR	Other	
ENCLOSURE COLOR	Black	
FUNCTIONS	Continuous light	
LIGHT MODULES	LED	
NUMBER OF MODULES	Max. 10 (with base for mounting on both sides) Max. 5 (with standard base)	

General	
CONNECTION TO SMARTWIRE-DT	No
DEGREE OF PROTECTION	NEMA 4X IP66
LIFESPAN, ELECTRICAL	100,000 h
LIGHT TYPE	Continuous light
MATERIAL	Enclosure: Polycarbonate (PC) Cap: Polycarbonate (PC)
MOUNTING POSITION	As required
OVERVOLTAGE CATEGORY	Ш
POLLUTION DEGREE	3
PRODUCT CATEGORY	SL signal towers
RADIATION ANGLE	360 °
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4000 V AC
SHOCK RESISTANCE	Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
ТҮРЕ	Continuous light module
VOLTAGE TYPE	AC

Climatic environmental conditions	
AMBIENT OPERATING TEMPERATURE - MIN	-30 °C
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

	Electrical rating	
	LEAKAGE CURRENT	0.003 A
	RATED INSULATION VOLTAGE (UI)	250 V
	RATED OPERATIONAL VOLTAGE (UE) AT AC - MIN	110 V
	RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	120 V
	RATED OPERATIONAL VOLTAGE (UE) AT DC - MIN	0 V
	RATED OPERATIONAL VOLTAGE (UE) AT DC - MAX	0 V

Resources	
CATALOGUES	eaton-pushbuttons-signal- towers-sensors- assortment-overview- catalog-ca047003en-en- us.pdf
	eaton-rmq-titan-brochure- br047004en-en-us.pdf
DECLARATIONS OF CONFORMITY	DA-DC-00004257.pdf
	DA-DC-00004253.pdf
DRAWINGS	eaton-operating-sl4- continuous-light- dimensions.eps
	eaton-operating-sl7- continuous-light-symbol- 002.eps
	eaton-operating-button- sl7-continuous-light- symbol-003.eps
ECAD MODEL	ETN.171322.edz
INSTALLATION INSTRUCTIONS	<u>IL047001ZU</u>
INSTALLATION VIDEOS	Signal towers SL4 and SL7
MCAD MODEL	DA-CS-sl4 bfl4
	DA-CD-sl4_bfl4

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.









