

# Specifications



Photo is representative

## Eaton 171800

Eaton Moeller series NZM Undervoltage release, 18VDC, +2N/O early, for NZM1

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller series NZM Undervoltage release
<b>CATALOG NUMBER</b>	171800
<b>MODEL CODE</b>	NZM1-XUHIV18DC
<b>EAN</b>	4015081683345
<b>PRODUCT LENGTH/DEPTH</b>	37 mm
<b>PRODUCT HEIGHT</b>	66 mm
<b>PRODUCT WIDTH</b>	32 mm
<b>PRODUCT WEIGHT</b>	0.056 kg
<b>COMPLIANCES</b>	UL/CSA IEC RoHS conform
<b>GLOBAL CATALOG</b>	171800



Powering Business Worldwide

## Product specifications

<b>USED WITH</b>	NZM1(-4), N(S)1(-4)
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF PROTECTION OF</b>	Does not apply, since the entire switchgear needs to

## Resources

<b>BROCHURES</b>	<a href="#">eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf</a> <a href="#">eaton-digital-nzm-brochure-br013003en-en-us.pdf</a>
<b>CATALOGS</b>	<a href="#">eaton-digital-nzm-catalog-ca013003en-en-us.pdf</a>
<b>DRAWINGS</b>	<a href="#">eaton-circuit-breaker-release-nzm-mccb-dimensions.eps</a>
<b>ECAD MODEL</b>	<a href="#">DA-CE-ETN.NZM1-XUHIV18DC</a>
<b>INSTALLATION VIDEOS</b>	<a href="#">The new digital NZM Range</a> <a href="#">Introduction of the new digital circuit breaker NZM</a>
<b>MCAD MODEL</b>	<a href="#">eaton-171798-3d-model.stp</a> <a href="#">eaton-171798-drawing.dwg</a>
<b>TECHNICAL DATA SHEETS</b>	<a href="#">eaton-nzm-technical-information-sheet</a>

<b>ASSEMBLIES</b>	be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>ELECTRIC CONNECTION TYPE</b>	Screw connection
<b>FITTED WITH:</b>	Two early-make auxiliary contacts
<b>FRAME</b>	NZM1
<b>NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)</b>	2
<b>RATED CONTROL SUPPLY VOLTAGE</b>	18 V DC
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX</b>	0 V
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN</b>	0 V
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX</b>	0 V
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN</b>	0 V
<b>SUITABLE FOR</b>	Off-load switch
<b>CONNECTION TYPE</b>	With terminal block on the left-hand switch side
<b>VOLTAGE TYPE</b>	AC

<b>TYPE</b>	Accessory Undervoltage release Undervoltage release with early-make auxiliary contact
<b>SPECIAL FEATURES</b>	Undervoltage release with 2 early-make auxiliary contacts, e.g., for early-make connection of undervoltage release in main switch applications, as well as for interlock and load shedding circuits. For use with emergency-stop devices in connection with an emergency-stop button. When the undervoltage trip is switched off, accidental contact with the circuit breaker's primary contacts is prevented when switched on. Early make of auxiliary contacts on switching on and off (manual operation): approx. 20 ms Undervoltage releases cannot be installed simultaneously with NZM...-XHIV... early-make auxiliary contact or NZM...-XA... shunt release.
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX</b>	18 V
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN</b>	18 V
<b>NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)</b>	0
<b>NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)</b>	0
<b>UNDELAYED SHORT-CIRCUIT RELEASE - MIN</b>	0 A
<b>UNDELAYED SHORT-CIRCUIT RELEASE - MAX</b>	0 A

---

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

---



**Eaton Corporation plc**

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

