SMKDS 5/2-9,5 A0 - PCB terminal block



1724385

https://www.phoenixcontact.com/us/products/1724385

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



PCB terminal block, number of positions per row: 2, product range: SMKDS 5, pitch: 9.52 mm, screw head form: L Slotted, Pin layout: Linear pinning, Solder pin [P]: 5 mm, type of packaging: packed in cardboard

Commercial data

Item number	1724385
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	AA02
Product key	AANFDN
GTIN	4017918242312
Weight per piece (including packing)	6.49 g
Weight per piece (excluding packing)	6.1 g
Customs tariff number	85369010
Country of origin	PL

SMKDS 5/ 2-9,5 A0 - PCB terminal block



1724385

https://www.phoenixcontact.com/us/products/1724385

Technical data

Product properties

Product type	Printed circuit board terminal
Product family	SMKDS 5
Туре	PC terminal block can be aligned
Number of positions	2
Pitch	9.52 mm
Pin layout	Linear pinning

Electrical properties

Rated voltage (II/2)	1000 V
Rated voltage (III/2)	1000 V
Rated surge voltage (II/2)	6 kV
Rated surge voltage (III/2)	6 kV
Rated surge voltage (III/3)	6 kV

Mounting

Mounting type	Wave soldering
Pin layout	Linear pinning
Drive form screw head	Slotted (L)

Material specifications

	Contact surface	Tin Sn
--	-----------------	--------

Dimensions

Width	19.04 mm
Height	26.5 mm
Installed height	21.5 mm
Length of the solder pin	5 mm
Length	18.5 mm
Length of the solder pin	5 mm
Hole diameter	1.3 mm
Pitch	9.52 mm

Packaging specifications

SMKDS 5/ 2-9,5 A0 - PCB terminal block



1724385

https://www.phoenixcontact.com/us/products/1724385

Classifications

ECLASS

ECLASS-13.0 27460101

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com