

Specifications



Eaton 172532

Eaton Moeller series NZM - Molded Case Circuit Breaker. Door coupling rotary handle, black, +key lock, size 3

General specifications

PRODUCT NAME	Eaton Moeller series NZM operating element
CATALOG NUMBER	172532
MODEL CODE	NZM3-XTVDKL
EAN	4015081690787
PRODUCT LENGTH/DEPTH	125 mm
PRODUCT HEIGHT	170 mm
PRODUCT WIDTH	225 mm
PRODUCT WEIGHT	1.476 kg
COMPLIANCES	UL/CSA IEC RoHS conform
GLOBAL CATALOG	172532

Product specifications

USED WITH	NZM3(-4), PN3(-4), N(S)3(-4)
FEATURES	Lockable Standard: black / gray With key lock
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.

Resources

BROCHURES

[eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf](#)

[eaton-digital-nzm-brochure-br013003en-en-us.pdf](#)

CATALOGS

[eaton-digital-nzm-catalog-ca013003en-en-us.pdf](#)

[eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-004.eps](#)

[eaton-circuit-breaker-padlock-nzm-rotary-handle-dimensions.eps](#)

DRAWINGS

[eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-006.eps](#)

[eaton-circuit-breaker-nzm-rotary-handle-3d-drawing-007.eps](#)

INSTALLATION VIDEOS

[The new digital NZM Range](#)

[Introduction of the new digital circuit breaker NZM](#)

TECHNICAL DATA SHEETS

[eaton-nzm-technical-information-sheet](#)

10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
COLOR	Black
FRAME	NZM3
SUITABLE FOR	Power circuit breaker Switch disconnecter
COVER/DOOR TYPE	Door interlock can be modified in the unlocked ON position Door interlock can be modified such that it can be defeated from the outside using a screwdriver Door to be opened in the OFF position when not locked Door interlock not defeatable in the locked OFF and ON positions with padlock on the handle
LOCKING FACILITY	Lockable in position 0 using cylinder lock and key withdrawable Lockable on the 0 position on the handle using up to 3 padlocks

	With door interlock
TYPE	Accessory Door coupling rotary handle
SPECIAL FEATURES	Door coupling rotary handle for operating the switch through a closed control panel door External warning plate/designation label can be clipped on. Complete including rotary drive and coupling parts Extension shaft additionally required. obtainable in two lengths
DEGREE OF PROTECTION / NEMA ENCLOSURE TYPE	IP66 4X. 12

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

