

Specifications

Eaton 173026

Eaton Moeller® series M22 Combination of contact element and self-monitoring contact element M22-K01SMC10 with screw terminals, M22-A mounting adapter, and M22-XSMC signaling contact actuator, 1 N/O, 3 NC

General specifications

PRODUCT NAME	Eaton Moeller® series M22 Accessory Contact element
CATALOG NUMBER	173026
MODEL CODE	M22-AK03SMC10
EAN	4015081696178
PRODUCT LENGTH/DEPTH	40.2 mm
PRODUCT HEIGHT	32.5 mm
PRODUCT WIDTH	47 mm
PRODUCT WEIGHT	0.047 kg
CERTIFICATIONS	CSA-C22.2 No. 14-05 IEC 60947-5-1 IEC/EN 60947-5 UL CE UL 508 CSA Class No.: 3211-03 CSA-C22.2 No. 94-91 UL File No.: E340491 CSA CSA File No.: 012528_C_000 UL Category Control No.: NISD

Features & Functions

ELECTRIC CONNECTION TYPE	Screw connection
---------------------------------	------------------

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
--	--------

AMBIENT OPERATING TEMPERATURE - MAX	70 °C
--	-------

AMBIENT STORAGE TEMPERATURE - MIN	-25 °C
--	--------

AMBIENT STORAGE TEMPERATURE - MAX	85 °C
--	-------

CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
--------------------------	--

General

DEGREE OF PROTECTION	IP20
-----------------------------	------

MODEL	Top mounting
--------------	--------------

MOUNTING METHOD	Front fastening
------------------------	-----------------

OPERATING TORQUE	0.8 Nm
-------------------------	--------

OVERVOLTAGE CATEGORY	III
-----------------------------	-----

POLLUTION DEGREE	3
-------------------------	---

RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
---	-----------

Terminal capacities

TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	0.5 - 1.5 mm ²
--	---------------------------

TERMINAL CAPACITY (SOLID)	0.75 - 2.5 mm ²
----------------------------------	----------------------------

TERMINAL CAPACITY (STRANDED)	0.5 - 2.5 mm ²
-------------------------------------	---------------------------

Electrical rating

RATED INSULATION VOLTAGE (UI)	500 V
--------------------------------------	-------

RATED OPERATIONAL CURRENT (IE) AT AC-15, 115 V	6 A
---	-----

RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V	6 A
---	-----

RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V	4 A
---	-----

RATED OPERATIONAL CURRENT (IE) AT AC-15, 500 V	2 A
---	-----

RATED OPERATIONAL CURRENT (IE) AT DC-13, 110 V	0.6 A
---	-------

RATED OPERATIONAL CURRENT (IE) AT DC-13, 220 V, 230 V	0.3 A
--	-------

RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V	3 A
--	-----

RATED OPERATIONAL CURRENT (IE) AT DC-13, 42 V	1.7 A
--	-------

RATED OPERATIONAL CURRENT (IE) AT DC-13, 60 V	1.2 A
--	-------

RATED OPERATIONAL CURRENT (IE) AT DC-13, 500 V	0.1 A
---	-------

Communication

CONNECTION TO SMARTWIRE-DT	No
-----------------------------------	----

CONNECTION TYPE	Front fixing Screw connection
------------------------	----------------------------------

Short-circuit rating

SHORT-CIRCUIT PROTECTION	PKZM0-10/FAZ-B6/1, Contacts, Max. short-circuit protective device, Fuseless
---------------------------------	---

SHORT-CIRCUIT PROTECTION RATING	Max. 10 A gG/gL, Fuse, Contacts
--	---------------------------------

Actuator

ACTUATING FORCE - MAX	15 N
------------------------------	------

Contacts

**FORCE FOR POSITIVE
OPENING - MIN** 0 N

**NUMBER OF CONTACTS
(CHANGE-OVER
CONTACTS)** 0

**NUMBER OF CONTACTS
(NORMALLY CLOSED
CONTACTS)** 3

**NUMBER OF CONTACTS
(NORMALLY OPEN
CONTACTS)** 1

Design verification

**EQUIPMENT HEAT
DISSIPATION, CURRENT-
DEPENDENT PVID** 0 W

**HEAT DISSIPATION
CAPACITY PDISS** 0 W

**HEAT DISSIPATION PER
POLE, CURRENT-
DEPENDENT PVID** 0.11 W

**RATED OPERATIONAL
CURRENT FOR SPECIFIED
HEAT DISSIPATION (IN)** 6 A

**STATIC HEAT
DISSIPATION, NON-
CURRENT-DEPENDENT
PVS** 0 W

**10.2.2 CORROSION
RESISTANCE** Meets the product
standard's requirements.

**10.2.3.1 VERIFICATION OF
THERMAL STABILITY OF
ENCLOSURES** Meets the product
standard's requirements.

**10.2.3.2 VERIFICATION OF
RESISTANCE OF
INSULATING MATERIALS
TO NORMAL HEAT** Meets the product
standard's requirements.

**10.2.3.3 RESIST. OF
INSUL. MAT. TO
ABNORMAL HEAT/FIRE
BY INTERNAL ELECT.
EFFECTS** Meets the product
standard's requirements.

**10.2.4 RESISTANCE TO
ULTRA-VIOLET (UV)
RADIATION** Meets the product
standard's requirements.

10.2.5 LIFTING Does not apply, since the
entire switchgear needs to
be evaluated.

**10.2.6 MECHANICAL
IMPACT** Does not apply, since the
entire switchgear needs to
be evaluated.

10.2.7 INSCRIPTIONS Meets the product
standard's requirements.

**10.3 DEGREE OF
PROTECTION OF
ASSEMBLIES** Does not apply, since the
entire switchgear needs to
be evaluated.

**10.4 CLEARANCES AND
CREEPAGE DISTANCES** Meets the product
standard's requirements.

**10.5 PROTECTION
AGAINST ELECTRIC
SHOCK** Does not apply, since the
entire switchgear needs to
be evaluated.

10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

CATALOGUES

[eaton-rmq-titan-brochure-br047004en-en-us.pdf](#)

[Flip catalog - Product Range Catalog - Command and indication](#)

[eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf](#)

CERTIFICATION REPORTS

[000Z425](#)

CONTROL TRAVEL DIAGRAM

[eaton-operating-diagram-m22-contact-element-contact-travel-diagram-009.eps](#)

DECLARATIONS OF CONFORMITY

[eaton-accessory-declaration-of-conformity-uk251351en.pdf](#)

[eaton-accessory-declaration-of-conformity-eu250868en.pdf](#)

[DA-DC-00004971.pdf](#)

[DA-DC-00004134.pdf](#)

[DA-DC-00004157.pdf](#)

[DA-DC-00004176.pdf](#)

[DA-DC-00004135.pdf](#)

[DA-DC-00004975.pdf](#)

DRAWINGS

[eaton-general-standards-000Z425.jpg](#)

ECAD MODEL

[DA-CE-ETN.M22-AK03SMC10](#)

FLYERS

[eaton-rmq-titan-selection-aid-brochure-fl047002-en-us.pdf](#)

INSTALLATION INSTRUCTIONS

[IL04716002Z](#)

[IL04716005Z.pdf](#)

INSTALLATION VIDEOS

[RMQ Flat Design](#)

MULTIMEDIA

[MCI Multicolor Light Indicator M22 with SmartWire-DT](#)

[RMQ small E-Stop emergency-stop button](#)

[MCI MultiColor Light Indicator RMQ compact solution](#)

[easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator](#)

[eaton-control circuit-devices rmq-titan-fl144090en-en-us.pdf](#)

[eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf](#)

[eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf](#)

[eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf](#)

SALES NOTES

WIRING DIAGRAMS

[eaton-operating-m22-contact-element-wiring-diagram-003.eps](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

