

HC-B 16-SMLD-67/M1PG21 - Housing



1771684

<https://www.phoenixcontact.com/pc/products/1771684>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Box mounting base, with single locking latch, height 67 mm, with screw connection, 1x Pg21, with protective covers

Commercial data

Item number	1771684
Packing unit	10 pc
Minimum order quantity	1 pc
Product key	BF7AAC
Catalog page	Page 573 (PC-2011)
GTIN	4017918036409
Weight per piece (including packing)	408.3 g
Weight per piece (excluding packing)	394.07 g
Customs tariff number	85389099
Country of origin	DE

HC-B 16-SMLD-67/M1PG21 - Housing



1771684

<https://www.phoenixcontact.com/pc/products/1771684>

Technical data

Notes

General	For contact inserts HC-B16, BB32, BBB40, D40, DD72, HS6, M, K
---------	---

Product properties

Type	B16
Product type	Housing with locking latch
Application	Standard
No. of cable outlets	1
Type of the screw connection	1x Pg21
Housing type	Box mounting bases
Protective cover	yes
Shielded	no
Cable outlet	left (view of the opened single locking latch)
Pg screw connection	with

Dimensions

Dimensional drawing	
Width	57 mm
Height	67 mm
Length	117 mm
Wrench size, union nut	28 mm

Material specifications

Material Screw connection	Brass, nickel-plated
Material Protective cover	PA
Seal material Cable seal	NBR
Housing surface material	Powder-coated, gray
Locking latch material	Stainless steel, handle: PA
Housing material	die-cast aluminum

Mechanical properties

Mechanical data

Type of the screw connection	1x Pg21
Locking type	Latch

Cable/line

HC-B 16-SMLD-67/M1PG21 - Housing



1771684

<https://www.phoenixcontact.com/pc/products/1771684>

External cable diameter (Cable 1)	10 mm ... 19 mm
-----------------------------------	-----------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65 (When plugged in)
	IP54 (with closed protective cover)
Ambient temperature (operation)	-40 °C ... 125 °C

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com