HC-D 15-TFL-66/M1PG16G - Housing



https://www.phoenixcontact.com/za/products/1772353



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sleeve housing, for single locking latch, height 66 mm, with screw connection, 1x Pg16, straight cable entry

Commercial data

Item number	1772353
Packing unit	10 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	020
Product key	BF7AAE
Catalog page	Page 422 (C-4-2013)
GTIN	4017918037024
Weight per piece (including packing)	184,77 g
Weight per piece (excluding packing)	180,39 g
Customs tariff number	85389099
Country of origin	DE

HC-D 15-TFL-66/M1PG16G - Housing



https://www.phoenixcontact.com/za/products/1772353



Technical data

Notes

General	For contact inserts HC-D15, A10

Product properties

Туре	D15
Product type	Housing with locking latch
Application	Standard
No. of cable outlets	1
Type of the screw connection	1x Pg16
Housing type	Sleeve housing
Shielded	no
Cable outlet	straight
Pg screw connection	with

Dimensions

Dimensional drawing	63
Width	36 mm
Height	66 mm
Length	63 mm
Wrench size, union nut	22 mm

Material specifications

Material Screw connection	Brass, nickel-plated
Seal material Cable seal	NBR
Housing surface material	Powder-coated, gray
Housing material	die-cast aluminum

Mechanical properties

Mechanical data

Type of the screw connection	1x Pg16
Locking type	Pin

Cable/line

External cable diameter (Cable 1)	7.5 mm 15 mm

Environmental and real-life conditions

HC-D 15-TFL-66/M1PG16G - Housing



1772353

https://www.phoenixcontact.com/za/products/1772353

Ambient conditions

Degree of protection	IP65
Ambient temperature (operation)	-40 °C 125 °C

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (Pty) Ltd. 36 Lyn Road P.O. Box 916 ZA-Ferndale 2160

+27/11/801-8200 info@phoenixcontact.co.za