

HC-KA-B 24-ST/PER - Contact insert

1772913

<https://www.phoenixcontact.com/us/products/1772913>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



HEAVYCON terminal adapter male insert, B24 series, 24. pos., protective conductor connection on the right for the left side of the control cabinet, screw connection; contact inserts with screw, crimp, and QUICKON connections usable as mating connectors.

Commercial data

Item number	1772913
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	BF61
Product key	BF7ADC
Catalog page	Page 382 (PC-2007)
GTIN	4017918037529
Weight per piece (including packing)	196.03 g
Weight per piece (excluding packing)	196.03 g
Customs tariff number	85369010
Country of origin	DE

HC-KA-B 24-ST/PER - Contact insert



1772913
<https://www.phoenixcontact.com/us/products/1772913>

Technical data

Notes

General	For HEAVYCON ADVANCE panel mounting flange and HEAVYCON panel mounting base of type B24. Contact inserts with screw, crimp, and QUICKON connections can be used as mating connectors.
---------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Product properties

Type	B24
Product type	Terminal adapter
Number of positions	24
Connection profile	24+PE
Type	for the left side of the control cabinet

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated voltage (III/3)	400 V
Rated surge voltage	6 kV
Rated current	16 A

Connection data


Connection technology

Connection technology	Screw connection
Connection in acc. with standard	IEC / EN

Conductor connection

Conductor cross section	0.2 mm² ... 2.5 mm²
Connection cross section AWG	22 ... 12
Tightening torque	0.5 Nm ... 0.8 Nm
Stripping length of the individual wire	14 mm

Dimensions

Dimensional drawing	
Width	111 mm

HC-KA-B 24-ST/PER - Contact insert



1772913

<https://www.phoenixcontact.com/us/products/1772913>

Terminal adapter width	104 mm
Length	79 mm

Material specifications

Flammability rating according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Ag
Contact carrier material	PA/PC

Cable/line

Stripping length of the individual wire	14 mm
-----------------------------------------	-------

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 500
-----------------------------	-------

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

Mounting

Assembly instructions	Connectors may be operated only when there is no load/voltage.
-----------------------	----------------------------------------------------------------

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com