

1820987

https://www.phoenixcontact.com/pc/products/1820987

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Printed circuit board terminal, nominal current: 6 A, rated voltage (III/2): 160 V, nominal cross section: 0.5 mm², number of potentials: 8, number of rows: 1, number of positions per row: 8, product range: PTSM 0,5/..-H-SMD WH, pitch: 2.5 mm, connection method: Push-in spring connection, mounting: SMD soldering, conductor/PCB connection direction: 0 °, color: signal white, Pin layout: Linear pad geometry, number of solder pins per potential: 1, type of packaging: packed in cardboard. SAMPLE set with 5 items in belt section. When used as part of soldering process, please use items without SAMPLE marking

Your advantages

- · White design: Stable color when welding and during use
- · Time saving push-in connection, tools not required
- · Defined contact force ensures that contact remains stable over the long term
- · High current carrying capacity of 6 A in very compact dimensions
- · Designed for integration into the SMT soldering process
- Additional solder anchors reduce the mechanical strain on the soldering spots

Commercial data

Item number	1820987
Packing unit	5 pc
Minimum order quantity	5 pc
Note	Made to order (non-returnable)
Product key	AAKDAB
GTIN	4046356787666
Weight per piece (including packing)	2.29 g
Weight per piece (excluding packing)	2.22 g
Customs tariff number	85369010
Country of origin	DE



1820987

https://www.phoenixcontact.com/pc/products/1820987

Technical data

Product properties

Product type	Printed circuit board terminal
Product family	PTSM 0,5/H-SMD WH
Product line	COMBICON Terminals XS
Number of positions	8
Pitch	2.5 mm
Number of connections	8
Number of rows	1
Number of potentials	8
Pin layout	Linear pad geometry
Solder pins per potential	1
Data management status	
Article revision	00

Electrical properties

Nominal current I _N	6 A
Nominal voltage U _N	160 V
Rated voltage (III/3)	63 V
Rated surge voltage (III/3)	2.5 kV
Rated voltage (III/2)	160 V
Rated surge voltage (III/2)	2.5 kV
Rated voltage (II/2)	320 V
Rated surge voltage (II/2)	2.5 kV

Connection data

Connection technology

Nominal cross section	0.5 mm²
Nominal cross section	0.5 mm ²

Conductor connection

Conductor connection	
Connection method	Push-in spring connection
Conductor cross section rigid	0.14 mm² 0.5 mm²
Conductor cross section flexible	0.2 mm ² 0.5 mm ² (up to 0.75 mm ² supported, with a stripping length of 7.5 mm and a rated insulation voltage of 32 V at III/2)
Conductor cross section AWG	26 20
Conductor cross section flexible, with ferrule without plastic sleeve	0.25 mm² 0.5 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve	0.25 mm ² 0.34 mm ² (possible from 0.14 mm ² , when using ferrule AI 0.14- 6 GY in combination with crimping pliers CRIMPFOX 10T-F)
Cylindrical gauge a x b / diameter	- / 1.2 mm
Stripping length	6 mm



1820987

https://www.phoenixcontact.com/pc/products/1820987

Mounting

Mounting type	SMD soldering
Pin layout	Linear pad geometry
Processing notes	
Process	Reflow soldering
Moisture Sensitive Level	MSL 1
Classification temperature T _c	260 °C
Solder cycles in the reflow	3

Material specifications

Material data - contact

Note	WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact material	Cu alloy
Surface characteristics	hot-dip tin-plated
Metal surface terminal point (top layer)	Tin (4 - 8 µm Sn)
Metal surface soldering area (top layer)	Tin (4 - 8 μm Sn)

Material data - housing

Color (Housing)	signal white (9003)
Insulating material	PA GF
Insulating material group	I
CTI according to IEC 60112	600
Flammability rating according to UL 94	V0

Dimensions

Dimensional drawing	n p
Pitch	2.5 mm
Width [w]	21.9 mm
Height [h]	5.12 mm
Length [I]	11 mm
Installed height	5 mm
PCB design	
Pad geometry	1.4 x 3.4 mm
Pin spacing	2.5 mm

Mechanical tests



1820987

https://www.phoenixcontact.com/pc/products/1820987

Rated insulation voltage (III/3)

minimum clearance value - non-homogenous field (III/3)

Rated surge voltage (III/3)

Specification	IEC 60998-2-2:2002-12
Result	Test passed
Test for conductor damage and slackening	
Specification	IEC 60998-2-2:2002-12
Result	Test passed
Pull-out test	
Specification	IEC 60998-2-2:2002-12
Conductor cross section/conductor type/tractive force	0.14 mm² / solid / > 10 N
setpoint/actual value	0.2 mm² / flexible / > 10 N
	0.5 mm² / solid / > 20 N
	0.75 mm² / flexible / > 30 N
Flexion test	
Specification	IEC 60998-2-2:2002-12
Result	Test passed
Result ectrical tests	Test passed
	Test passed
ectrical tests	Test passed IEC 60998-2-1:2002-12
ectrical tests Temperature-rise test	
ectrical tests Temperature-rise test Specification	IEC 60998-2-1:2002-12
ectrical tests Temperature-rise test Specification Requirement temperature-rise test	IEC 60998-2-1:2002-12
ectrical tests Temperature-rise test Specification Requirement temperature-rise test Insulation resistance	IEC 60998-2-1:2002-12 Increase in temperature ≤ 45 K
ectrical tests Temperature-rise test Specification Requirement temperature-rise test Insulation resistance Specification Insulation resistance, neighboring positions	IEC 60998-2-1:2002-12 Increase in temperature ≤ 45 K IEC 60998-1:2002-12
ectrical tests Temperature-rise test Specification Requirement temperature-rise test Insulation resistance Specification Insulation resistance, neighboring positions Air clearances and creepage distances	IEC 60998-2-1:2002-12 Increase in temperature ≤ 45 K IEC 60998-1:2002-12
ectrical tests Temperature-rise test Specification Requirement temperature-rise test Insulation resistance Specification Insulation resistance, neighboring positions	IEC 60998-2-1:2002-12 Increase in temperature ≤ 45 K IEC 60998-1:2002-12 > 5 MΩ

minimum creepage distance (III/3)	1.6 mm
Rated insulation voltage (III/2)	160 V
Rated surge voltage (III/2)	2.5 kV
minimum clearance value - non-homogenous field (III/2)	1.5 mm
minimum creepage distance (III/2)	1.5 mm
Rated insulation voltage (II/2)	320 V
Rated surge voltage (II/2)	2.5 kV
minimum clearance value - non-homogenous field (II/2)	1.5 mm
minimum creepage distance (II/2)	1.6 mm

63 V

2.5 kV

1.5 mm



1820987

https://www.phoenixcontact.com/pc/products/1820987

Environmental and real-life conditions

Type of packaging

Specification	IEC 60068-2-6:2007-12
Frequency	10 - 150 - 10 Hz
Sweep speed	1 octave/min
Amplitude	0.35 mm (10 Hz 60.1 Hz)
Acceleration	5g (60.1 Hz 150 Hz)
Test duration per axis	2.5 h
Test directions	X-, Y- and Z-axis
ow-wire test Specification	IEC 60998-1:2002-12
Specification	IEC 60998-1:2002-12
Temperature	850 °C
Time of exposure	5 s
nbient conditions	
Ambient temperature (operation)	-40 °C 100 °C (Depending on the current carrying capacity/derating curve)
Ambient temperature (storage/transport)	-40 °C 70 °C
Relative humidity (storage/transport)	30 % 70 %
Relative numberly (Storage/transport)	

packed in cardboard





1820987

https://www.phoenixcontact.com/pc/products/1820987

Drawings

Dimensional drawing






Type: PTSM 0,5/...-2,5-H SMD WH (L) R.. Tested in accordance with DIN EN 60512-5-2:2003-01 Reduction factor = 1 Number of positions: 5



1820987

https://www.phoenixcontact.com/pc/products/1820987

Drilling plan/solder pad geometry





1820987

https://www.phoenixcontact.com/pc/products/1820987

Classifications

ECLASS

UNSPSC 21.0

	ECLASS-11.0	27460101	
	ECLASS-12.0	27460101	
	ECLASS-13.0	27460101	
ETIM			
	ETIM 9.0	EC002643	
UNSPSC			

39121400



1820987

https://www.phoenixcontact.com/pc/products/1820987

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions		
China RoHS			
Environment friendly use period (EFUP)	EFUP-E		
	No hazardous substances above the limits		
EU REACH SVHC			
REACH candidate substance (CAS No.)	No substance above 0.1 wt%		

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstraße 8 D-32825 Blomberg +49 (0) 5235-3 00 info@phoenixcontact.com