

# Specifications



## Eaton 182958

Eaton Moeller® series M30 Illuminated pushbutton actuator, RMQ-Titan, Flat, momentary, red, inscribed 0, Metal bezel

### General specifications

|                             |                                                                                                                                                                                                                                                           |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>PRODUCT NAME</b>         | Eaton Moeller® series M30 Illuminated pushbutton actuator                                                                                                                                                                                                 |
| <b>CATALOG NUMBER</b>       | 182958                                                                                                                                                                                                                                                    |
| <b>MODEL CODE</b>           | M30C-FDL-R-X0                                                                                                                                                                                                                                             |
| <b>EAN</b>                  | 4015081778850                                                                                                                                                                                                                                             |
| <b>PRODUCT LENGTH/DEPTH</b> | 36 mm                                                                                                                                                                                                                                                     |
| <b>PRODUCT HEIGHT</b>       | 30 mm                                                                                                                                                                                                                                                     |
| <b>PRODUCT WIDTH</b>        | 46 mm                                                                                                                                                                                                                                                     |
| <b>PRODUCT WEIGHT</b>       | 0.041 kg                                                                                                                                                                                                                                                  |
| <b>CERTIFICATIONS</b>       | VDE 0660<br>IEC/EN 60947<br>CSA File No.: 012528<br>CSA Class No.: 3211-03<br>DNV<br>UL File No.: E29184<br>GL<br>IEC/EN 60947-5<br>UL 508<br>CSA-C22.2 No. 14-05 and 94-M91<br>CE marking<br>UL Category Control No.: NKCR<br>UL Listed<br>CSA certified |
| <b>GLOBAL CATALOG</b>       | 182958                                                                                                                                                                                                                                                    |

## Product specifications

|                                            |                                                                                                                           |
|--------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| <b>TYPE</b>                                | Illuminated pushbutton actuator                                                                                           |
| <b>ACTUATOR COLOR</b>                      | Red                                                                                                                       |
| <b>FEATURES</b>                            | Labelled                                                                                                                  |
| <b>ACTUATOR FUNCTION</b>                   | Spring-return<br>Momentary                                                                                                |
| <b>FITTED WITH:</b>                        | Front ring                                                                                                                |
| <b>OPERATING FREQUENCY</b>                 | 3600 Operations/h                                                                                                         |
| <b>CLIMATIC PROOFING</b>                   | Damp heat, cyclic, to IEC 60068-2-30<br>Damp heat, constant, to IEC 60068-2-78                                            |
| <b>CONNECTION TO SMARTWIRE-DT</b>          | With SWD-RMQ connections<br>Yes                                                                                           |
| <b>ACTUATING FORCE</b>                     | 5 N                                                                                                                       |
| <b>AMBIENT OPERATING TEMPERATURE - MAX</b> | 70 °C                                                                                                                     |
| <b>AMBIENT OPERATING TEMPERATURE - MIN</b> | -25 °C                                                                                                                    |
| <b>FORCE FOR POSITIVE OPENING - MIN</b>    | 0 N                                                                                                                       |
| <b>NUMBER OF COMMAND POSITIONS</b>         | 1                                                                                                                         |
| <b>OPENING DIAMETER</b>                    | 30.5 mm                                                                                                                   |
| <b>OPENING HEIGHT</b>                      | 0 mm                                                                                                                      |
| <b>BEZEL COLOR</b>                         | Titanium                                                                                                                  |
| <b>SHOCK RESISTANCE</b>                    | 15 g, Mechanical,<br>According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms<br>Mechanical, According to IEC/EN 60068-2-27 |
| <b>BEZEL MATERIAL</b>                      | Metal                                                                                                                     |
| <b>DESIGN</b>                              | Flat<br>Flat front                                                                                                        |
| <b>MOUNTING POSITION</b>                   | As required                                                                                                               |
| <b>DEGREE OF PROTECTION</b>                | IP66<br>IP67<br>IP69K                                                                                                     |
| <b>DEGREE OF PROTECTION (FRONT SIDE)</b>   | IP67/IP69K<br>NEMA 4X, 13                                                                                                 |
| <b>INSCRIPTION</b>                         | Inscribed                                                                                                                 |
| <b>FRONT ELEMENT TYPE</b>                  | Flat                                                                                                                      |
| <b>LENS TYPE</b>                           | Round                                                                                                                     |

## Resources

### CATALOGS

[eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf](#)

[eaton-rmq-titan-brochure-br047004en-en-us.pdf](#)

[Flip catalog - Product Range Catalog - Command and indication](#)

### DECLARATIONS OF CONFORMITY

[eaton-key-operated-actuator-declaration-of-conformity-eu250864en.pdf](#)

[eaton-key-operated-actuator-declaration-of-conformity-eu250863en.pdf](#)

[eaton-operating-m30-dimensions-005.eps](#)

[eaton-operating-m30-dimensions-006.eps](#)

[eaton-operating-m30-dimensions-004.eps](#)

[eaton-operating-m30-dimensions.eps](#)

### DRAWINGS

[eaton-general-m22-symbol.eps](#)

[eaton-operating-m30-3d-drawing.eps](#)

[eaton-operating-button-m22-symbol-011.eps](#)

[eaton-general-approval-m22-symbol.eps](#)

### ECAD MODEL

[ETN.182958.edz](#)

### FLYERS

[eaton-rmq-titan-selection-aid-brochure-fl047002-en-us.pdf](#)

### INSTALLATION INSTRUCTIONS

[eaton-operating-devices-m30-rmq-titan-flat-front-instruction-leaflet-il047019zu.pdf](#)

### INSTALLATION VIDEOS

[RMQ Flat Design](#)

|                      |                           |
|----------------------|---------------------------|
| LIFESPAN, MECHANICAL | 5,000,000 Operations      |
| WIDTH OPENING        | 0 mm                      |
| PRODUCT CATEGORY     | RMQ-Titan                 |
| SIZE                 | Front dimensions: Ø 36 mm |
| SUITABLE FOR         | Illumination              |

|             |                                                                                                                                                                                                                                                                                                                  |
|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MCAD MODEL  | <a href="#">DA-CD-drucktaste_flach_flatfront</a><br><a href="#">DA-CS-drucktaste_flach_flatfront</a>                                                                                                                                                                                                             |
| MULTIMEDIA  | <a href="#">MCI Multicolor Light Indicator M22 with SmartWire-DT</a><br><a href="#">easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator</a><br><a href="#">RMQ small E-Stop emergency-stop button</a><br><a href="#">MCI MultiColor Light Indicator RMQ compact solution</a>      |
| SALES NOTES | <a href="#">eaton-control circuit-devices rmq-titan-fl144090en-en-us.pdf</a><br><a href="#">eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf</a><br><a href="#">eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf</a><br><a href="#">eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf</a> |

|                 |
|-----------------|
| PROJECT NAME:   |
| PROJECT NUMBER: |
| PREPARED BY:    |
| DATE:           |



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

Follow us on social media to get the latest product and support information.

