

Specifications



Eaton 183777

Eaton Moeller series IZMX/INX - ACB. Circuit-breaker, 4p, 3200A, 105 kA, P measurement, IEC, Fixed

General specifications

PRODUCT NAME	Eaton Moeller series IZMX/INX circuit-breaker
CATALOG NUMBER	183777
MODEL CODE	IZMX40H4-P32F-1
EAN	4015081795130
PRODUCT LENGTH/DEPTH	584 mm
PRODUCT HEIGHT	597 mm
PRODUCT WIDTH	521 mm
PRODUCT WEIGHT	56 kg
COMPLIANCES	IEC/EN 60947 IEC RoHS conform
GLOBAL CATALOG	183777

Product specifications

USED WITH	Open circuit breaker Air circuit breakers/switch-disconnector
AMPERAGE RATING	3200 A
FEATURES	Complete device with protection unit Motor drive optional
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL	Does not apply, since the

Resources

CATALOGS	eaton-acb-izm63-catalog-ca0135003en-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-circuit-breaker-declaration-of-conformity-eu250301en.pdf
DRAWINGS	eaton-circuit-breaker-mounting-izmx-inx-mccb-dimensions.eps
	eaton-circuit-breaker-izmx-inx-mccb-dimensions-013.eps
	eaton-circuit-breaker-mounting-izmx-inx-mccb-dimensions-002.eps
ECAD MODEL	DA-CE-ETN.IZMX40H4-P32F-1
INSTALLATION VIDEOS	Air Circuit Breakers Series IZMX
MANUALS AND USER GUIDES	MN013002_EN
MCAD MODEL	DA-CD-izmx40_4pol_f
	DA-CS-izmx40_4pol_f

IMPACT	entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
FITTED WITH:	Switched-off indicator
FRAME	IZMX40
POLLUTION DEGREE	3
RATED UNINTERRUPTED CURRENT (IU)	3200 A
MOUNTING METHOD	Fixed
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT	385 W
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	12 kV AC
UTILIZATION CATEGORY	B
DEVICE CONSTRUCTION	Built-in device fixed built-in technique
DIRECTION OF INCOMING SUPPLY	As required
ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT	Rail connection

ACTUATOR TYPE	Push button
SHORT-CIRCUIT RELEASE	1.5 - 10 x I_r
NON-DELAYED SETTING	
ADJUSTMENT RANGE	
SHORT-TERM DELAYED	32000 A
SHORT-CIRCUIT RELEASE	
- MAX	
ADJUSTMENT RANGE	
SHORT-TERM DELAYED	1920 A
SHORT-CIRCUIT RELEASE	
- MIN	
ADJUSTMENT RANGE	
UNDELAYED SHORT-	48000 A
CIRCUIT RELEASE - MAX	
ADJUSTMENT RANGE	
UNDELAYED SHORT-	6400 A
CIRCUIT RELEASE - MIN	
AMBIENT OPERATING	70 °C
TEMPERATURE - MAX	
AMBIENT OPERATING	-20 °C
TEMPERATURE - MIN	
AMBIENT STORAGE	70 °C
TEMPERATURE - MAX	
AMBIENT STORAGE	-20 °C
TEMPERATURE - MIN	
HEAT DISSIPATION AT	
RATED CURRENT WITH	385 W
FIXED MOUNTING	
NUMBER OF AUXILIARY	
CONTACTS (CHANGE-	2
OVER CONTACTS)	
NUMBER OF AUXILIARY	
CONTACTS (NORMALLY	0
CLOSED CONTACTS)	
NUMBER OF AUXILIARY	
CONTACTS (NORMALLY	0
OPEN CONTACTS)	
NUMBER OF STANDARD	
MECHANICAL	
OPERATIONS PER HOUR -	60
MAX	
OPERATING SEQUENCE	
UP TO 690 V, 50/60 HZ	85 kA
(IEC/EN 60947)	
OVERLOAD RELEASE	
CURRENT SETTING - MAX	3200 A
OVERLOAD RELEASE	
CURRENT SETTING - MIN	1280 A
RATED INSULATION	1000 V

VOLTAGE (UI)	20000 operations (switching capacity, with maintenance)
LIFESPAN, MECHANICAL	10000 switching cycles (ON/OFF)
OVERVOLTAGE CATEGORY	III
SHORT-CIRCUIT RELEASE	
NON-DELAYED SETTING -	0 A
MIN	
WEIGHT OF FIXED MOUNTING VERSION (4- POLE)	56 kg
AMBIENT OPERATING TEMPERATURE DETAILS	-20 °C - 70 °C
PROTECTION	P measurement
VOLTAGE RATING AT AC	690 V AC
SHORT-CIRCUIT RELEASE	
NON-DELAYED SETTING -	48000 A
MAX	
SHORT-CIRCUIT RELEASE DELAYED SETTING - MAX	32000 A
NUMBER OF POLES	Four-pole
DEGREE OF PROTECTION	IP31 IP31 with door seals IP55 with protective cover
CLOSING DELAY VIA SPRING RELEASE	35 ms
LIFESPAN, ELECTRICAL	5000 operations (switching capacity) 10000 operations (switching cycles ON/OFF, with maintenance)
TYPE	<ul style="list-style-type: none"> • Air circuit breakers/switch- disconnector • Open circuit breaker
SPECIAL FEATURES	<ul style="list-style-type: none"> • External IZMX-DTP- PTM-1 voltage measuring module required (1 module is suitable for 16 circuit breakers) • suitable for zone selectivity • suitable for

communication

- with integrated system monitor
- with integrated test possibility
- With graphic LCD display
- optionally fittable by user with comprehensive accessories
- Terminal capacity hint: These are values used in separate switchgear. The actual values will depend on the temperature around the circuit breaker, which is influenced by the ambient temperature, the degree of protection (IP), the mounting height, the partitions, and any external ventilation.
- Depending on the specific switchgear design, this may result in derating, which can then be compensated for by increasing the cross-sectional area. Temperature rise tests in the specific switchgear can provide specific and detailed information.

**POSITION OF
CONNECTION FOR MAIN
CURRENT CIRCUIT** Back side

RELEASE SYSTEM Electronic release

**RATED OPERATING
VOLTAGE (UE) - MAX** 690 V

**RATED OPERATING
VOLTAGE (UE) - MIN** 690 V

RATED OPERATIONAL 3200 A

**CURRENT FOR SPECIFIED
HEAT DISSIPATION (IN)**

**RATED SHORT-CIRCUIT
BREAKING CAPACITY AT** 105 kA
400 V, 50 HZ

**RATED SHORT-CIRCUIT
MAKING CAPACITY UP TO** 231 kA
440 V, 50/60 HZ

**RATED SHORT-CIRCUIT
MAKING CAPACITY UP TO** 166 kA
690 V, 50/60 HZ

**RATED SHORT-TIME
WITHSTAND CURRENT (T = 1 S)** 85 kA

**RATED SHORT-TIME
WITHSTAND CURRENT AT 50/60 HZ (T = 3 S)** 66 kA

**RATED UNINTERRUPTED
CURRENT (IU) AT 50°C** 3200 A

**RATED UNINTERRUPTED
CURRENT (IU) AT 60°C** 3200 A

**RATED UNINTERRUPTED
CURRENT (IU) AT 70°C** 3200 A

**SHORT-CIRCUIT RELEASE
DELAYED SETTING - MIN** 2400 A

**TERMINAL CAPACITY
(COPPER BAR)** 80 mm x 10 mm (3x) for
fixed mounting (black)

POWER LOSS 385 W

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the
latest product and support
information.

