


Specifications



Eaton 184112

Eaton Moeller series IZMX/INX - ACB.
Undervoltage release 60 VDC

General specifications

PRODUCT NAME	Eaton Moeller series IZMX/INX undervoltage release
CATALOG NUMBER	184112
MODEL CODE	IZMX-UVR60DC-1
EAN	4015081783168
PRODUCT LENGTH/DEPTH	150 mm
PRODUCT HEIGHT	100 mm
PRODUCT WIDTH	100 mm
PRODUCT WEIGHT	0.091 kg
COMPLIANCES	RoHS conform
GLOBAL CATALOG	184112

Product specifications

USED WITH	INX16..., INX40... IZMX16..., IZMX40...
ELECTRIC CONNECTION TYPE	Flat plug-in connection
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX	0 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN	0 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX	0 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN	0 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX	60 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN	60 V
ACCESSORY/SPARE PART TYPE	Remote switching
CURRENT RATING - MAX	0.07 A (maximum holding current)
PICK-UP POWER CONSUMPTION AT 35 MS - MAX	890 VA/W
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
NUMBER OF ACTUATION PER MINUTE - MAX	3
NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	0
VOLTAGE TYPE	DC
CIRCUIT BREAKER TOTAL SWITCHING TIME	40 ms (Us = 100%) (IZMX40..., INX40...)

Resources

CATALOGS	eaton-acb-izm63-catalog-ca0135003en-en-us.pdf
DRAWINGS	eaton-circuit-breaker-izm-x-inx-acb-3d-drawing-010.eps
ECAD MODEL	DA-CE-ETN.IZMX-UVR60DC-1
INSTALLATION INSTRUCTIONS	eaton-izm-x16-izm-x40-uvr-st-ots-il0131087en-z.pdf
INSTALLATION VIDEOS	Air Circuit Breakers Series IZMX

	50 ms (Us = 100%) (IZMX16..., INX16...)
CONTROL VOLTAGE	60 V DC
OPERATING RANGE	0.85 - 1.1 x Us
TYPE	Accessory
SPECIAL FEATURES	<ul style="list-style-type: none"> • Cannot be combined with a second shunt release. • Retrofitting kit • Slot on the right on the adapter plate. • Limited to 3/min due to the high pick-up current for 35 ms. • Please note - the circuit-breaker's switching frequency = 60/h • The retrofit kit includes the required SEC control cable terminals.
POWER CONSUMPTION	5 VA/W AC/DC
RATED OPERATIONAL CURRENT	0.07 A (maximum holding current)
SUITABLE FOR	Power circuit breaker Motor safety switch Off-load switch Overload relay

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

