

Specifications

Eaton 185145



Eaton Moeller® series C22 Indicator light, Flat, Cable (black) with non-terminated end, 4 pole, 3.5 m, Lens green, LED green, 24 V AC/DC

Photo is representative



General specifications

PRODUCT NAME	Eaton Moeller® series C22 Indicator light
CATALOG NUMBER	185145
MODEL CODE	C22-L-G-24-P65
EAN	4015081806270
PRODUCT LENGTH/DEPTH	3561 mm
PRODUCT HEIGHT	30 mm
PRODUCT WIDTH	30 mm
PRODUCT WEIGHT	0.12 kg
CERTIFICATIONS	CE CSA IEC/EN 60947-5-1 UL VDE 0660

Features & Functions

BEZEL COLOR	Other
BEZEL MATERIAL	Plastic
DESIGN	Cable end open Flat
ELECTRIC CONNECTION TYPE	Other
FITTED WITH:	Light source Front ring
LENS COLOR	Green
LIGHT COLOR	Green

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MIN	-30 °C
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78

Actuator

ACTUATOR DIAMETER	4.7 mm
--------------------------	--------

General

CABLE LENGTH	3.5 m
CABLE MATERIAL	PUR
CONNECTION TO SMARTWIRE-DT	No
CONNECTION TYPE	Cable (black) with non-terminated end, 4 pole
DEGREE OF PROTECTION	IP Other NEMA Other
MOUNTING POSITION	As required
OPENING DIAMETER	22.5 mm
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	RMQ compact solution
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	800 V AC
SHOCK RESISTANCE	30 g, Mechanical, Shock duration 11 ms
TIGHTENING TORQUE	2 Nm, Threaded ring
TYPE	Indicator lights
VOLTAGE TYPE	AC/DC

Electrical rating

RATED CONDITIONAL SHORT-CIRCUIT CURRENT (IQ)	1 kA
RATED INSULATION VOLTAGE (UI)	30 V
RATED OPERATIONAL VOLTAGE	24 V AC/DC (LED)
RATED OPERATIONAL VOLTAGE (UE) - MIN	24 V
RATED OPERATIONAL VOLTAGE (UE) - MAX	24 V
SHORT-CIRCUIT PROTECTION RATING	Max. 4 A gG/gL, Fuse, Contacts

Resources

CATALOGUES	eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf
DECLARATIONS OF CONFORMITY	DA-DC-00004157.pdf DA-DC-00004135.pdf
DRAWINGS	eaton-operating-c22-indicator-light-dimensions-003.eps eaton-operating-c22-pushbutton-3d-drawing.eps eaton-operating-button-symbol-004.eps
ECAD MODEL	DA-CE-ETN.C22-L-G-24-P65
FLYERS	eaton-rmq-titan-selection-aid-brochure-fl047002-en-us.pdf
INSTALLATION INSTRUCTIONS	IL047016ZU
INSTALLATION VIDEOS	Eaton's RMQ compact solution pilot devices
MCAD MODEL	DA-CD-c22 open cable DA-CS-c22 open cable
SALES NOTES	eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf
WIRING DIAGRAMS	eaton-operating-c22-indicator-light-wiring-diagram-003.eps

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

