

Specifications

Photo is representative

Eaton 185171

Eaton Moeller® series C22 Emergency stop/emergency switching off pushbutton, Mushroom-shaped, 38 mm, Pull-to-release function, 1 NC, 1 N/O, Cable (black) with M12A plug, 4 pole, 0.2 m

General specifications

PRODUCT NAME	Eaton Moeller® series C22 Emergency stop/emergency switching off pushbutton
CATALOG NUMBER	185171
MODEL CODE	C22-PV-K11-P1
EAN	4015081806560
PRODUCT LENGTH/DEPTH	297 mm
PRODUCT HEIGHT	38 mm
PRODUCT WIDTH	38 mm
PRODUCT WEIGHT	0.061 kg
CERTIFICATIONS	CE CSA UL VDE 0660 IEC/EN 60947-5-5 CSA Class No.: 321103 CSA File No.: 165628 IEC/EN 60947-5-1 UL 508 CSA-C22.2 No. 14-10 CSA-C22.2 No. 94-91 CSA-C22.2 No. 94.2-07 CE marking UL File No.: E340491
CATALOG NOTES	Contacts with safety function, by positive opening to IEC/EN 60947-5-1
GLOBAL CATALOG	185171

Product specifications

TYPE	Controlled stop pushbutton/emergency-stop button
ACTUATOR COLOR	Red
FEATURES	Tamper-proof (according to ISO 13850, EN 418) Positive opening
ACTUATOR FUNCTION	Pull-to-release
OPERATING FREQUENCY	300 Operations/h
POLLUTION DEGREE	3
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
CONNECTION TO SMARTWIRE-DT	No
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	800 V AC
ILLUMINATION	Non-illuminated
CABLE MATERIAL	PUR
BASE COLOR	Yellow
ACTUATING FORCE	50 N
ACTUATOR DIAMETER	38 mm
ACTUATOR TRAVEL AND ACTUATION FORCE (DIN EN 60947-5-1)	4.65 mm
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-30 °C
DIAMETER CAP	38 mm
FORCE FOR POSITIVE OPENING - MIN	20 N
KNOB TRAVEL	5.7 mm
LAMP VOLTAGE - MAX	0 V
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	1
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	1
DESIGN	M12A Mushroom-shaped Classical

Resources

CATALOGS	eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf
CONTROL TRAVEL DIAGRAM	eaton-operating-circuit-pushbutton-contact-travel-diagram.eps
DECLARATIONS OF CONFORMITY	DA-DC-00004177.pdf DA-DC-00004138.pdf
DRAWINGS	eaton-operating-c22-dimensions-003.eps eaton-operating-3d-drawing-003.eps eaton-operating-button-symbol-006.eps
ECAD MODEL	DA-CE-ETN.C22-PV-K11-P1
FLYERS	eaton-rmq-titan-selection-aid-brochure-fl047002-en-us.pdf
INSTALLATION INSTRUCTIONS	IL047010ZU.pdf
INSTALLATION VIDEOS	Eaton's RMQ compact solution pilot devices
MCAD MODEL	DA-CD-c22_pv_m12a_4pol DA-CS-c22_pv_m12a_4pol
SALES NOTES	eaton-rmq-c22-compact-pilot-device-flyer-fl047013en-en-us.pdf eaton-rmq-compact-solution-flyer-fl047001en-en-us.pdf eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf
WIRING DIAGRAMS	eaton-operating-wiring-diagram-007.eps

MOUNTING POSITION	As required
RATED CONDITIONAL SHORT-CIRCUIT CURRENT (IQ)	1 kA
CONNECTION TYPE	Cable (black) with M12A plug, 4 pole
MOUNTING METHOD	Built-in
CABLE LENGTH	0.2 m
OVERVOLTAGE CATEGORY	III
CONTROL CIRCUIT RELIABILITY	1 failure per 17,000,000 swtching operations (statistically determined, at 17 V DC/7 mA: N/O contact 1 failure per 900,000 switching operations statistically determined, at 17 V DC/7 mA: N/C contact)
CONNECTION TYPE (AUXILIARY CIRCUIT)	Other
DEGREE OF PROTECTION	NEMA 4X, 13 IP66
SHOCK RESISTANCE	30 g, Mechanical, Shock duration 11 ms
LIFESPAN, MECHANICAL	50,000 operations
UNLOCKING METHOD	Pull-release
SHORT-CIRCUIT PROTECTION RATING	Max. 4 A gG/gL, Fuse, Contacts
OPENING DIAMETER	22.5 mm
RATED INSULATION VOLTAGE (UI)	250 V
RATED OPERATIONAL CURRENT (IE) AT AC-15, 24 V	4 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V	3 A
PRODUCT CATEGORY	RMQ compact solution
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
AMBIENT STORAGE TEMPERATURE - MIN	30 °C
TIGHTENING TORQUE	1 Nm, Plug 2 Nm, Threaded ring

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

