

Specifications

Eaton 185957

Eaton Moeller® series C30 Indicator light, Flat, Cable (black) with non-terminated end, 4 pole, 1 m, Lens white, LED white, 24 V AC/DC

General specifications

PRODUCT NAME	Eaton Moeller® series C30 Indicator light
CATALOG NUMBER	185957
MODEL CODE	C30C-FL-W-24-P62
EAN	4015081814589
PRODUCT LENGTH/DEPTH	1060 mm
PRODUCT HEIGHT	46 mm
PRODUCT WIDTH	36 mm
PRODUCT WEIGHT	0.063 kg
CERTIFICATIONS	IEC/EN 60947-5-1 VDE 0660
GLOBAL CATALOG	185957

Product specifications

TYPE	Indicator lights
PRODUCT CATEGORY	RMQ compact solution
ELECTRIC CONNECTION TYPE	Other
FITTED WITH:	Light source Front ring
POLLUTION DEGREE	3
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
CONNECTION TO SMARTWIRE-DT	No
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	800 V AC
BEZEL COLOR	Chrome
CABLE MATERIAL	PUR
LAMP SOCKET TYPE	LED
ACTUATOR DIAMETER	4.7 mm
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
NUMBER OF PILOT LIGHTS	1
OPENING DIAMETER	30 mm
OPENING HEIGHT	0 mm
RATED INSULATION VOLTAGE (UI)	30 V
RATED OPERATIONAL VOLTAGE (UE) - MAX	24 V
BEZEL MATERIAL	Metal
DEGREE OF PROTECTION	IP Other NEMA Other
LENS COLOR	White
VOLTAGE TYPE	AC/DC
DESIGN	Cable end open Flat
MOUNTING POSITION	As required
LIGHT COLOR	White
RATED CONDITIONAL SHORT-CIRCUIT CURRENT (IQ)	1 kA

Resources

CATALOGS	eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf
DECLARATIONS OF CONFORMITY	DA-DC-00004135.pdf DA-DC-00004157.pdf
DRAWINGS	eaton-operating-c30-indicator-light-dimensions-002.eps eaton-operating-c30-indicator-light-3d-drawing-002.eps eaton-operating-button-symbol-013.eps
ECAD MODEL	DA-CE-ETN.C30C-FL-W-24-P62
FLYERS	eaton-rmq-titan-selection-aid-brochure-fl047002-en-us.pdf
INSTALLATION INSTRUCTIONS	IL047021ZU
INSTALLATION VIDEOS	Eaton's RMQ compact solution pilot devices
MCAD MODEL	DA-CS-c30 I open cable DA-CD-c30 I open cable
SALES NOTES	eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf
WIRING DIAGRAMS	eaton-operating-c22-indicator-light-wiring-diagram-003.eps

RATED OPERATIONAL VOLTAGE (UE) - MIN	24 V
WIDTH OPENING	0 mm
OVERVOLTAGE CATEGORY	III
CABLE LENGTH	1 m
CONNECTION TYPE	Cable (black) with non-terminated end, 4 pole
LENS TYPE	Round Flat
SHOCK RESISTANCE	30 g, Mechanical, Shock duration 11 ms
RATED OPERATIONAL VOLTAGE	24 V AC/DC (LED)
SHORT-CIRCUIT PROTECTION RATING	Max. 4 A gG/gL, Fuse, Contacts
TIGHTENING TORQUE	2 Nm, Threaded ring

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

