

# Specifications



Photo is representative



## Eaton 186276

Eaton Moeller® series C22 Key-operated actuator, RMQ compact solution, maintained, 1 NC, 1 N/O, Cable (black) with non-terminated end, 4 pole, 3.5 m, 2 positions, MS1, Bezel: titanium

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller® series C22 Key-operated actuator
<b>CATALOG NUMBER</b>	186276
<b>MODEL CODE</b>	C22-WRS-MS1-K11-P65
<b>EAN</b>	4015081817771
<b>PRODUCT LENGTH/DEPTH</b>	3597 mm
<b>PRODUCT HEIGHT</b>	30 mm
<b>PRODUCT WIDTH</b>	30 mm
<b>PRODUCT WEIGHT</b>	0.143 kg
<b>CERTIFICATIONS</b>	UL IEC/EN 60947-5-1 CSA CE VDE 0660 CSA File No.: 165628 CSA Class No.: 321103 UL File No.: E29184 UL 508 CSA-C22.2 No. 14-18 and No. 94.2-15 CE marking UL Category Control No.: NKCR UL listed, CSA certified
<b>GLOBAL CATALOG</b>	186276



Powering Business Worldwide

## Product specifications

<b>TYPE</b>	Key-operated button
<b>ACCESSORIES</b>	1 key included with supplied equipment.
<b>ACTUATOR COLOR</b>	Black
<b>PRODUCT CATEGORY</b>	RMQ compact solution
<b>FEATURES</b>	Positive opening
<b>ACTUATOR FUNCTION</b>	Maintained Key withdrawable in position 0 Switching function latching  Key withdrawable in position 1
<b>ELECTRIC CONNECTION TYPE</b>	Other
<b>FITTED WITH:</b>	Front ring
<b>OPERATING FREQUENCY</b>	100 Operations/h
<b>POLLUTION DEGREE</b>	3
<b>CLIMATIC PROOFING</b>	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
<b>CONNECTION TO SMARTWIRE-DT</b>	No
<b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b>	800 V AC
<b>ACTUATOR TYPE</b>	Key
<b>ACTUATOR DIAMETER</b>	4.7 mm
<b>ACTUATOR TRAVEL AND ACTUATION FORCE (DIN EN 60947-5-1)</b>	4.65 mm
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	70 °C
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-30 °C
<b>FORCE FOR POSITIVE OPENING - MIN</b>	20 N
<b>KNOB TRAVEL</b>	5.7 mm
<b>NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)</b>	0
<b>NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)</b>	1
<b>NUMBER OF CONTACTS</b>	1

## Resources

<b>CATALOGS</b>	<a href="#">eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf</a>
<b>CONTROL TRAVEL DIAGRAM</b>	<a href="#">eaton-operating-circuit-pushbutton-contact-travel-diagram.eps</a>
<b>DECLARATIONS OF CONFORMITY</b>	<a href="#">DA-DC-00004135.pdf</a> <a href="#">DA-DC-00004157.pdf</a>
<b>DRAWINGS</b>	<a href="#">eaton-operating-c22-key-operated-actuator-dimensions.eps</a> <a href="#">eaton-operating-c22-key-operated-actuator-3d-drawing.eps</a>
<b>ECAD MODEL</b>	<a href="#">DA-CE-ETN.C22-WRS-MS1-K11-P65</a>
<b>FLYERS</b>	<a href="#">eaton-rmq-titan-selection-aid-brochure-fl047002-en-us.pdf</a>
<b>INSTALLATION INSTRUCTIONS</b>	<a href="#">IL047016ZU</a>
<b>INSTALLATION VIDEOS</b>	<a href="#">Eaton's RMQ compact solution pilot devices</a>
<b>MCAD MODEL</b>	<a href="#">DA-CD-c22_ws_open_cable</a> <a href="#">DA-CS-c22_ws_open_cable</a>
<b>SALES NOTES</b>	<a href="#">eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf</a>
<b>WIRING DIAGRAMS</b>	<a href="#">eaton-operating-wiring-diagram-005.eps</a>

<b>(NORMALLY OPEN CONTACTS)</b>	
<b>OPENING DIAMETER</b>	22.5 mm
<b>OPENING HEIGHT</b>	0 mm
<b>OPERATING TORQUE</b>	0.5 Nm
<b>RATED INSULATION VOLTAGE (UI)</b>	250 V
<b>RATED OPERATIONAL CURRENT (IE) AT AC-15, 24 V</b>	4 A
<b>RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V</b>	3 A
<b>BEZEL COLOR</b>	Titanium
<b>CABLE MATERIAL</b>	PUR
<b>KEY CODE</b>	MS1
<b>BEZEL MATERIAL</b>	Plastic
<b>DESIGN</b>	Cable end open Classical
<b>MOUNTING POSITION</b>	As required
<b>RATED CONDITIONAL SHORT-CIRCUIT CURRENT (IQ)</b>	1 kA
<b>CABLE LENGTH</b>	3.5 m
<b>CONNECTION TYPE</b>	Cable (black) with non-terminated end, 4 pole
<b>OVERVOLTAGE CATEGORY</b>	III
<b>CONTROL CIRCUIT RELIABILITY</b>	1 failure per 900,000 switching operations statistically determined, at 17 V DC/7 mA: N/C contact) 1 failure per 17,000,000 switching operations (statistically determined, at 17 V DC/7 mA: N/O contact
<b>DEGREE OF PROTECTION</b>	IP66 IP65, rear NEMA Other
<b>SHOCK RESISTANCE</b>	30 g, Mechanical, Shock duration 11 ms
<b>NUMBER OF SWITCH POSITIONS</b>	2
<b>TIGHTENING TORQUE</b>	2 Nm, Threaded ring
<b>SHORT-CIRCUIT PROTECTION RATING</b>	Max. 4 A gG/gL, Fuse, Contacts

SUPPLY VOLTAGE - MAX	0 V
SUPPLY VOLTAGE - MIN	0 V
SWITCHING ANGLE	60 °
WIDTH OPENING	0 mm

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

