

1868720

<https://www.phoenixcontact.com/us/products/1868720>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



PCB terminal block, number of positions per row: 3, product range: MK3DS 1,5, pitch: 5.08 mm, screw head form: L Slotted, color: green-yellow, Pin layout: Linear pinning, Solder pin [P]: 3.5 mm, type of packaging: packed in cardboard. The article can be aligned to create different nos. of positions!

Commercial data

Item number	1868720
Packing unit	50 pc
Minimum order quantity	50 pc
Note	Made to order (non-returnable)
Sales key	AA12
Product key	AALFJA
Catalog page	Page 99 (C-1-2013)
GTIN	4017918141868
Weight per piece (including packing)	18.34 g
Weight per piece (excluding packing)	11.648 g
Customs tariff number	85369010
Country of origin	DE

MK3DS 1,5/ 3-5,08-A-GNYYE - PCB terminal block



1868720

<https://www.phoenixcontact.com/us/products/1868720>

Technical data

Product properties

Product type	Printed circuit board terminal
Product family	MK3DS 1,5
Type	PC terminal block can be aligned
Number of positions	3
Pitch	5.08 mm
Pin layout	Linear pinning

Electrical properties

Maximum load current	17.5 A (with a 2.5 mm² conductor cross section)
Rated voltage (II/2)	630 V
Rated voltage (III/2)	400 V
Rated surge voltage (II/2)	4 kV
Rated surge voltage (III/2)	4 kV
Rated surge voltage (III/3)	4 kV

Mounting

Mounting type	Wave soldering
Pin layout	Linear pinning
Drive form screw head	Slotted (L)

Material specifications

Color	green-yellow
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA
Contact surface	Tin Sn

Dimensions

Dimensional drawing	
Width	17.78 mm
Installed height	37 mm
Height	36.6 mm
Length of the solder pin	3.5 mm
Length	32.25 mm
Length of the solder pin	3.5 mm
Hole diameter	1.3 mm

MK3DS 1,5/ 3-5,08-A-GNYE - PCB terminal block



1868720

<https://www.phoenixcontact.com/us/products/1868720>


Pitch	5.08 mm
-------	---------

Packaging specifications


Type of packaging	packed in cardboard
-------------------	---------------------

Drawings

Dimensional drawing



Drilling plan/solder pad geometry



MK3DS 1,5/ 3-5,08-A-GNYYE - PCB terminal block



1868720

<https://www.phoenixcontact.com/us/products/1868720>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1868720>

	VDE Zeichengenehmigung Approval ID: 40055535			
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
	400 V	17.5 A	-	0.2 - 2.5

	cULus Recognized Approval ID: E60425-19870326			
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
Use group B				
	125 V	10 A	30 - 14	-
Use group D				
	300 V	10 A	30 - 14	-

MK3DS 1,5/ 3-5,08-A-GNYE - PCB terminal block



1868720

<https://www.phoenixcontact.com/us/products/1868720>

Classifications

ECLASS

ECLASS-11.0	27460101
ECLASS-12.0	27460101
ECLASS-13.0	27460101

ETIM

ETIM 8.0	EC002643
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

MK3DS 1,5/ 3-5,08-A-GNYE - PCB terminal block



1868720

<https://www.phoenixcontact.com/us/products/1868720>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

MK3DS 1,5/ 3-5,08-A-GNYYE - PCB terminal block



1868720

<https://www.phoenixcontact.com/us/products/1868720>

Accessories

SK 5,08/3,8:FORTL.ZAHLEN - Marker card

0804293

<https://www.phoenixcontact.com/us/products/0804293>



Marker card, white, labeled, horizontal: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... (99)100, mounting type: adhesive, for terminal block width: 5.08 mm, lettering field size: 5.08 x 3.8 mm

SZS 0,6X3,5 - Screwdriver

1205053

<https://www.phoenixcontact.com/us/products/1205053>



Actuation tool, for ST terminal blocks, insulated, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

MK3DS 1,5/ 3-5,08-A-GNYP - PCB terminal block

1868720

<https://www.phoenixcontact.com/us/products/1868720>



EBP 2- 5 - Insertion bridge

1733169

<https://www.phoenixcontact.com/us/products/1733169>

Insertion bridge for connectors with 5.0 mm or 5.08 mm pitch



Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com