

# Specifications



## Eaton 188062

Eaton Moeller® series M30 Illuminated pushbutton actuator, RMQ-Titan, flat, momentary, Blue, blank, Front ring stainless steel M30I-FDL-B

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller® series
	M30 Illuminated pushbutton actuator
<b>CATALOG NUMBER</b>	188062
<b>MODEL CODE</b>	M30I-FDL-B
<b>EAN</b>	4015081857418
<b>PRODUCT LENGTH/DEPTH</b>	36 mm
<b>PRODUCT HEIGHT</b>	30 mm
<b>PRODUCT WIDTH</b>	46 mm
<b>PRODUCT WEIGHT</b>	0.041 kg
<b>CERTIFICATIONS</b>	IEC/EN 60947
	VDE 0660
	CSA File No.: 012528
	CSA Class No.: 3211-03
	DNV
	UL File No.: E29184
	GL
	IEC/EN 60947-5
	UL 508
	CSA-C22.2 No. 14-05 and 94-M91
	CE marking
	UL Category Control No.: NKCR
	UL Listed
	CSA certified
<b>GLOBAL CATALOG</b>	188062

## Product specifications

<b>TYPE</b>	Illuminated pushbutton actuator
<b>ACTUATOR COLOR</b>	Blue
<b>ACTUATOR FUNCTION</b>	Momentary Spring-return
<b>FITTED WITH:</b>	Front ring
<b>OPERATING FREQUENCY</b>	3600 Operations/h
<b>CLIMATIC PROOFING</b>	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
<b>CONNECTION TO SMARTWIRE-DT</b>	With SWD-RMQ connections Yes
<b>ACTUATING FORCE</b>	5 N
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	70 °C
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>FORCE FOR POSITIVE OPENING - MIN</b>	0 N
<b>NUMBER OF COMMAND POSITIONS</b>	1
<b>OPENING DIAMETER</b>	30.5 mm
<b>OPENING HEIGHT</b>	0 mm
<b>BEZEL COLOR</b>	Stainless steel
<b>SHOCK RESISTANCE</b>	15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27
<b>BEZEL MATERIAL</b>	Metal
<b>DESIGN</b>	Flat Flat front
<b>MOUNTING POSITION</b>	As required
<b>DEGREE OF PROTECTION</b>	IP66 IP69 IP67
<b>DEGREE OF PROTECTION (FRONT SIDE)</b>	IP67 NEMA 4X, 13
<b>INSCRIPTION</b>	Blank
<b>FRONT ELEMENT TYPE</b>	Flat
<b>LENS TYPE</b>	Round
<b>LIFESPAN, MECHANICAL</b>	5,000,000 Operations

## Resources

### CATALOGS

[eaton-rmq-titan-brochure-br047004en-en-us.pdf](#)

[eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf](#)

[Flip catalog - Product Range Catalog - Command and indication](#)

### DECLARATIONS OF CONFORMITY

[eaton-key-operated-actuator-declaration-of-conformity-eu250863en.pdf](#)

[eaton-key-operated-actuator-declaration-of-conformity-eu250864en.pdf](#)

[eaton-operating-m30-dimensions-005.eps](#)

[eaton-operating-m30-dimensions-006.eps](#)

[eaton-operating-m30-dimensions-004.eps](#)

[eaton-operating-m30-dimensions.eps](#)

### DRAWINGS

[eaton-general-m22-symbol.eps](#)

[eaton-operating-m30-3d-drawing.eps](#)

[eaton-general-approval-m22-symbol.eps](#)

[eaton-operating-symbol-002.eps](#)

### ECAD MODEL

[ETN.188062.edz](#)

### FLYERS

[eaton-rmq-titan-selection-aid-brochure-fl047002-en-us.pdf](#)

### INSTALLATION INSTRUCTIONS

[eaton-operating-devices-m30-rmq-titan-flat-front-instruction-leaflet-il047019zu.pdf](#)

### INSTALLATION VIDEOS

[RMQ Flat Design](#)

WIDTH OPENING	0 mm
PRODUCT CATEGORY	RMQ-Titan
SIZE	Front dimensions: Ø 36 mm
SUITABLE FOR	Illumination

MCAD MODEL	<a href="#">DA-CS-drucktaste_flach_flatfront</a>
	<a href="#">DA-CD-drucktaste_flach_flatfront</a>
	<a href="#">easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator</a>
MULTIMEDIA	<a href="#">MCI Multicolor Light Indicator M22 with SmartWire-DT</a>
	<a href="#">MCI MultiColor Light Indicator RMQ compact solution</a>
	<a href="#">RMQ small E-Stop emergency-stop button</a>
SALES NOTES	<a href="#">eaton-control-circuit-devices-rmq-titan-fl144090en-en-us.pdf</a>
	<a href="#">eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf</a>
	<a href="#">eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf</a>
	<a href="#">eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf</a>

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

Follow us on social media to get the latest product and support information.

