


Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



1-level terminal block with double connection on one side, cross section: 0.2 - 4 mm<sup>2</sup>, AWG: 24 - 12, width: 6.2 mm, color: blue

Your advantages

- These twin modular terminal blocks are designed for the basic task of potential branching
- Two independent conductor connections can be used on the control cabinet side
- Universal foot for mounting on NS 35.. or NS 32... DIN rails
- Easy connection of different types of conductors with different cross sections
- Can be bridged in the terminal center, even with neighboring feed-through terminal blocks aligned

Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 1923047             |
| Packing unit                         | 50 pc               |
| Minimum order quantity               | 50 pc               |
| Sales key                            | BE01                |
| Product key                          | BE1212              |
| Catalog page                         | Page 467 (C-1-2019) |
| GTIN                                 | 4017918052447       |
| Weight per piece (including packing) | 12.663 g            |
| Weight per piece (excluding packing) | 11.7 g              |
| Customs tariff number                | 85369010            |
| Country of origin                    | CN                  |

# UK 5-TWIN BU - Feed-through terminal block



1923047

<https://www.phoenixcontact.com/ca/products/1923047>

## Technical data

### Product properties

|                       |                                |
|-----------------------|--------------------------------|
| Product type          | Multi-conductor terminal block |
| Number of connections | 3                              |
| Number of rows        | 2                              |
| Potentials            | 1                              |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

|                                                 |        |
|-------------------------------------------------|--------|
| Rated surge voltage                             | 6 kV   |
| Maximum power dissipation for nominal condition | 1.02 W |

### Connection data

|                                 |                   |
|---------------------------------|-------------------|
| Number of connections per level | 3                 |
| Nominal cross section           | 4 mm <sup>2</sup> |

#### 1 level

|                                                                                           |                                                                                                                                                                |
|-------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Screw thread                                                                              | M3                                                                                                                                                             |
| Tightening torque                                                                         | 0.6 ... 0.8 Nm                                                                                                                                                 |
| Stripping length                                                                          | 8 mm                                                                                                                                                           |
| Connection in acc. with standard                                                          | IEC 60947-7-1                                                                                                                                                  |
| Conductor cross section rigid                                                             | 0.2 mm <sup>2</sup> ... 4 mm <sup>2</sup>                                                                                                                      |
| Cross section AWG                                                                         | 24 ... 12 (converted acc. to IEC)                                                                                                                              |
| Conductor cross section flexible                                                          | 0.2 mm <sup>2</sup> ... 4 mm <sup>2</sup>                                                                                                                      |
| Conductor cross section, flexible [AWG]                                                   | 24 ... 12 (converted acc. to IEC)                                                                                                                              |
| Conductor cross-section flexible (ferrule without plastic sleeve)                         | 0.25 mm <sup>2</sup> ... 4 mm <sup>2</sup>                                                                                                                     |
| Flexible conductor cross section (ferrule with plastic sleeve)                            | 0.25 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>                                                                                                                   |
| Cross-section with insertion bridge, rigid                                                | 4 mm <sup>2</sup>                                                                                                                                              |
| Cross-section with insertion bridge, flexible                                             | 4 mm <sup>2</sup>                                                                                                                                              |
| 2 conductors with same cross section, solid                                               | 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>                                                                                                                    |
| 2 conductors with same cross section, flexible                                            | 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>                                                                                                                    |
| 2 conductors with same cross section, flexible, with ferrule without plastic sleeve       | 0.25 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>                                                                                                                   |
| 2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve | 0.5 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>                                                                                                                    |
| Nominal current                                                                           | 32 A (with 4 mm <sup>2</sup> conductor cross section)                                                                                                          |
| Maximum load current                                                                      | 32 A (in case of a 4 mm <sup>2</sup> conductor cross section, the maximum load current must not be exceeded by the total current of all connected conductors.) |
| Nominal voltage                                                                           | 500 V (With tightened clamping screws)                                                                                                                         |
| Nominal cross section                                                                     | 4 mm <sup>2</sup>                                                                                                                                              |

# UK 5-TWIN BU - Feed-through terminal block



1923047

<https://www.phoenixcontact.com/ca/products/1923047>

## Ex data

### Rated data (ATEX/IECEx)

|                             |                                       |
|-----------------------------|---------------------------------------|
| Identification              | Ex II 2 G Ex eb IIC Gb                |
| Operating temperature range | -50 °C ... 110 °C                     |
| Ex-certified accessories    | 1923034 D-UK 5-TWIN                   |
|                             | 9911501 UK 5-TWIN DECKELSEGMENTGY7042 |
|                             | 1205053 SZS 0,6X3,5                   |
| Ex temperature increase     | 33 K (32 A / 4 mm²)                   |
| Rated voltage               | 275 V                                 |
| Rated insulation voltage    | 250 V                                 |
| output                      | (Permanent)                           |

### Ex level General

|                      |         |
|----------------------|---------|
| Rated current        | 32 A    |
| Maximum load current | 32 A    |
| Contact resistance   | 0.34 mΩ |

### Ex connection data General

|                                                       |                     |
|-------------------------------------------------------|---------------------|
| Stripping length                                      | 8 mm                |
| Torque range                                          | 0.6 Nm ... 0.8 Nm   |
| Nominal cross section                                 | 4 mm²               |
| Rated cross section AWG                               | 12                  |
| Connection capacity rigid                             | 0.2 mm² ... 4 mm²   |
| Connection capacity AWG                               | 24 ... 12           |
| Connection capacity flexible                          | 0.2 mm² ... 4 mm²   |
| Connection capacity AWG                               | 24 ... 12           |
| 2 conductors with same cross section, solid           | 0.2 mm² ... 1.5 mm² |
| 2 conductors with the same cross-section AWG rigid    | 24 ... 16           |
| 2 conductors with same cross section, stranded        | 0.2 mm² ... 1.5 mm² |
| 2 conductors with the same cross-section AWG flexible | 24 ... 16           |

## Dimensions

|                    |         |
|--------------------|---------|
| Width              | 6.2 mm  |
| End cover width    | 2 mm    |
| Height             | 50.5 mm |
| Depth on NS 32     | 52 mm   |
| Depth on NS 35/7,5 | 47 mm   |
| Depth on NS 35/15  | 54.5 mm |

## Material specifications

|                                        |      |
|----------------------------------------|------|
| Color                                  | blue |
| Flammability rating according to UL 94 | V2   |
| Insulating material group              | I    |
| Insulating material                    | PA   |

# UK 5-TWIN BU - Feed-through terminal block



1923047

<https://www.phoenixcontact.com/ca/products/1923047>

|                                                                         |             |
|-------------------------------------------------------------------------|-------------|
| Static insulating material application in cold                          | -60 °C      |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C      |
| Relative insulation material temperature index (Elec., UL 746 B)        | 130 °C      |
| Fire protection for rail vehicles (DIN EN 45545-2) R22                  | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R23                  | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R24                  | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R26                  | HL 1 - HL 3 |
| Calorimetric heat release NFPA 130 (ASTM E 1354)                        | 28 MJ/kg    |
| Surface flammability NFPA 130 (ASTM E 162)                              | passed      |
| Specific optical density of smoke NFPA 130 (ASTM E 662)                 | passed      |
| Smoke gas toxicity NFPA 130 (SMP 800C)                                  | passed      |

## Electrical tests

### Surge voltage test

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 7.3 kV      |
| Result                | Test passed |

### Temperature-rise test

|                                                      |                                     |
|------------------------------------------------------|-------------------------------------|
| Requirement temperature-rise test                    | Increase in temperature $\leq 45$ K |
| Result                                               | Test passed                         |
|                                                      | Test passed                         |
| Short-time withstand current 4000000 mm <sup>2</sup> | 0.00048 kA                          |
| Result                                               | Test passed                         |

### Power-frequency withstand voltage

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 1.89 kV     |
| Result                | Test passed |

## Mechanical properties

### Mechanical data

|                 |     |
|-----------------|-----|
| Open side panel | Yes |
|-----------------|-----|

## Mechanical tests

### Mechanical strength

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

### Attachment on the carrier

|                         |             |
|-------------------------|-------------|
| DIN rail/fixing support | NS 32/NS 35 |
| Test force setpoint     | 1 N         |
| Result                  | Test passed |

### Test for conductor damage and slackening

|                |                |
|----------------|----------------|
| Rotation speed | 10 (+/- 2) rpm |
| Revolutions    | 135            |

# UK 5-TWIN BU - Feed-through terminal block



1923047

<https://www.phoenixcontact.com/ca/products/1923047>

|                                |                              |
|--------------------------------|------------------------------|
| Conductor cross section/weight | 0.2 mm <sup>2</sup> / 0.2 kg |
|                                | 1.5 mm <sup>2</sup> / 0.4 kg |
|                                | 4 mm <sup>2</sup> / 0.9 kg   |
| Result                         | Test passed                  |

## Environmental and real-life conditions

### Needle-flame test

|                  |             |
|------------------|-------------|
| Time of exposure | 30 s        |
| Result           | Test passed |

### Oscillation/broadband noise

|               |                                     |
|---------------|-------------------------------------|
| Specification | DIN EN 50155 (VDE 0115-200):2018-05 |
|---------------|-------------------------------------|

### Ambient conditions

|                                          |                                                                                                                              |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Ambient temperature (operation)          | -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.) |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)                                                    |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                                                                              |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                                                                              |
| Permissible humidity (operation)         | 20 % ... 90 %                                                                                                                |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                                                                                |

## Standards and regulations

|                                  |               |
|----------------------------------|---------------|
| Connection in acc. with standard | IEC 60947-7-1 |
|----------------------------------|---------------|

## Mounting

|               |           |
|---------------|-----------|
| Mounting type | NS 35/7,5 |
|               | NS 35/15  |
|               | NS 32     |

# UK 5-TWIN BU - Feed-through terminal block

1923047

<https://www.phoenixcontact.com/ca/products/1923047>



## Drawings

Circuit diagram



# UK 5-TWIN BU - Feed-through terminal block



1923047

<https://www.phoenixcontact.com/ca/products/1923047>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/ca/products/1923047>

### DNV

Approval ID: TAE00001CT



### CSA

Approval ID: 13631

|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  | 300 V                 | 30 A                  | 22 - 10           | -                           |



### IECEE CB Scheme

Approval ID: NL-65052

|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  | 500 V                 | 32 A                  | -                 | - 4                         |



### EAC

Approval ID: RU C-DE.BL08.B.00534



### cULus Recognized

Approval ID: E60425

|                | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|----------------|-----------------------|-----------------------|-------------------|-----------------------------|
| Use group B    |                       |                       |                   |                             |
| Field wiring   | 300 V                 | 30 A                  | 30 - 10           | -                           |
| Factory wiring | 300 V                 | 35 A                  | 30 - 10           | -                           |
| Use group C    |                       |                       |                   |                             |
| Field wiring   | 150 V                 | 30 A                  | 30 - 10           | -                           |
| Factory wiring | 150 V                 | 35 A                  | 30 - 10           | -                           |



### KEMA-KEUR

Approval ID: 71-119845

|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  | 500 V                 | 32 A                  | -                 | 0.2 - 4                     |



### CSA

Approval ID: 13631

|             | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|-------------|-----------------------|-----------------------|-------------------|-----------------------------|
| Use group B |                       |                       |                   |                             |
|             | 300 V                 | 30 A                  | -                 | -                           |

# UK 5-TWIN BU - Feed-through terminal block



1923047

<https://www.phoenixcontact.com/ca/products/1923047>

|             |       |      |   |   |
|-------------|-------|------|---|---|
| Use group C |       |      |   |   |
|             | 150 V | 30 A | - | - |
| Use group D |       |      |   |   |
|             | 300 V | 10 A | - | - |

|                                                                                                                                 |                       |                       |                   |                             |
|---------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|  <b>cUL Recognized</b><br>Approval ID: E192998 |                       |                       |                   |                             |
|                                                                                                                                 | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|                                                                                                                                 | 150 V                 | 30 A                  | 30 - 10           | -                           |

|                                                                                                                                      |  |  |  |  |
|--------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|
|  <b>EAC Ex</b><br>Approval ID: RU C-DE.HA91.B.00066 |  |  |  |  |
|--------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|

|                                                                                                                                 |                       |                       |                   |                             |
|---------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|  <b>UL Recognized</b><br>Approval ID: E192998 |                       |                       |                   |                             |
|                                                                                                                                 | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|                                                                                                                                 | 150 V                 | 30 A                  | 30 - 10           | -                           |

|                                                                                                                                 |  |  |  |  |
|---------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|
|  <b>CCC</b><br>Approval ID: 2020322313000623 |  |  |  |  |
|---------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|

|                         |  |  |  |  |
|-------------------------|--|--|--|--|
| <b>cULus Recognized</b> |  |  |  |  |
|-------------------------|--|--|--|--|

# UK 5-TWIN BU - Feed-through terminal block



1923047

<https://www.phoenixcontact.com/ca/products/1923047>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141120 |
| ECLASS-13.0 | 27250101 |

### ETIM

|          |          |
|----------|----------|
| ETIM 8.0 | EC000897 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |