

MC 1,5/ 9-G-3,5 THT - PCB header

1937567

<https://www.phoenixcontact.com/pc/products/1937567>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



PCB headers, color: black, contact surface: Tin, number of positions: 9, product range: MC 1,5/..-G-THT, pitch: 3.5 mm, pin layout: Linear pinning, solder pin [P]: 3.4 mm, type of packaging: packed in cardboard, For user information and design recommendations for through-hole reflow technology, go to: Downloads

Commercial data

Item number	1937567
Packing unit	50 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	AAB1GJ
Catalog page	Page 196 (CC-2011)
GTIN	4017918890230
Weight per piece (including packing)	3.694 g
Weight per piece (excluding packing)	3.666 g
Customs tariff number	85366930
Country of origin	DE

MC 1,5/ 9-G-3,5 THT - PCB header

1937567

<https://www.phoenixcontact.com/pc/products/1937567>



Technical data

Product properties

Product type	PCB headers
Product family	MC 1,5/...-G-THT
Type	Component suitable for through hole reflow
Number of positions	9
Pitch	3.5 mm
Mounting flange	without
Pin layout	Linear pinning

Electrical properties

Maximum load current	8 A (per position)
Rated voltage (II/2)	250 V
Rated voltage (III/2)	160 V
Rated surge voltage (II/2)	2.5 kV
Rated surge voltage (III/2)	2.5 kV
Rated surge voltage (III/3)	2.5 kV


Mounting

Mounting type	THR soldering
Pin layout	Linear pinning

Material specifications

Color	black
Flammability rating according to UL 94	V0
Insulating material group	IIIa
Insulating material	PA-GF
Contact surface	Tin Sn
Contact surface material	Sn

Dimensions

Dimensional drawing	
Width	32.9 mm
Installed height	7.25 mm
Height	10.65 mm
Length of the solder pin	3.4 mm
Length	9.2 mm
Length of the solder pin	3.4 mm

MC 1,5/ 9-G-3,5 THT - PCB header

1937567

<https://www.phoenixcontact.com/pc/products/1937567>



Hole diameter	1.4 mm
Pitch	3.5 mm

Packaging specifications

Type of packaging	packed in cardboard
Outer packaging type	Dry bag

MC 1,5/ 9-G-3,5 THT - PCB header


1937567

<https://www.phoenixcontact.com/pc/products/1937567>




Drawings

Dimensional drawing



Bottom view, free space for solder paste, 0.3 mm deep

Drilling plan/solder pad geometry




MC 1,5/ 9-G-3,5 THT - PCB header

1937567

<https://www.phoenixcontact.com/pc/products/1937567>



Dimensional drawing




MC 1,5/ 9-G-3,5 THT - PCB header

1937567

<https://www.phoenixcontact.com/pc/products/1937567>



Dimensional drawing



MC 1,5/ 9-G-3,5 THT - PCB header

1937567

<https://www.phoenixcontact.com/pc/products/1937567>



Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1937567>

 cULus Recognized Approval ID: E60425-20110128				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Use group B				
	300 V	8 A	-	-
Use group D				
	300 V	8 A	-	-

 VDE Zeichengenehmigung Approval ID: 40011723				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	160 V	8 A	-	-

MC 1,5/ 9-G-3,5 THT - PCB header

1937567

<https://www.phoenixcontact.com/pc/products/1937567>



Classifications

ECLASS

ECLASS-13.0	27460201
-------------	----------

MC 1,5/ 9-G-3,5 THT - PCB header

1937567

<https://www.phoenixcontact.com/pc/products/1937567>



Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com