

194EA403753

Allen-Bradley 194E C/O Switch Body, Base/DIN rail mount 3 Pole 40A



Component type	Switch disconnecter
Range	194E
Model	N/A
Product status	Phased Out

Bulletin 194E Load Break Switches provide a safe and reliable way to disconnect and isolate power from machinery. Featuring visible on/off indication, padlockable handles, a blade stop, easy maintenance and switch longevity. Available from 16A to 100A and in 3 Pole to 6 Pole configurations. Options include additional poles, grounding and neutral terminals and auxiliary contacts.

ELECTRICAL

Max. rated operation voltage Ue AC	690.0 V
Rated permanent current at AC-21, 400 V	40.0 A
Rated permanent current Iu	40.0 A
Number of poles	3.0
Rated operation power at AC-3, 400 V	15.0 kW
Rated operation power at AC-23, 400 V	22.0 kW
Rated short-time withstand current Icw	1300.0 kA
Type of electrical connection of main circuit	Screw connection
Conditioned rated short-circuit current Iq	20.0 kA
Number of auxiliary contacts as normally closed contact	0.0
Number of auxiliary contacts as normally open contact	0.0

CONSTRUCTION

Device construction	Built-in device fixed built-in technique
Degree of protection (IP), front side	IP20
Version as main switch	Yes
Version as maintenance-/service switch	Yes
Version as emergency stop installation	No
Version as reversing switch	No
Number of switches	1.0
Suitable for distribution board installation	No
Degree of protection (NEMA)	Other

DIMENSIONS

Depth	105.0 mm
Height	180.0 mm

ENVIRONMENT

Storage temperature	-40 - 80 °C
---------------------	-------------