


LBS FRONT/DOOR ON-OFF 3P 40A W/O ACTUATOR

Power Distribution and Protection > Isolators and Transfer Switches > Load Break Switches > Allen-Bradley Load Break Switches > 194E Load Break Switches (16 to 100A) > Front / Door Mounting

**LBS Front/Door ON-OFF 3P 63A W/O ACT**

- Suitable as At-Motor Disconnect Switch (UL508) useful for overseas application with added UL requirements
- Bulletin 194R also suitable as service entrance disconnecting (UL98) providing even greater application use
- Greater installation flexibility with selection of front/door or DIN/base mounting configurations (194E series only)
- Padlockable Handles Available (up to 3 padlocks) for added security
- Wide range of accessories available which is flexible in adapting to various applications and reduces the cost of management and storage

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Product Series	Bul. 194E
Operator Type	Off/On Switch (Isolator) type
Number of Poles	3
Ui, Rated Insulation Voltage	690 V (rms)
Uimp, Impulse Withstand Voltage	8 kV
Ie, Rated Operational Current, AC-21a, 415V	40 A@415V
Ie, Rated Operational Current, AC-21a, 690V	40 A@690V
kW Rating, AC-23a, 400V, 3ph	18.5 kW @400V
kW Rating, AC-23a, 690V, 3ph	18.5 kW @690V
Wire / Conductor Size, Flex Cable, Min	2.5 mm ² min
Wire / Conductor Size, Flex Cable, Max	16 mm ² max
Wire / Conductor Size, Rigid Cable, Min	2.5 mm ² min
Wire / Conductor Size, Rigid Cable, Max	25 mm ² max
Height	72 mm
Width	54 mm
Depth	74 mm
Operating Temperature, Min	-25 °C min
Operating Temperature, Max	60 °C max
Storage Temperature, Min	-40 °C min
Storage Temperature, Max	80 °C max

LBS FRONT/DOOR ON-OFF 3P 40A W/O ACTUATOR

Power Distribution and Protection > Isolators and Transfer Switches > Load Break Switches > Allen-Bradley Load Break Switches > 194E Load Break Switches (16 to 100A) > Front / Door Mounting

REFERENCES	
IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-