

1954359

https://www.phoenixcontact.com/us/products/1954359

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Coding profile, for insertion between the coding ribs of the connector and the header following the reflow soldering process, insulating material, color: natural



Commercial data

Item number	1954359
Packing unit	100 pc
Minimum order quantity	100 pc
Sales key	AA08
Product key	AAHZBC
Catalog page	Page 446 (CC-2007)
GTIN	4017918897376
Weight per piece (including packing)	0.773 g
Weight per piece (excluding packing)	0.756 g
Customs tariff number	39269097
Country of origin	DE



1954359

https://www.phoenixcontact.com/us/products/1954359

Technical data

Product properties

Product type	Coding element
Product family	Coding
Number of positions	1
Pitch	0 mm
Data management status	
Article revision	00

Mounting

Processing notes

Process	Reflow/wave soldering
Moisture Sensitive Level	MSL 3
Classification temperature T _c	260 °C
Solder cycles in the reflow	3

Dimensions

Pitch	0 mm



1954359

https://www.phoenixcontact.com/us/products/1954359

Classifications

UNSPSC 21.0

ECLASS

27460401
27460401
27460401
EC002943

39121400



1954359

https://www.phoenixcontact.com/us/products/1954359

Environmental product compliance

EU RoHS

20 1.01.0	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com