

Specifications

Eaton 197215

Eaton Moeller® series EASY Control relays easyE4 with display (expandable, Ethernet), 100 - 240 V AC, 110 - 220 V DC (cULus: 100 - 110 V DC), Inputs Digital: 8, screw terminal EASY-E4-AC-12RC1

General specifications

PRODUCT NAME	Eaton Moeller® series EASY Control relay
CATALOG NUMBER	197215
MODEL CODE	EASY-E4-AC-12RC1
EAN	4015081939442
PRODUCT LENGTH/DEPTH	58 mm
PRODUCT HEIGHT	90 mm
PRODUCT WIDTH	72 mm
PRODUCT WEIGHT	0.25 kg
COMPLIANCES	Eaton supports the product until its end of life
CERTIFICATIONS	EN 61010 IEC/EN 61000-6-2 CULus per UL 61010 IEC/EN 61000-4-2 IEC/EN 61131-2 IEC 60068-2-30 CSA-C22.2 No. 61010 EN 50178 IEC 60664 IEC 60068-2-27 IEC 60068-2-6 IEC/EN 61000-6-3 UL Listed UL Category Control No.: NRAQ, NRAQ7 UL File No.: E205091 DNV GL CE UL hazardous location class I UL hazardous location division 2 UL hazardous location

	group A (acetylene) UL hazardous location group B (hydrogen) UL hazardous location group C (ethylene) UL hazardous location group D (propane)
CATALOG NOTES	Accuracy of the real-time clock depending on ambient air temperature - fluctuations of up to ± 5 s/day (± 0.5 h/year) are possible

Features & Functions	
FEATURES	Networkable (Ethernet) Expandable Display indication of 6 lines x 16 characters
FITTED WITH:	Relay output Timer Keypad Display Real time clock
INDICATION	LCD-display used as status indication of Digital inputs 115/230 V AC

General	
DEGREE OF PROTECTION	IP20
DISPLAY TEMPERATURE - MIN	0 °C
DISPLAY TEMPERATURE - MAX	55 °C
DISPLAY TYPE	Monochrome
INPUT FREQUENCY	50/60 Hz (Digital inputs, at 115/230 V AC) 50/60 Hz (Digital inputs, at 24 V DC)
INSULATION RESISTANCE	According to EN 50178, EN 61010-2-201, UL61010-2-201, CSA-C22.2 NO. 61010-2-201
LIFESPAN, ELECTRICAL	25,000 Operations (Fluorescent lamp load 1 x 58 W at 230/240 V AC, conventional, compensated) 25,000 Operations (Fluorescent lamp load 10 x 58 W at 230/240 V AC, with upstream electrical device) 25,000 Operations (Filament bulb load at 1000 W, 230/240 V AC) 25,000 Operations (Fluorescent lamp load 10 x 58 W at 230/240 V AC, uncompensated) 25,000 Operations (Filament bulb load at 500 W, 115/120 V AC)
LIFESPAN, MECHANICAL	1,000,000 Operations
MOUNTING METHOD	Screw fixing using fixing

	brackets ZB4-101-GF1 (accessories) Rail mounting possible Top-hat rail fixing (according to IEC/EN 60715, 35 mm) Wall mounting/direct mounting Front build in possible
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	2
PRODUCT CATEGORY	Control relays easyE4
PROTECTION	B16 circuit breaker or 8 A (T) fuse, Protection of an Output relay
PROTOCOL	TCP/IP MODBUS
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6 kV (contact-coil)
RESIDUAL RIPPLE	≤ 5 %
RESOLUTION	<ul style="list-style-type: none"> • 1 min (Range H:M) • 1 s (Range M:S) • 5 ms (Range S)
SOFTWARE	EASYSOFT-SWLIC/easySoft
SWITCHING FREQUENCY	10 Hz, Relay outputs 2 Hz, Resistive load/lamp load, Relay outputs 0.5 Hz, Inductive load, Relay outputs
TYPE	easyE4 base device
USED WITH	easyE4
UTILIZATION CATEGORY	B 300 Light Pilot Duty, UL/CSA Control Circuit Rating Codes AC R 300 Light Pilot Duty, UL/CSA Control Circuit Rating Codes DC
VOLTAGE TYPE	AC

Ambient conditions, mechanical

DROP AND TOPPLE	50 mm Drop height, Drop to IEC/EN 60068-2-31
HEIGHT OF FALL (IEC/EN 60068-2-32) - MAX	0.3 m
MOUNTING POSITION	Horizontal Vertical
SHOCK RESISTANCE	15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 18 Impacts
VIBRATION RESISTANCE	According to IEC/EN 60068-2-6 57 - 150 Hz, 2 g constant acceleration 10 - 57 Hz, 0.15 mm constant amplitude

Climatic environmental conditions

AIR PRESSURE	795 - 1080 hPa (operation)
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
AMBIENT STORAGE TEMPERATURE - MAX	70 °C
ENVIRONMENTAL CONDITIONS	Condensation: prevent with appropriate measures Clearance in air and creepage distances according to EN 50178, EN 61010-2-201, UL61010-2-201, CSA-C22.2 NO. 61010-2-201
RELATIVE HUMIDITY	5 - 95 % (IEC 60068-2-30, IEC 60068-2-78)

Electro magnetic compatibility

AIR DISCHARGE	8 kV
BURST IMPULSE	2 kV, Signal cable According to IEC/EN 61000-4-4 2 kV, Supply cable
CONTACT DISCHARGE	6 kV
ELECTROMAGNETIC FIELDS	3 V/m at 1.4 - 2 GHz (according to IEC EN 61000-4-3) 1 V/m at 2.0 - 2.7 GHz (according to IEC EN 61000-4-3) 10 V/m at 0.8 - 1.0 GHz (according to IEC EN 61000-4-3)
IMMUNITY TO LINE-CONDUCTED INTERFERENCE	10 V (according to IEC/EN 61000-4-6)
RADIO INTERFERENCE CLASS	Class B (EN 61000-6-3)
SURGE RATING	1 kV, Supply cables, symmetrical, power pulses (Surge), EMC According to IEC/EN 61000-4-5, power pulses (Surge), EMC 2 kV, Supply cables, asymmetrical, power pulses (Surge), EMC
VOLTAGE DIPS	10 ms

Terminal capacities

TERMINAL CAPACITY	0.2 - 4 mm ² (AWG 22 - 12), solid 0.2 - 2.5 mm ² (22 - 12 AWG), flexible with ferrule
SCREWDRIVER SIZE	3.5 x 0.8 mm, Terminal screw
TIGHTENING TORQUE	0.6 Nm, Screw terminals

Electrical rating

CONVENTIONAL THERMAL CURRENT ITH OF AUXILIARY CONTACTS (1-POLE, OPEN)

8 A

INRUSH CURRENT

12.5 A (for 6 ms)

POWER CONSUMPTION

4 W

POWER LOSS

10 W

RATED BREAKING CAPACITY

300000 Operations at AC-
15, 250 V AC, 3 A (600
Ops./h)
200000 Operations at DC-
13, 24 V DC, 1 A (500
Ops./h)

RATED INSULATION VOLTAGE (UI)

240 V

RATED OPERATIONAL VOLTAGE

Max. 300 V DC
100/110/115/120/230/240
AC (-15 %/+10 %)
85 - 264 V AC
Max. 300 V AC
110/120 V DC (power
supply)
240 V AC

SUPPLY FREQUENCY

50/60 Hz (± 5%)

SUPPLY VOLTAGE AT AC, 50 HZ - MIN

85 VAC

SUPPLY VOLTAGE AT AC, 50 HZ - MAX

264 VAC

SUPPLY VOLTAGE AT DC - MIN

85 VDC

SUPPLY VOLTAGE AT DC - MAX

264 VDC

UNINTERRUPTED CURRENT

5 A AC, max. thermal
continuous current $\cos \phi$
= 1 at B 300 (UL/CSA)
8 A AC, at 240 V AC
(UL/CSA)
8 A DC, at 24 V DC
(UL/CSA)
1 A DC, at R 300 (UL/CSA)

Communication

CONNECTION TYPE

Screw terminal
Ethernet: RJ45 plug, 8-pole

DATA TRANSFER RATE

10/100 MBit/s

Short-circuit rating

SHORT-CIRCUIT PROTECTION

≥ 1A (T), Fuse, Power
supply

Cable

CABLE LENGTH

100 m (max. permissible
per input I7 to I8), Digital
inputs 115/230 V AC
40 m (max. permissible
per input I1 to I6), Digital

	inputs 115/230 V AC
CABLE TYPE	CAT5

Input/Output

ACCURACY	± 1 %, Repetition accuracy of timing relays (of values) ± 2 s/day, Real-time clock to inputs (± 0.2 h/Year)
DELAY TIME	<p>21 ms typ., Digital Inputs 100 - 240 V AC 60 Hz (I1 - I8), Delay time from 0 to 1, Debounce OFF</p> <p>20 ms typ., Digital Inputs 100 - 240 V DC (I1 - I8), Delay time from 0 to 1, Debounce ON</p> <p>20 ms, Digital inputs 115/230 V AC 50 Hz (I7, I8), Delay time from 1 to 0, Debounce OFF</p> <p>21 ms typ., Digital Inputs 100 - 240 V AC 60 Hz (I1 - I8), Delay time from 1 to 0, Debounce OFF</p> <p>16⅔ ms, Digital inputs 115/230 V AC 60 Hz (I7, I8), Delay time from 1 to 0, Debounce OFF</p> <p>0.03 ms typ., Digital Inputs 100 - 240 V DC (I1 - I8), Delay time from 0 to 1, Debounce OFF</p> <p>0.03 ms typ., Digital Inputs 100 - 240 V DC (I1 - I8), Delay time from 1 to 0, Debounce OFF</p> <p>20 ms typ., Digital Inputs 100 - 240 V DC (I1 - I8), Delay time from 1 to 0, Debounce ON</p>
INPUT CURRENT	<p>2 x 4 mA (I7 - I8, at 115 V AC, 60 Hz, at signal 1)</p> <p>6 x 0.25 mA (I1 - I6, at 115 V AC, 60 Hz, at signal 1)</p> <p>2 x 6 mA (I7 - I8, at 230 V AC, 50 Hz, at signal 1)</p> <p>6 x 0.5 mA (I1 - I6, at 230 V AC, 50 Hz, at signal 1)</p>
INPUT VOLTAGE	<p>Condition 0: 0 - 40 V AC, Digital inputs, 115/230 V AC)</p> <p>Condition 1: 79 - 264 V AC, Digital inputs, 115/230 V AC)</p>
MAKING/BREAKING CAPACITY	3600/360 VA (AC, at B 300) 28/28 VA (DC, at R 300)
NUMBER OF INPUTS	0

Safety

EXPLOSION SAFETY CATEGORY FOR GAS	None
POTENTIAL ISOLATION	<p>Between Digital inputs 115/230 V AC and Power supply: no</p> <p>Between Relay outputs and expansion devices: yes</p> <p>Between Digital inputs 115/230 V AC: no</p> <p>Between Relay outputs and Inputs: yes</p> <p>Between Digital inputs 115/230 V AC and base unit: yes</p> <p>Between Digital inputs 115/230 V AC and Outputs: yes</p> <p>Between Digital inputs 115/230 V AC and Ethernet: yes</p> <p>Between Relay outputs and Ethernet: yes</p> <p>Basic isolation: 600 V AC (Relay outputs)</p> <p>Between Digital inputs 115/230 V AC and expansion devices: yes</p> <p>Safe isolation according to EN 50178: 300 V AC (Relay outputs)</p> <p>Between Relay outputs: yes</p> <p>Between Digital inputs 115/230 V AC and Memory card: no</p> <p>Between Relay outputs and Power supply: yes</p> <p>Between Digital inputs 115/230 V AC and Interface: yes</p>
PROTECTION AGAINST POLARITY REVERSAL	Yes, for supply voltage (Siemens MPI optional)
EXPLOSION SAFETY CATEGORY FOR DUST	None
SAFE ISOLATION	<p>300 V AC, Between two contacts, According to EN 50178</p> <p>300 V AC, Between coil and contact, According to EN 50178</p>

(ANALOG)	
NUMBER OF INPUTS (DIGITAL)	8
NUMBER OF OUTPUTS (ANALOG)	0
NUMBER OF OUTPUTS (DIGITAL)	4
OUTPUT	Relay outputs in groups of 1 4 Relay Outputs > 500 mA (Relay outputs, Recommended for load: 12 V AC/DC) Voltage Current
PARALLEL SWITCHING	Not permitted

Design verification

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	4 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	4 W
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Meets the product standard's requirements.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.

Resources

APPLICATION NOTES	eaton-easye4-aws-ap050027-en-us.pdf
BROCHURES	easy E4 control relay-brochure
CATALOGUES	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
CHARACTERISTIC CURVE	eaton-electrical-timers-easy-control-relays-characteristic-curve-002.eps
DECLARATIONS OF CONFORMITY	DA-DC-00005048.pdf DA-DC-00005057.pdf
DRAWINGS	eaton-modular-plc-starter-kit-dimensions.eps eaton-modular-plc-easy-control-relays-3d-drawing.eps
ECAD MODEL	ETN.EASY-E4-AC-12-RC1
INSTALLATION INSTRUCTIONS	IL050020ZU
INSTALLATION VIDEOS	Video easy E4 control relay Control relay easyE4: The new generation
MANUALS AND USER GUIDES	MN050009_EN
MCAD MODEL	DA-CS-uc_12rc1 DA-CD-uc_12rc1
MULTIMEDIA	How to process ModbusRTU devices with the EASY-COM-RTU-M1 module on an easyE4? Handling of the data logger as a ring buffer with the easyE4 using the ST programming language. easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator How to connect the easyE4 to the touch panel XV-102 for easy? - 5 Steps

10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

	How to connect the Remote Touch Display EASY-RTD to the easyE4?
	How to process SmartWire-DT modules using the EASY-COM-SWD-C1 module connected to an easyE4?
PRODUCT NOTIFICATIONS	MZ049014EN
SALES NOTES	eaton-easy-remote-touch-display-flyer-fl048004en-us.pdf eaton-control-relay-easye4-flyer-fl050007en-us.pdf

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
 Eaton House
 30 Pembroke Road
 Dublin 4, Ireland
 Eaton.com

Follow us on social media to get the latest product and support information.

