

Specifications

Eaton 197456

Eaton Moeller® series T3 T3, 32 A, surface mounting, 3 contact unit(s), 90 °, maintained, 0-1, in steel enclosure, Design number 8342

General specifications

PRODUCT NAME	Eaton Moeller® series T3 On-off switch
CATALOG NUMBER	197456
EAN	4015080896357
PRODUCT LENGTH/DEPTH	250 mm
PRODUCT HEIGHT	147 mm
PRODUCT WIDTH	200 mm
PRODUCT WEIGHT	2.475 kg
CERTIFICATIONS	IEC/EN 60947 IEC/EN 60204 VDE 0660 IEC/EN 60947-3
MODEL CODE	T3-3-8342/SE2

Features & Functions

FITTED WITH:	Black thumb grip and front plate
INSCRIPTION	0-1
NUMBER OF POLES	Six-pole

General

DEGREE OF PROTECTION	NEMA 12
DEGREE OF PROTECTION (FRONT SIDE)	IP65
LIFESPAN, MECHANICAL	500,000 Operations
MOUNTING METHOD	Surface mounting
MOUNTING POSITION	As required
NUMBER OF CONTACT UNITS	3
OPERATING FREQUENCY	1200 Operations/h
OVERTVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	On-Off switch
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
SAFE ISOLATION	440 V AC, Between the contacts, According to EN 61140
SAFETY PARAMETER (EN ISO 13849-1)	B10d values as per EN ISO 13849-1, table C.1
SHOCK RESISTANCE	15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms
SUITABLE FOR	Ground mounting
SWITCHING ANGLE	90 °

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C

Terminal capacities

TERMINAL CAPACITY	1 x (0.75 - 4) mm ² , flexible with ferrules to DIN 46228 2 x (1 - 6) mm ² , solid or stranded 1 x (1 - 6) mm ² , solid or stranded 2 x (1 - 2.5) mm ² , solid or stranded 1 x (0.75 - 2.5) mm ² , flexible with ferrules to DIN 46228 1 x (1 - 2.5) mm ² , solid or stranded 2 x (0.75 - 4) mm ² , flexible with ferrules to DIN 46228 2 x (0.75 - 2.5) mm ² , flexible with ferrules to
--------------------------	--

	DIN 46228
SCREW SIZE	M4, Terminal screw
TIGHTENING TORQUE	17.7 lb-in, Screw terminals 1.6 Nm, Screw terminals

Electrical rating

RATED BREAKING

CAPACITY AT 220/230 V 260 A
(COS PHI TO IEC 60947-3)

RATED BREAKING

CAPACITY AT 400/415 V 260 A
(COS PHI TO IEC 60947-3)

RATED BREAKING

CAPACITY AT 500 V (COS PHI TO IEC 60947-3) 240 A

RATED BREAKING

CAPACITY AT 660/690 V 170 A
(COS PHI TO IEC 60947-3)

RATED OPERATIONAL

CURRENT (IE) AT AC-21, 440 V 32 A

RATED OPERATIONAL

CURRENT (IE) AT AC-23A, 230 V 32 A

RATED OPERATIONAL

CURRENT (IE) AT AC-23A, 400 V, 415 V 32 A

RATED OPERATIONAL

CURRENT (IE) AT AC-23A, 500 V 26.4 A

RATED OPERATIONAL

CURRENT (IE) AT AC-23A, 690 V 17 A

RATED OPERATIONAL

CURRENT (IE) AT AC-3, 220 V, 230 V, 240 V 23.7 A

RATED OPERATIONAL

CURRENT (IE) AT AC-3, 380 V, 400 V, 415 V 23.7 A

RATED OPERATIONAL

CURRENT (IE) AT AC-3, 500 V 23.7 A

RATED OPERATIONAL

CURRENT (IE) AT AC-3, 660 V, 690 V 14.7 A

RATED OPERATIONAL

CURRENT (IE) AT DC-1, LOAD-BREAK SWITCHES L/R 25 A
L/R = 1 MS

RATED OPERATIONAL

CURRENT (IE) AT DC-13, CONTROL SWITCHES L/R 20 A
= 50 MS

RATED OPERATIONAL

CURRENT (IE) AT DC-21, 1 A

Short-circuit rating

RATED CONDITIONAL

SHORT-CIRCUIT CURRENT (IQ) 1 kA

RATED SHORT-TIME

WITHSTAND CURRENT (ICW) 650 A, Contacts, 1 second
0.65 kA

SHORT-CIRCUIT

PROTECTION RATING 35 A gG/gL, Fuse, Contacts

240 V

RATED OPERATIONAL

CURRENT (IE) AT DC-23A, 12 A

120 V

RATED OPERATIONAL

CURRENT (IE) AT DC-23A, 25 A

24 V

RATED OPERATIONAL

CURRENT (IE) AT DC-23A, 5 A

240 V

RATED OPERATIONAL

CURRENT (IE) AT DC-23A, 25 A

48 V

RATED OPERATIONAL

CURRENT (IE) AT DC-23A, 25 A

60 V

RATED OPERATIONAL

CURRENT (IE) STAR- 32 A

DELTA AT AC-3, 220/230 V

RATED OPERATIONAL

CURRENT (IE) STAR- 32 A

DELTA AT AC-3, 380/400 V

RATED OPERATIONAL

CURRENT (IE) STAR- 32 A

DELTA AT AC-3, 500 V

RATED OPERATIONAL

CURRENT (IE) STAR- 25.5 A

DELTA AT AC-3, 690 V

RATED OPERATIONAL

POWER AT AC-23A, 7.5 kW

220/230 V, 50 Hz

RATED OPERATIONAL

POWER AT AC-23A, 400 V, 15 kW

50 Hz

RATED OPERATIONAL

POWER AT AC-23A, 500 V, 15 kW

50 Hz

RATED OPERATIONAL

POWER AT AC-23A, 690 V, 15 kW

50 Hz

RATED OPERATIONAL

POWER AT AC-3, 380/400

11 kW

V, 50 Hz

RATED OPERATIONAL

POWER AT AC-3, 415 V, 50

11 kW

Hz

RATED OPERATIONAL

POWER AT AC-3, 690 V, 50

11 kW

Hz

RATED OPERATIONAL 7.5 kW

POWER STAR-DELTA AT**220/230 V, 50 HZ****RATED OPERATIONAL****POWER STAR-DELTA AT** 15 kW
380/400 V, 50 HZ**RATED OPERATIONAL****POWER STAR-DELTA AT** 18.5 kW
500 V, 50 HZ**RATED OPERATIONAL****POWER STAR-DELTA AT** 22 kW
690 V, 50 HZ**RATED OPERATIONAL****VOLTAGE (UE) AT AC -** 690 V
MAX**RATED UNINTERRUPTED****CURRENT (IU)** 32 A**UNINTERRUPTED**
CURRENT

Rated uninterrupted current lu is specified for max. cross-section.

UNINTERRUPTED
CURRENT

Rated uninterrupted current lu is specified for max. cross-section.

Switching capacity

NUMBER OF CONTACTS	
IN SERIES AT DC-21A, 240 V	1
NUMBER OF CONTACTS	
IN SERIES AT DC-23A, 24 V	1
NUMBER OF CONTACTS	
IN SERIES AT DC-23A, 48 V	2
NUMBER OF CONTACTS	
IN SERIES AT DC-23A, 60 V	3
NUMBER OF CONTACTS	
IN SERIES AT DC-23A, 120 V	3
NUMBER OF CONTACTS	
IN SERIES AT DC-23A, 240 V	5
RATED MAKING	
CAPACITY UP TO 690 V (COS PHI TO IEC/EN 60947-3)	320 A
VOLTAGE PER CONTACT PAIR IN SERIES	60 V
LOAD RATING	1.6 x I _e (with intermittent operation class 12, 40 % duty factor) 1.3 x I _e (with intermittent operation class 12, 60 % duty factor) 2 x I _e (with intermittent operation class 12, 25 % duty factor)

Contacts

CONTROL CIRCUIT RELIABILITY	1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA)
NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	0

Actuator

ACTUATOR COLOR	Black
ACTUATOR FUNCTION	Maintained
ACTUATOR TYPE	Short thumb-grip

Design verification

10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO	UV resistance only in

ULTRA-VIOLET (UV) RADIATION	connection with protective shield.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 MECHANICAL FUNCTION

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

CATALOGUES	P Switch-disconnectors and T Rotary cam switches catalogue CA042001EN
DECLARATIONS OF CONFORMITY	DA-DC-00004923.pdf DA-DC-00004894.pdf
	eaton-rotary-switches-t0-main-switch-dimensions-004.eps
	eaton-rotary-switches-front-plate-t0-on-off-switch-symbol-002.eps
DRAWINGS	eaton-general-totally-insulated-t0-main-switch-symbol.eps
	eaton-rotary-switches-t0-changeover-switch-3d-drawing-002.eps
	eaton-general-rotary-switch-t0-step-switch-symbol.eps
ECAD MODEL	ETN.197456.edz
INSTALLATION INSTRUCTIONS	IL008055ZU
WIRING DIAGRAMS	eaton-rotary-switches-on-off-switch-t0-on-off-switch-wiring-diagram-003.eps

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

