

# PTSA 1,5/24-3,5-Z - PCB terminal block



1985412

<https://www.phoenixcontact.com/us/products/1985412>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



PCB terminal block, nominal current: 8 A, rated voltage (III/2): 400 V, nominal cross section: 1.5 mm<sup>2</sup>, number of potentials: 24, number of rows: 1, number of positions per row: 24, product range: PTSA 1,5, pitch: 3.5 mm, connection method: Push-in spring connection, mounting: Wave soldering, conductor/PCB connection direction: 45 °, color: green, Pin layout: Zigzag pinning W, Solder pin [P]: 3.5 mm, number of solder pins per potential: 1, type of packaging: packed in cardboard. Offset soldering legs, two-rowed

## Your advantages

- Time saving push-in connection, tools not required
- Defined contact force ensures that contact remains stable over the long term
- Angled connection enables multi-row arrangement on the PCB

## Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 1985412                        |
| Packing unit                         | 40 pc                          |
| Minimum order quantity               | 40 pc                          |
| Note                                 | Made to order (non-returnable) |
| Sales key                            | AA12                           |
| Product key                          | AALBDA                         |
| Catalog page                         | Page 305 (CC-2005)             |
| GTIN                                 | 4017918922481                  |
| Weight per piece (including packing) | 12.3 g                         |
| Weight per piece (excluding packing) | 9.211 g                        |
| Customs tariff number                | 85369010                       |
| Country of origin                    | CN                             |

# PTSA 1,5/24-3,5-Z - PCB terminal block



1985412

<https://www.phoenixcontact.com/us/products/1985412>

## Technical data

### Product properties

|                           |                                |
|---------------------------|--------------------------------|
| Product type              | Printed circuit board terminal |
| Product family            | PTSA 1,5                       |
| Product line              | COMBICON Terminals S           |
| Type                      | PC termination block           |
| Number of positions       | 24                             |
| Pitch                     | 3.5 mm                         |
| Number of connections     | 24                             |
| Number of rows            | 1                              |
| Number of potentials      | 24                             |
| Pin layout                | Zigzag pinning W               |
| Solder pins per potential | 1                              |

### Electrical properties

|                             |       |
|-----------------------------|-------|
| Nominal current $I_N$       | 8 A   |
| Nominal voltage $U_N$       | 400 V |
| Degree of pollution         | 3     |
| Rated voltage (III/3)       | 250 V |
| Rated surge voltage (III/3) | 4 kV  |
| Rated voltage (III/2)       | 400 V |
| Rated surge voltage (III/2) | 4 kV  |
| Rated voltage (II/2)        | 630 V |
| Rated surge voltage (II/2)  | 4 kV  |

### Connection data

#### Connection technology

|                       |                      |
|-----------------------|----------------------|
| Type                  | PC termination block |
| Nominal cross section | 1.5 mm <sup>2</sup>  |

#### Conductor connection

|                                                                       |                                              |
|-----------------------------------------------------------------------|----------------------------------------------|
| Connection method                                                     | Push-in spring connection                    |
| Conductor cross section rigid                                         | 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>  |
| Conductor cross section flexible                                      | 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>  |
| Conductor cross section AWG                                           | 24 ... 16                                    |
| Conductor cross section flexible, with ferrule without plastic sleeve | 0.25 mm <sup>2</sup> ... 1 mm <sup>2</sup>   |
| Conductor cross section, flexible, with ferrule, with plastic sleeve  | 0.25 mm <sup>2</sup> ... 0.5 mm <sup>2</sup> |
| Stripping length                                                      | 9 mm                                         |

### Mounting

|               |                  |
|---------------|------------------|
| Mounting type | Wave soldering   |
| Pin layout    | Zigzag pinning W |

# PTSA 1,5/24-3,5-Z - PCB terminal block



1985412

<https://www.phoenixcontact.com/us/products/1985412>

## Material specifications

### Material data - contact

|                                          |                                                                                  |
|------------------------------------------|----------------------------------------------------------------------------------|
| Note                                     | WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201 |
| Contact material                         | Cu alloy                                                                         |
| Surface characteristics                  | hot-dip tin-plated                                                               |
| Metal surface terminal point (top layer) | Tin (4 - 8 µm Sn)                                                                |
| Metal surface soldering area (top layer) | Tin (4 - 8 µm Sn)                                                                |

### Material data - housing

|                                                                   |              |
|-------------------------------------------------------------------|--------------|
| Color (Housing)                                                   | green (6021) |
| Insulating material                                               | PA           |
| Insulating material group                                         | I            |
| CTI according to IEC 60112                                        | 600          |
| Flammability rating according to UL 94                            | V0           |
| Glow wire flammability index GWFI according to EN 60695-2-12      | 850          |
| Glow wire ignition temperature GWIT according to EN 60695-2-13    | 775          |
| Temperature for the ball pressure test according to EN 60695-10-2 | 125 °C       |

### Material data – actuating element

|                           |              |
|---------------------------|--------------|
| Color (Actuating element) | green (6021) |
|---------------------------|--------------|

## Dimensions

|                       |               |
|-----------------------|---------------|
| Dimensional drawing   |               |
| Pitch                 | 3.5 mm        |
| Width [w]             | 85.5 mm       |
| Height [h]            | 16.7 mm       |
| Length [l]            | 12 mm         |
| Installed height      | 13.1 mm       |
| Solder pin length [P] | 3.5 mm        |
| Pin dimensions        | 0.4 x 0.75 mm |

### PCB design

|               |        |
|---------------|--------|
| Pin spacing   | 3.5 mm |
| Hole diameter | 1 mm   |

## Mechanical tests

Test for conductor damage and slackening

# PTSA 1,5/24-3,5-Z - PCB terminal block



1985412

<https://www.phoenixcontact.com/us/products/1985412>

|               |                     |
|---------------|---------------------|
| Specification | IEC 60999-1:1999-11 |
| Result        | Test passed         |

## Pull-out test

|                                                                                |                                         |
|--------------------------------------------------------------------------------|-----------------------------------------|
| Specification                                                                  | IEC 60999-1:1999-11                     |
| Conductor cross section/conductor type/tractive force<br>setpoint/actual value | 0.2 mm <sup>2</sup> / solid / > 10 N    |
|                                                                                | 0.2 mm <sup>2</sup> / flexible / > 10 N |
|                                                                                | 1.5 mm <sup>2</sup> / solid / > 40 N    |
|                                                                                | 1.5 mm <sup>2</sup> / flexible / > 40 N |

## Electrical tests

### Temperature-rise test

|                                   |                                                                                                                                |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Specification                     | IEC 60947-7-4:2013-08                                                                                                          |
| Requirement temperature-rise test | The sum of ambient temperature and temperature rise of the PCB terminal block shall not exceed the upper limiting temperature. |

### Short-time withstand current

|               |                       |
|---------------|-----------------------|
| Specification | IEC 60947-7-4:2013-08 |
|---------------|-----------------------|

### Insulation resistance

|                                              |                       |
|----------------------------------------------|-----------------------|
| Specification                                | IEC 60512-3-1:2002-02 |
| Insulation resistance, neighboring positions | > 5 MΩ                |

### Air clearances and creepage distances |

|                                                        |                                                       |
|--------------------------------------------------------|-------------------------------------------------------|
| Specification                                          | IEC 60947-1:2007-06 + A1:2010-12 + A2:2014-09         |
| Insulating material group                              | I                                                     |
| Comparative tracking index (IEC 60112)                 | CTI 600                                               |
| Rated insulation voltage (III/3)                       | 250 V                                                 |
| Rated surge voltage (III/3)                            | 4 kV                                                  |
| minimum clearance value - non-homogenous field (III/3) | 3 mm                                                  |
| minimum creepage distance (III/3)                      | 3.2 mm                                                |
| Note on connection cross section                       | With connected conductor 1.5 mm <sup>2</sup> (solid). |
| Rated insulation voltage (III/2)                       | 400 V                                                 |
| Rated surge voltage (III/2)                            | 4 kV                                                  |
| minimum clearance value - non-homogenous field (III/2) | 3 mm                                                  |
| minimum creepage distance (III/2)                      | 3 mm                                                  |
| Rated insulation voltage (II/2)                        | 630 V                                                 |
| Rated surge voltage (II/2)                             | 4 kV                                                  |
| minimum clearance value - non-homogenous field (II/2)  | 3 mm                                                  |
| minimum creepage distance (II/2)                       | 3.2 mm                                                |

## Environmental and real-life conditions

### Vibration test

|               |                       |
|---------------|-----------------------|
| Specification | IEC 60068-2-6:2007-12 |
| Frequency     | 10 - 150 - 10 Hz      |

# PTSA 1,5/24-3,5-Z - PCB terminal block



1985412

<https://www.phoenixcontact.com/us/products/1985412>

|                        |                             |
|------------------------|-----------------------------|
| Sweep speed            | 1 octave/min                |
| Amplitude              | 0.35 mm (10 Hz ... 60.1 Hz) |
| Acceleration           | 5g (60.1 Hz ... 150 Hz)     |
| Test duration per axis | 2.5 h                       |

## Glow-wire test

|                  |                        |
|------------------|------------------------|
| Specification    | IEC 60695-2-10:2000-10 |
| Temperature      | 850 °C                 |
| Time of exposure | 5 s                    |

## Aging

|               |                       |
|---------------|-----------------------|
| Specification | IEC 60947-7-4:2013-08 |
|---------------|-----------------------|


## Ambient conditions

|                                         |                                                                               |
|-----------------------------------------|-------------------------------------------------------------------------------|
| Ambient temperature (operation)         | -40 °C ... 100 °C (Depending on the current carrying capacity/derating curve) |
| Ambient temperature (storage/transport) | -40 °C ... 70 °C                                                              |
| Relative humidity (storage/transport)   | 30 % ... 70 %                                                                 |
| Ambient temperature (assembly)          | -5 °C ... 85 °C                                                               |

## Packaging specifications

|                   |                     |
|-------------------|---------------------|
| Type of packaging | packed in cardboard |
|-------------------|---------------------|

## Drawings



### Type: PTSA 1,5/4-3,5-Z

Tested in accordance with DIN EN 60512-5-2:2003-01

Reduction factor = 1

Number of positions: 4

### Drilling plan/solder pad geometry



The figure shows the drilling plan of the 5-pos. version of the article – Zig-zag pinning starts at the right-hand position. Other pinning available on request.

# PTSA 1,5/24-3,5-Z - PCB terminal block



1985412

<https://www.phoenixcontact.com/us/products/1985412>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1985412>

|  <b>cULus Recognized</b><br>Approval ID: E60425-20030527 |                       |                       |                   |                             |
|-------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                                                                                                                           | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| Use group B                                                                                                                               | 300 V                 | 5 A                   | 24 - 16           | -                           |
| Use group D                                                                                                                               | 300 V                 | 5 A                   | 24 - 16           | -                           |

|  <b>VDE Gutachten mit Fertigungsüberwachung</b><br>Approval ID: 40018594 |                       |                       |                   |                             |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                                                                                                                                           | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|                                                                                                                                                           | 250 V                 | 2 A                   | -                 | 0.5 - 0.75                  |

|  <b>VDE Zeichengenehmigung</b><br>Approval ID: 40057505 |                       |                       |                   |                             |
|--------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                                                                                                                            | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|                                                                                                                                            | 400 V                 | 8 A                   | -                 | 0.2 - 1.5                   |

# PTSA 1,5/24-3,5-Z - PCB terminal block



1985412

<https://www.phoenixcontact.com/us/products/1985412>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27460101 |
| ECLASS-12.0 | 27460101 |
| ECLASS-13.0 | 27460101 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002643 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# PTSA 1,5/24-3,5-Z - PCB terminal block



1985412

<https://www.phoenixcontact.com/us/products/1985412>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

# PTSA 1,5/24-3,5-Z - PCB terminal block



1985412

<https://www.phoenixcontact.com/us/products/1985412>

## Accessories

### SZS 0,4X2,5 VDE - Screwdriver

1205037

<https://www.phoenixcontact.com/us/products/1205037>



Screwdriver, slot-headed, VDE insulated, size: 0.4 x 2.5 x 80 mm, 2-component grip, with non-slip grip

---

### CRIMPFOX 6 - Crimping pliers

1212034

<https://www.phoenixcontact.com/us/products/1212034>



Crimping pliers, for ferrules without insulating collar according to DIN 46228 Part 1 and ferrules with insulating collar according to DIN 46228 Part 4, 0.25 mm<sup>2</sup> ... 6.0 mm<sup>2</sup>, lateral entry, trapezoidal crimp

---

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)