

PRODUCT-DETAILS

RBR101R-24VUC

RBR101R-24VUC Interface relay R600 1n/o,A1-A2=24VAC/DC,5-250VAC/60mA-6A, with integrated output contact protection



General Information

Extended Product Type	RBR101R-24VUC
Product ID	1SNA645519R0600
EAN	4013614508301
Catalog Description	RBR101R-24VUC Interface relay R600 1n/o,A1-A2=24VAC/DC,5-250VAC/60mA-6A, with integrated output contact protection
Long Description	The RBR101R-24VUC is a boxed interface relay with spring terminals, which can be seamlessly snap-on mounted onto a DIN Rail. The relay is soldered into device housing, ensuring a high resistance against vibration and this is further enhanced by the spring terminals which improve contact reliability by automatically adjusting the tension to the wire gauge. This relay operates with a 24 V AC/DC rated control supply voltage and has a 1 n/c (SPST) output with contacts rated at 250 V / 6 A. This 6mm wide boxed interface relay may be used for electrical isolation, amplification and signal matching and enables the switching of high currents on a small footprint. It has an integrated LED, which provides the visual indication of the energization of the relay coil and UL 94 -V0 certified device housing, improving safety by providing high levels flame retardation. Jumper bars are available as accessories.

Ordering

Minimum Order Quantity	5 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical Information	2CDC110004C0210_05
-----------------------------------	--------------------

Instructions and
Manuals

1SVC645000M9000

Dimensions

Product Net Width	12 mm
Product Net Height	67.5 mm
Product Net Depth / Length	75 mm
Product Net Weight	0.04 kg

Technical

Function	Boxed interface relay R600
Sub-Function	Relay with built in LED and RC circuit
Output	1 n/c contact
Output Signal	5 ... 250VAC / 60mA ... 6A
Rated Control Supply Voltage (U _s)	24 V AC/DC
Terminal Type	Spring Terminals

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CB Certificate	CB_DK-53188-UL
CCC Certificate	CCC_2017010303941444
CQC Certificate	CQC_2017010303941444
CSA Certificate	CSA_254821
cUR Certificate	cUR_E352056
Declaration of Conformity - CCC	CCC_2020980303000254
Declaration of Conformity - CE	1SVD982016-0001
Declaration of Conformity - UKCA	1SVD982016-1000
EAC Certificate	EAC_RU_C-FR.ME77.B.01634
Instructions and Manuals	1SVC645000M9000
LR Certificate	LR_16_20068
RoHS Information	1SVD982016-0001
UR Certificate	UR_E352056

Container Information

Package Level 1 Units	box 5 piece
Package Level 1 Width	73 mm
Package Level 1 Height	71 mm
Package Level 1 Depth / Length	80 mm
Package Level 1 Gross Weight	0.24 kg
Package Level 1 EAN	3472596455194

Classifications

Object Classification	K	
Code		
ETIM 4	EC001437 - Switching relay	
ETIM 5	EC001437 - Switching relay	
ETIM 6	EC001437 - Switching relay	
ETIM 7	EC001437 - Switching relay	
ETIM 8	EC001437 - Switching relay	
eClass	V11.0 : 27371601	
UNSPSC	39122331	
E-Number (Sweden)	4001115	

Categories

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Interface Relays and Optocouplers

