

Product Net Width	21.2 mm
Product Net Height	35.6 mm
Product Net Depth / Length	27.5 mm
Product Net Weight	0.033 kg

Technical

Function	Pluggable miniature interface relay CR-M
Sub-Function	Relay w/o built in LED
Output	4 c/o (SPDT) contacts
Output Signal	250 V / 6 A
Rated Control Supply Voltage (U _s)	120 V AC

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CCC Certificate	CCC_2014010303720193
CQC Certificate	CQC2014010303720193
CSA Certificate	CSA_2735700
cUR Certificate	cUR_E244330
Declaration of Conformity - CCC (CCC)	2020980303000200
Declaration of Conformity - CE	1SVD982021
EAC Certificate	EAC_RU_C-DE.ME77.B.00446-19
Environmental Information	1SAA981009-2401
Instructions and Manuals	1SVC405600M9000
LR Certificate	LR_05_20002_E5
RMRS Certificate	RMRS_1740019250
RoHS Information	1SVD982021-0001
UR Certificate	UR_E244330
VDE Certificate	VDE_40040327

Container Information

Package Level 1 Units	10 piece
Package Level 1 Width	114 mm
Package Level 1 Height	61 mm
Package Level 1 Depth / Length	50 mm
Package Level 1 Gross Weight	0.35 kg
Package Level 1 EAN	4013614373558

Classifications

Object Classification Code	K
ETIM 4	EC001437 - Switching relay

ETIM 5	EC001437 - Switching relay
ETIM 6	EC001437 - Switching relay
ETIM 7	EC001437 - Switching relay
eClass	7.0 27371601
UNSPSC	39122331

Categories

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Interface Relays and Optocouplers

