

PRODUCT-DETAILS

CR-U024AC2L

CR-U024AC2L Pluggable interface relay 2c/o, A1-A2=24VAC, 250V/10A, LED



| General Information | |
|-----------------------|--|
| Extended Product Type | CR-U024AC2L |
| Product ID | 1SVR405621R0100 |
| EAN | 4013614498367 |
| Catalog Description | CR-U024AC2L Pluggable interface relay 2c/o, A1-A2=24VAC, 250V/10A, LED |
| Long Description | The CR-U024AC2L pluggable interface relay is from the CR-U (universal) relay range. This relay operates with a 24 V AC rated control supply voltage and has 2 c/o (SPDT) output contacts rated at 250 V / 10 A. The relay has an integrated orange test button for manual actuation and locking of the output contacts and an integrated LED. Standard sockets, logic sockets, pluggable function modules, holder and marker are available as accessories. |

| | Standard sockets, logic sockets, pluggable function modules, holder and marker are available as accessories. |
|--------------------------------------|--|
| Ordering | |
| Minimum Order Quantity | 10 piece |
| Customs Tariff Number | 85364900 |
| Popular Downloads | |
| Data Sheet, Technical Information | 2CDC117003D0205 |
| Instructions and | 1SVC405600M9000 |

Dimensions

VDE_40019116

| Product Net Width | 35 mm |
|----------------------------|----------|
| Product Net Height | 54.4 mm |
| Product Net Depth / Length | 35 mm |
| Product Net Weight | 0.083 kg |

| Technical | |
|---|--|
| Function | Pluggable universal interface relay CR-U |
| Sub-Function | Relay with built in LED |
| Output | 2 c/o (SPDT) contacts |
| Output Signal | 250 V / 10 A |
| Rated Control Supply Voltage (U _s) | 24 V AC |

Environmental

VDE Certificate

RoHS Status Following EU Directive 2011/65/EU

| Certificates and Declarations (Document Number) | |
|---|-----------------------------|
| CCC Certificate | CCC_2017010303949759 |
| CQC Certificate | CQC2017010303949759 |
| CSA Certificate | CSA_1587291 |
| Declaration of Conformity - CCC (CCC) | 2020980303000199 |
| Declaration of Conformity - CE | 1SVD982021 |
| EAC Certificate | EAC_RU_C-DE.ME77.B.00446-19 |
| Environmental Information | 1SAA981009-2401 |
| Instructions and Manuals | 1SVC405600M9000 |
| LR Certificate | LR_05_20002_E5 |
| RMRS Certificate | RMRS_1740019250 |
| RoHS Information | 1SVD982021-0001 |
| UR Certificate | UR_E244330 |

| Container Information | |
|-----------------------------------|---------------|
| Package Level 1 Units | 10 piece |
| Package Level 1 Width | 182 mm |
| Package Level 1 Height | 76 mm |
| Package Level 1 Depth / Length | 77 mm |
| Package Level 1 Gross Weight | 0.87 kg |
| Package Level 1 EAN | 4013614374098 |

| Classifications | |
|-------------------------------|----------------------------|
| Object Classification Code | К |
| ETIM 4 | EC001437 - Switching relay |
| ETIM 5 | EC001437 - Switching relay |

CR-U024AC2L

| ETIM 6 | EC001437 - Switching relay |
|-------------------|----------------------------|
| ETIM 7 | EC001437 - Switching relay |
| eClass | 7.0 27371601 |
| UNSPSC | 39122331 |
| E-Number (Sweden) | 4005411 |

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Control\ Products \rightarrow Electronic\ Relays\ and\ Controls \rightarrow Interface\ Relays\ and\ Optocouplers$

