

Detailed information for: CT-MFE

This page contains technical data sheet, documents library and links to offering related to this product. If you require any other information, please contact us using form located at the bottom of the page.

Data Sheet

Documentation

CT-MFE

General Information

Extended Product Type: CT-MFE

Product ID: 1SVR550029R8100

EAN: 4013614346156

Catalog Description: CT-MFE Time relay, multifunction 1c/o, 0.05s-100h, 24-240VAC/DC

Long Description: The CT-MFE is a multifunction electronic time relay from the CT-E timer range. It provides 6 timing functions with 8 time ranges from 0.05 s to 100 h. This time relay operates with a rated control supply voltage of 24 - 240 V AC / DC and has a 1 c/o (SPDT) output rated at 250 V / 4 A. A control input works with voltage-related (non-floating) triggering.



Categories

Products » Low Voltage Products and Systems » Control Products » Electronic Relays and Controls » Time Delay Relays



Ordering

EAN: 4013614346156

Minimum Order Quantity: 1 piece

Customs Tariff Number: 85364900

Container Information

Package Level 1 Units: 1 piece

Package Level 1 Width: 81 mm

Package Level 1 Depth / Length: 26 mm

Package Level 1 Height: 83.1 mm

Package Level 1 Gross Weight:	0.086 kg
Package Level 1 EAN:	4013614346156
Dimensions	
Product Net Width:	22.5 mm
Product Net Height:	78 mm
Product Net Depth / Length:	78.5 mm
Product Net Weight:	0.07 kg

Technical

Timer Relay Type:	ON-Delay OFF-Delay Impulse ON Flasher Starting with ON Flasher Starting with OFF Pulse Former
Time Range:	0.05 s - 100 h
Rated Control Supply Voltage (U_s):	24 ... 240 V AC/DC
Output:	1 c/o (SPDT) contact
Terminal Type:	Screw Terminals
Rated Operational Current AC-12 (230 V) 4 A (I_e):	
Rated Operational Current AC-15 (230 V) 3 A (I_e):	
Rated Operational Current DC-12 (24 V) 4 A (I_e):	
Rated Operational Current DC-13 (24 V) 2 A (I_e):	
Mounting Position:	Any
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Standards:	EN 50581 IEC/EN 61812-1 UL 508 CAN/CSA C22.2 No.14

Environmental

RoHS Status:	Following EU Directive 2011/65/EU
---------------------	-----------------------------------

Certificates and Declarations (Document Number)

CB Certificate:	<u>CB_DK-8575</u>
CCC Certificate:	<u>CCC_2010010303393101</u>
cUL Certificate:	<u>cUL508_E140448</u>
Data Sheet, Technical Information:	<u>2CDC111145D0201</u>
Declaration of Conformity - CE:	<u>1SVD981002-0001</u>
DNV GL Certificate:	<u>DNV_GL_TAA00000F2</u>
EAC Certificate:	<u>EAC_RU_C-DE.ME77.B.02016</u>
Environmental Information:	<u>1SAA981011-2402</u>
Instructions and Manuals:	<u>1SVC550021M1000</u>

RMRS Certificate:	_____
RoHS Information:	<u>1SVD981002-0001</u>
UL Certificate:	_____

Classifications

Object Classification Code:	K
E-nummer:	4033072
ETIM 4:	EC001439 - Timer relay
ETIM 5:	EC001439 - Timer relay
ETIM 6:	EC001439 - Timer relay
ETIM 7:	EC001439 - Timer relay
eClass:	7.0 27371790
UNSPSC:	39121519