

## PRODUCT-DETAILS

# CT-WBS.22S

CT-WBS.22S Time relay, impulse & flasher  
2c/o, 24-48VDC, 24-240VAC



## General Information

Extended Product Type	CT-WBS.22S
Product ID	1SVR730040R3300
EAN	4016779851435
Catalog Description	CT-WBS.22S Time relay, impulse & flasher 2c/o, 24-48VDC, 24-240VAC
Long Description	The CT-WBS.22S is an electronic impulse and flasher time relay from the CT-S timer range. It provides 7 timing functions with 10 time ranges from 0.05 s to 300 h. This time relay operates with a rated control supply voltage of 24 - 48 V DC / 24 - 240 V AC and has a 2 c/o (SPDT) output with contacts rated at 250 V / 4 A. A sealable transparent cover for protection against unauthorized changes is available as accessory. The device offers screw connection technology with double-chamber cage connection terminals.

## Ordering

EAN	4016779851435
Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

## Popular Downloads

Data Sheet, Technical Information	2CDC110004C0210_01
Instructions and Manuals	1SVC730050M1000

## Dimensions

Product Net Width	22.5 mm
Product Net Height	85.6 mm
Product Net Depth / Length	103.7 mm
Product Net Weight	0.123 kg

## Technical

Timer Relay Type	Flasher Starting with OFF Flasher Starting with ON Impulse ON ON-Delay Adjustable Impulse with Fixed Time Delay Fixed Impulse with Adjustable Time Delay ON / OFF Function
Time Range	0.05 s ... 300 h
Rated Control Supply Voltage (U <sub>s</sub> )	24 ... 240 V AC 24 ... 48 V DC
Rated Frequency (f)	50 Hz 60 Hz DC
Output	2 c/o (SPDT) contacts
Terminal Type	Screw Terminals
Rated Operational Current AC-12 (I <sub>e</sub> )	(230 V) 4 A
Rated Operational Current AC-15 (I <sub>e</sub> )	(230 V) 3 A
Rated Operational Current DC-12 (I <sub>e</sub> )	(24 V) 4 A
Rated Operational Current DC-13 (I <sub>e</sub> )	(24 V) 2 A
Minimum Switching Capacity	12 V 10 mA
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	Input Circuit 4 kV Output Circuit 1 / Output Circuit 2 4 kV
Rated Insulation Voltage (U <sub>i</sub> )	Input Circuit / Output Circuit 500 V Output Circuit 1 / Output Circuit 2 300 V
Degree of Protection	Housing IP50 Terminals IP20
Overvoltage Category	III
Pollution Degree	3
Short-Circuit Protective Devices	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
Electrical Durability	AC-12 100000 cycle
Mechanical Durability	30000000 cycle
Connecting Capacity	Flexible with Ferrule 1x 0.5 ... 2.5 mm <sup>2</sup> Flexible with Ferrule 2x 0.5 ... 1.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1x 0.5 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 0.5 ... 1.5 mm <sup>2</sup> Flexible 1x 0.5 ... 2.5 mm <sup>2</sup> Flexible 2x 0.5 ... 1.5 mm <sup>2</sup> Rigid 1x 0.5 ... 4 mm <sup>2</sup> Rigid 2x 0.5 ... 2.5 mm <sup>2</sup>
Tightening Torque	0.6 ... 0.8 N·m
Wire Stripping Length	8 mm
Recommended Screw Driver	Pozidriv 1 0.8 x 4 4.5
Mounting Position	1 ... 6
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715

## Standards

CAN/CSA C22.2 No.14  
IEC/EN 63000  
IEC/EN 61812-1  
UL 508

## Technical UL/CSA

Maximum Operating Voltage UL/CSA	Output Circuit 300 V AC
Contact Rating UL/CSA	B300
Connecting Capacity UL/CSA	Flexible 1x 18-14 AWG Flexible 2x 18-16 AWG Rigid 1x 20-12 AWG Rigid 2x 20-14 AWG
Tightening Torque UL/CSA	7.08 in-lb

## Environmental

Ambient Air Temperature	Operation -25 ... +60 °C Storage -40 ... +85 °C
Maximum Operating Altitude Permissible	Without Derating 2000 m
RoHS Status	Following EU Directive 2011/65/EU

## Certificates and Declarations (Document Number)

CQC Certificate	CQC2007010303255979
cULus Certificate	cULus508_20110711-E140448A
Data Sheet, Technical Information	2CDC110004C0210_01
Declaration of Conformity - CCC	2020980303000207
Declaration of Conformity - CE	1SVD981008
Declaration of Conformity - UKCA	1SVD981008-10
DNV GL Certificate	DNV_GL_TAA00000XR
EAC Certificate	EAC_RU_C-DE.ME77.B.00568/20
Instructions and Manuals	1SVC730050M1000
RMRS Certificate	RMRS_1740021250
RoHS Information	1SVD981008

## Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	97 mm
Package Level 1 Depth / Length	30 mm
Package Level 1 Height	109 mm
Package Level 1 Gross Weight	0.145 kg
Package Level 1 EAN	4016779851435

## Classifications

Object Classification Code	K
----------------------------	---

ETIM 4	EC001439 - Timer relay
ETIM 5	EC001439 - Timer relay
ETIM 6	EC001439 - Timer relay
ETIM 7	EC001439 - Timer relay
eClass	V11.0 : 27371605
UNSPSC	39121519
E-Number (Finland)	2712201
E-Number (Sweden)	4033113

---

## Categories

---

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Time Relays → CT-S

