

PRODUCT-DETAILS

CM-PVS.31P

CM-PVS.31P Three-phase monitoring relay
2c/o, 0,0.1-30s, L1-L2-L3=3x160-300VAC



General Information

| | |
|-----------------------|--|
| Extended Product Type | CM-PVS.31P |
| Product ID | 1SVR740794R1300 |
| EAN | 4016779852012 |
| Catalog Description | CM-PVS.31P Three-phase monitoring relay 2c/o, 0,0.1-30s, L1-L2-L3=3x160-300VAC |
| Long Description | <p>The CM-PVS.31P relay is from the CM three-phase monitors range. This relay operates with a rated control supply voltage / three-phase measuring voltage of 160-300 V AC and has a 2 c/o output with contacts rated at 250 V / 4 A. The CM-PVS.31P monitors the phase parameters over/undervoltage and phase failure. The corresponding threshold values are adjustable. Phase sequence monitoring as well as an ON or OFF tripping delay are selectable. The tripping delay is adjustable over a range of instantaneous to 30 s (0, 0.1-30 s). A sealable transparent cover for protection against unauthorized changes is available as accessory. The device offers maintenance free Easy Connect Technology with push-in terminals.</p> |

Ordering

| | |
|------------------------|----------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85364900 |

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 2CDC112211D0201 |
| Instructions and Manuals | 1SVC730510M0000 |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width | 22.5 mm |
| Product Net Depth / Length | 103.7 mm |
| Product Net Height | 85.6 mm |
| Product Net Weight | 0.132 kg |

Technical

| | |
|---|---|
| Function | Phase failure detection Phase sequence monitoring Over- and undervoltage monitoring |
| Standards | CAN/CSA C22.2 No.14 EN 50581 IEC/EN 60255-27 IEC/EN 61000-6-2 IEC/EN 61000-6-3 UL 508 |
| Measuring Range | (L-L) 160 ... 300 V AC |
| Rated Control Supply Voltage (U _s) | (L-L) 160 ... 300 V AC |
| Rated Frequency (f) | Supply Circuit 50/60 Hz |
| Output | 2 c/o (SPDT) contacts |
| Time Range | 200 ms start-up delay 0 s or 0.1 ... 30 s tripping delay (ON or OFF) |
| Terminal Type | Screwless Terminals |
| Rated Operational Current AC-12 (I _e) | (230 V) 4 A |
| Rated Operational Current AC-15 (I _e) | (230 V) 3 A |
| Rated Operational Current DC-12 (I _e) | (24 V) 4 A |
| Rated Operational Current DC-13 (I _e) | (24 V) 2 A |
| Minimum Switching Capacity | 24 V 10 mA |
| Rated Insulation Voltage (U _i) | Input Circuit / Output Circuit 600 V Output Circuit 1 / Output Circuit 2 300 V |
| Rated Impulse Withstand Voltage (U _{imp}) | Input Circuit 6 kV Output Circuit 4 kV |
| Degree of Protection | Housing IP50 Terminals IP20 |
| Overvoltage Category | III |
| Pollution Degree | 3 |
| Short-Circuit Protective Devices | Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A |
| Electrical Durability | AC-12 100000 cycle |
| Mechanical Durability | 30000000 cycle |
| Connecting Capacity | Flexible with Ferrule 2x 0.5 ... 1.5 mm ² Flexible with Insulated Ferrule 2x 0.5 ... 1.5 mm ² Flexible 2x 0.5 ... 1.5 mm ² Rigid 2x 0.5 ... 1.5 mm ² |
| Wire Stripping Length | 8 mm |
| Mounting Position | Any |
| Mounting on DIN Rail | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 |

Environmental

| | |
|-------------------------|--|
| Ambient Air Temperature | Operation -25 ... +60 °C Storage -40 ... +85 °C |
| RoHS Status | Following EU Directive 2011/65/EU |

Technical UL/CSA

| | |
|----------------------------------|---|
| Maximum Operating Voltage UL/CSA | Output Circuit 300 V AC |
| Contact Rating UL/CSA | B300 |
| Connecting Capacity UL/CSA | Flexible 2x 18-16 AWG Rigid 2x 20-16 AWG |

Certificates and Declarations (Document Number)

| | |
|---------------------------------------|---------------------------|
| CCC Certificate | CCC_2009010303326655 |
| CQC Certificate | CQC2009010303326655 |
| cULus Certificate | cULus508_20120829-E140448 |
| Declaration of Conformity - CCC (CCC) | 2020980303000197 |
| Declaration of Conformity - CE | 1SVD981014 |
| DNV GL Certificate | DNV_GL_TAA000017D |
| EAC Certificate | EAC_RU_C-DE.ME77.B.03424 |
| Environmental Information | 1SAA981020-2401 |
| Instructions and Manuals | 1SVC730510M0000 |
| RMRS Certificate | RMRS_1740020250 |
| RoHS Information | 1SVD981014 |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | 1 piece |
| Package Level 1 Width | 97 mm |
| Package Level 1 Height | 109 mm |
| Package Level 1 Depth / Length | 30 mm |
| Package Level 1 Gross Weight | 0.157 kg |
| Package Level 1 EAN | 4016779852012 |

Classifications

| | |
|----------------------------|-----------------------------------|
| Object Classification Code | B |
| ETIM 4 | EC001441 - Phase monitoring relay |
| ETIM 5 | EC001441 - Phase monitoring relay |
| ETIM 6 | EC001441 - Phase monitoring relay |
| ETIM 7 | EC001441 - Phase monitoring relay |
| eClass | 7.0 27371803 |
| UNSPSC | 39121536 |
| E-Number (Sweden) | 3860602 |

Categories

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Three Phase Monitors

