

PRODUCT-DETAILS

CM-ESS.2P

CM-ESS.2P Voltage monitoring relay 2c/o, B-C=3-600VRMS, 24-240VAC/DC



General Information

| | |
|-----------------------|----------------------------------------------------------------------|
| Extended Product Type | CM-ESS.2P |
| Product ID | 1SVR740830R0400 |
| EAN | 4016779852401 |
| Catalog Description | CM-ESS.2P Voltage monitoring relay 2c/o, B-C=3-600VRMS, 24-240VAC/DC |

Long Description

The CM-ESS.2P is a single-functional voltage monitoring relay from the CM single-phase monitors range. This monitoring relay operates with a rated control supply voltage of 24 - 240 V AC / DC and has a 2 c/o (SPDT) output with contacts rated at 250 V / 4 A. It provides a RMS measuring principle for DC and AC voltages with 4 measuring ranges: 3-30 V, 6-60 V, 30-300 V and 60-600 V and works according to the open-circuit principle. The CM-ESS.2P is configurable for over- or undervoltage monitoring. The hysteresis is adjustable within a range of 3 to 30 % of the threshold value and the tripping delay is adjustable over a range of instantaneous to 30 s (0, 0.1-30 s). A sealable transparent cover for protection against unauthorized changes is available as accessory. The device offers maintenance free Easy Connect Technology with push-in terminals.

Ordering

| | |
|------------------------|---------------|
| EAN | 4016779852401 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85364900 |

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 2CDC112172D0201 |
|-----------------------------------|-----------------|

Dimensions

| | |
|-------------------------------|----------|
| Product Net Width | 22.5 mm |
| Product Net Depth / Length | 103.7 mm |
| Product Net Height | 85.6 mm |
| Product Net Weight | 0.142 kg |

Technical

| | |
|--------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Function | Over- or undervoltage monitoring |
| Measuring Range | 3 ... 30 V 6 ... 60 V 30 ... 300 V 60 ... 600 V |
| Rated Control Supply Voltage (U _s) | 24 ... 240 V AC/DC |
| Output | 2 c/o (SPDT) contacts |
| Time Range | 0 s or 0.1 ... 30 s tripping delay (ON) |
| Terminal Type | Screwless Terminals |
| Rated Operational Current AC-12 (I _e) | (230 V) 4 A |
| Rated Operational Current AC-15 (I _e) | (230 V) 3 A |
| Rated Operational Current DC-12 (I _e) | (24 V) 4 A |
| Rated Operational Current DC-13 (I _e) | (24 V) 2 A |
| Minimum Switching Capacity | 24 V 10 mA |
| Rated Insulation Voltage (U _i) | Measuring Circuit / Output Circuit 600 V Output Circuit 1 / Output Circuit 2 250 V Supply Circuit / Measuring Circuit 600 V Supply Circuit / Output Circuit 250 V |
| Rated Impulse Withstand Voltage (U _{imp}) | Measuring Circuit / Output Circuit 6 kV Output Circuit 1 / Output Circuit 2 4 kV Output Circuit 4 kV Supply Circuit / Measuring Circuit 6 kV Supply Circuit / Output Circuit 4 kV |
| Degree of Protection | Housing IP50 Terminals IP20 |
| Overvoltage Category | III |
| Pollution Degree | 3 |
| Short-Circuit Protective Devices | Output Circuit NC - F Type Fuses 10 A Output Circuit NO - F Type Fuses 10 A |
| Electrical Durability | AC-12 100000 cycle |
| Mechanical Durability | 30000000 cycle |
| Connecting Capacity | Flexible with Ferrule 2x 0.5 ... 1.5 mm ² Flexible with Insulated Ferrule 2x 0.5 ... 1.5 mm ² Flexible 2x 0.5 ... 1.5 mm ² Rigid 2x 0.5 ... 1.5 mm ² |
| Wire Stripping Length | 8 mm |
| Mounting Position | 1 ... 6 |
| Mounting on DIN Rail | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 |
| Standards | CAN/CSA C22.2 No.14 IEC/EN 63000 IEC/EN 60255-27 IEC/EN 61000-6-2 IEC/EN 61000-6-3 |

UL 508

Technical UL/CSA

| | |
|----------------------------------|---------------------------------------------|
| Maximum Operating Voltage UL/CSA | Output Circuit 300 V AC |
| Contact Rating UL/CSA | B300 |
| Connecting Capacity UL/CSA | Flexible 2x 18-16 AWG Rigid 2x 20-16 AWG |

Environmental

| | |
|----------------------------------------|----------------------------------------------------|
| Ambient Air Temperature | Operation -20 ... +60 °C Storage -40 ... +85 °C |
| Maximum Operating Altitude Permissible | Without Derating 2000 m |
| RoHS Status | Following EU Directive 2011/65/EU |

Certificates and Declarations (Document Number)

| | |
|-----------------------------------|---------------------------|
| CB Certificate | CB_DK-28255-UL |
| CQC Certificate | CQC2007010303243843 |
| cULus Certificate | cULus508_20120203-E140448 |
| Data Sheet, Technical Information | 2CDC112172D0201 |
| Declaration of Conformity - CCC | 2020980303000196 |
| Declaration of Conformity - CE | 1SVD981013-00 |
| Declaration of Conformity - UKCA | 1SVD981013-10 |
| DNV GL Certificate | DVN_GL_TAA0000292 |
| EAC Certificate | EAC_RU_C-DE.ME77.B.03424 |
| Instructions and Manuals | 1SVC730710M1000 |
| RoHS Information | 1SVD981013-00 |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 97 mm |
| Package Level 1 Height | 109 mm |
| Package Level 1 Depth / Length | 30 mm |
| Package Level 1 Gross Weight | 0.164 kg |
| Package Level 1 EAN | 4016779852401 |

Classifications

| | |
|----------------------------|-------------------------------------|
| Object Classification Code | B |
| ETIM 4 | EC001438 - Voltage monitoring relay |
| ETIM 5 | EC001438 - Voltage monitoring relay |
| ETIM 6 | EC001438 - Voltage monitoring relay |
| ETIM 7 | EC001438 - Voltage monitoring relay |
| eClass | V11.0 : 27371801 |
| UNSPSC | 39121514 |

E-Number (Finland)

2712247

E-Number (Sweden)

3860642

Categories

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Single Phase Monitors

