

PRODUCT-DETAILS

CM-ESS.1P

CM-ESS.1P Voltage monitoring relay 1c/o, B-C=3-600VRMS, 110-130VAC



General Information

Extended Product Type	CM-ESS.1P
Product ID	1SVR740831R0300
EAN	4016779852425
Catalog Description	CM-ESS.1P Voltage monitoring relay 1c/o, B-C=3-600VRMS, 110-130VAC
Long Description	<p>The CM-ESS.1P is a single-functional voltage monitoring relay from the CM single-phase monitors range. This monitoring relay operates with a rated control supply voltage of 110 - 130 V AC and has a 1 c/o (SPDT) output contact rated at 250 V / 4 A. It provides a RMS measuring principle for DC and AC voltages with 4 measuring ranges: 3-30 V, 3-60 A, 30-300 V and 60-600 V and works according to the open-circuit principle. The CM-ESS.1P is configurable for over- or undervoltage monitoring, the hysteresis is adjustable within a range of 3 to 30 % of the threshold value. A sealable transparent cover for protection against unauthorized changes is available as accessory. The device offers maintenance free Easy Connect Technology with push-in terminals.</p>

Ordering

EAN	4016779852425
Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical Information	2CDC112171D0201
Instructions and	1SVC730590M0000

Manuals

Dimensions

Product Net Width	22.5 mm
Product Net Depth / Length	103.7 mm
Product Net Height	85.6 mm
Product Net Weight	0.155 kg

Technical

Function	Over- or undervoltage monitoring
Measuring Range	3 ... 30 V 6 ... 60 V 30 ... 300 V 60 ... 600 V
Rated Control Supply Voltage (U _s)	110 ... 130 V AC
Output	1 c/o (SPDT) contact
Terminal Type	Screwless Terminals
Rated Operational Current AC-12 (I _e)	(230 V) 4 A
Rated Operational Current AC-15 (I _e)	(230 V) 3 A
Rated Operational Current DC-12 (I _e)	(24 V) 4 A
Rated Operational Current DC-13 (I _e)	(24 V) 2 A
Minimum Switching Capacity	24 V 10 mA
Rated Insulation Voltage (U _i)	Measuring Circuit / Output Circuit 600 V Output Circuit 1 / Output Circuit 2 250 V Supply Circuit / Measuring Circuit 600 V Supply Circuit / Output Circuit 250 V
Rated Impulse Withstand Voltage (U _{imp})	Measuring Circuit / Output Circuit 6 kV Output Circuit 1 / Output Circuit 2 4 kV Supply Circuit / Measuring Circuit 6 kV Supply Circuit / Output Circuit 4 kV
Degree of Protection	Housing IP50 Terminals IP20
Overvoltage Category	III
Pollution Degree	3
Short-Circuit Protective Devices	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
Electrical Durability	AC-12 100000 cycle
Mechanical Durability	30000000 cycle
Connecting Capacity	Flexible with Ferrule 2x 0.5 ... 1.5 mm ² Flexible with Insulated Ferrule 2x 0.5 ... 1.5 mm ² Flexible 2x 0.5 ... 1.5 mm ² Rigid 2x 0.5 ... 1.5 mm ²
Wire Stripping Length	8 mm
Mounting Position	Any
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Standards	CAN/CSA C22.2 No.14 EN 50178 EN 50581 IEC/EN 60255-27 IEC/EN 61000-6-2 IEC/EN 61000-6-3 UL 508

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Output Circuit 300 V AC
Contact Rating UL/CSA	B300
Connecting Capacity UL/CSA	Flexible 2x 18-16 AWG Rigid 2x 20-16 AWG

Environmental

Ambient Air Temperature	Operation -20 ... +60 °C Storage -40 ... +85 °C
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

CB Certificate	CB_DK-28255-UL
CCC Certificate	CCC_2007010303243843.pdf
CQC Certificate	CQC2007010303243843
cULus Certificate	cULus508_20120203-E140448
Data Sheet, Technical Information	2CDC112171D0201
Declaration of Conformity - CCC (CCC)	2020980303000196
Declaration of Conformity - CE	1SVD981013
DNV GL Certificate	DVN_GL_TAA0000292
EAC Certificate	EAC_RU_C-DE.ME77.B.03424
Environmental Information	1SAA981019-2401
Instructions and Manuals	1SVC730590M0000
RMRS Certificate	RMRS_1740020250
RoHS Information	1SVD981013

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	97 mm
Package Level 1 Height	109 mm
Package Level 1 Depth / Length	30 mm
Package Level 1 Gross Weight	0.178 kg
Package Level 1 EAN	4016779852425

Classifications

Object Classification Code	B
ETIM 4	EC001438 - Voltage monitoring relay
ETIM 5	EC001438 - Voltage monitoring relay
ETIM 6	EC001438 - Voltage monitoring relay
ETIM 7	EC001438 - Voltage monitoring relay
eClass	7.0 27371801
UNSPSC	39121514
E-Number (Sweden)	3860644

Categories

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Single Phase Monitors

