

PRODUCT-DETAILS

CM-ENS.11P CM-ENS.11P Liquid level monitoring relay 1c/o, sensitivity 5-100kOhm



General Information

Extended Product Type	CM-ENS.11P
Product ID	1SVR740850R0100
EAN	4013614502873
Catalog Description	CM-ENS.11P Liquid level monitoring relay 1c/o, sensitivity 5-100kOhm
Long Description	The CM-ENS.11P belongs to the CM liquid level monitoring relay range. It operates with a rated control supply voltage of 24 - 240 V AC/DC and has a 1 c/o (SPDT) output with contacts rated at 250 V / 4 A. It monitors liquid levels of conductive fluids and protects pumps against dry running or tanks against overflow and works according to the open-circuit principle. The sensitivity can be selected via front-face potentiometers. Several electrodes and a sealable transparent cover for protection against unauthorized changes are available as accessory. The device offers maintenance free Easy Connect Technology with push-in terminals.

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical Information

2CDC112228D0201

Dimensions	
Product Net Width	22.5 mm
Product Net Height	85.6 mm
Product Net Depth / Length	103.7 mm
Product Net Weight	0.117 kg

Technical	
Function	Filling or draining monitoring
Measuring Range	5 100 kΩ
Number of Electrodes	3
Rated Control Supply Voltage (U _s)	24 240 V AC/DC
Output	1 c/o (SPDT) contact
Terminal Type	Screwless Terminals
Rated Operational Current AC-12 (I _e)	(230 V) 4 A
Rated Operational Current AC-15 (I _e)	(230 V) 3 A
Rated Operational Current DC-12 (I _e)	(24 V) 4 A
Rated Operational Current DC-13 (I _e)	(24 V) 2 A
Minimum Switching Capacity	12 V 10 mA
Rated Insulation Voltage (U _i)	Measuring Circuit / Output Circuit 300 V Output Circuit 1 / Output Circuit 2 300 V Supply Circuit / Measuring Circuit 300 V Supply Circuit / Output Circuit 300 V
Rated Impulse Withstand Voltage (U _{imp})	Measuring Circuit / Output Circuit 4 kV Output Circuit 1 / Output Circuit 2 4 kV Supply Circuit / Measuring Circuit 4 kV Supply Circuit / Output Circuit 4 kV
Degree of Protection	Housing IP50 Terminals IP20
Overvoltage Category	
Pollution Degree	3
Short-Circuit Protective Devices	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
Electrical Durability	AC-12 100000 cycle
Mechanical Durability	1000000 cycle
Connecting Capacity	Flexible with Ferrule 2x 0.5 1.5 mm² Flexible with Insulated Ferrule 2x 0.5 1.5 mm² Flexible 2x 0.5 1.5 mm² Rigid 2x 0.5 1.5 mm²
Wire Stripping Length	8 mm
Mounting Position	Any
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715

Standards	CAN/CSA C22.2 No.14 EN 50581 IEC/EN 60255-27 IEC/EN 61000-6-2 IEC/EN 61000-6-3 UL 508	
Technical UL/CSA		
Maximum Operating Voltage UL/CSA	Output Circuit 300 V AC	
Contact Rating UL/CSA	B300	
Connecting Capacity UL/CSA	Flexible 2x 18-16 AWG Rigid 2x 20-16 AWG	
Environmental		
Ambient Air Temperature	Operation -25 +60 °C Storage -40 +85 °C	
RoHS Status	Following EU Directive 2011/65/E	
Certificates and Declarations (Document Number)		
CCC Certificate	CCC_2015010303819793	
CQC Certificate		
cULus Certificate	cULus508_20150627-E140448	
Declaration of Conformity - CCC (CCC)	2020980303000198	
Declaration of Conformity - CE	1SVD981005	
DNV GL Certificate	DNV_GL_TAA00000RW	
EAC Certificate	EAC_RU_C-DE.ME77.B.02330	
Instructions and Manuals	1SVC730680M0000	
RMRS Certificate	RMRS_1740020250	
RoHS Information	1SVD981005	
Container Information		
Package Level 1 Units	1 piece	
Package Level 1 Width	97 mm	
Package Level 1 Height	109 mm	
Package Level 1 Depth / Length	30 mm	
Package Level 1 Gross Weight	0.142 kg	
Package Level 1 EAN	4013614502873	
Classifications		
Object Classification Code	В	
ETIM 5	EC001447 - (Fill) level monitoring relay	

ETIM 6	EC001447 - (Fill) level monitoring relay
ETIM 7	EC001447 - (Fill) level monitoring relay
eClass	7.0 27371813

Categories

Low Voltage Products and Systems

→ Control Products
→ Electronic Relays and Controls
→ Liquid Level Monitors and Controls

