



PRODUCT-DETAILS

CM-MPN.62S

CM-MPN.62S Three-phase monitoring relay 2c/o, 0,0.1-30s, L1-L2-L3=3x450-720VAC



General Information	
Extended Product Type	CM-MPN.62S
Product ID	1SVR750488R8300
EAN	4016779851923
Catalog Description	CM-MPN.62S Three-phase monitoring relay 2c/o, 0,0.1-30s, L1-L2-L3=3x450-720VAC
Long Description	The CM-MPN.62S is a multifunctional relay from the CM three-phase monitors range. It operates with a rated control supply voltage / three-phase measuring voltage of 450-720 V AC 50/60 Hz and has a 2 c/o (SPDT) output with contacts rated at 250 V / 4 A. This relay monitors all phase parameters such as over/undervoltage, phase unbalance and phase failure. The corresponding threshold values are adjustable. The CM-MPN.62S also offers selection of phase sequence monitoring, automatic phase sequence correction as well as an ON or OFF tripping delay. The output contacts can be configured as 1x2 c/o (SPDT) contacts (common signal) or 2x1 c/o (SPDT) contact (separate signal for over- and undervoltage thresholds) operation. The tripping delay is adjustable over a range of instantaneous to 30 s (0, 0.1-30 s). A sealable transparent cover for protection against unauthorized changes is available as accessory. The device offers screw connection technology with double-chamber cage connection terminals.

Ordering	
EAN	4016779851923

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical Information	2CDC112177D0201
Instructions and Manuals	1SVC730730M1000 1SVC730730M0000
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	45 mm
Product Net Height	85.6 mm
Product Net Depth / Length	104.8 mm
Product Net Weight	0.229 kg

Technical

Function	Automatic phase sequence correction Over- and undervoltage monitoring Phase failure detection Phase unbalance detection Phase sequence monitoring
Measuring Range	(L-L) 450 ... 720 V AC
Time Range	0 s or 0.1 ... 30 s tripping delay (ON or OFF) 200 ms start-up delay
Rated Control Supply Voltage (U _s)	(L-L) 450 ... 720 V AC
Rated Frequency (f)	Supply Circuit 50/60 Hz
Output	2 x 1 c/o or 1 x 2 c/o contacts, configurable
Terminal Type	Screw Terminals
Rated Operational Current AC-12 (I _e)	(230 V) 4 A
Rated Operational Current AC-15 (I _e)	(230 V) 3 A
Rated Operational Current DC-12 (I _e)	(24 V) 4 A
Rated Operational Current DC-13 (I _e)	(24 V) 2 A
Minimum Switching Capacity	24 V 10 mA
Rated Impulse Withstand Voltage (U _{imp})	Input Circuit 8 kV Output Circuit 4 kV
Rated Insulation Voltage (U _i)	Input Circuit / Output Circuit 1000 V Output Circuit 1 / Output Circuit 2 300 V
Degree of Protection	Housing IP50 Terminals IP20
Overvoltage Category	III
Pollution Degree	3
Short-Circuit Protective Devices	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
Electrical Durability	AC-12 100000 cycle

Mechanical Durability	30000000 cycle
Connecting Capacity	Flexible with Ferrule 1x 0.5 ... 2.5 mm ² Flexible with Ferrule 2x 0.5 ... 1.5 mm ² Flexible with Insulated Ferrule 1x 0.5 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.5 ... 1.5 mm ² Flexible 1x 0.5 ... 2.5 mm ² Flexible 2x 0.5 ... 1.5 mm ² Rigid 1x 0.5 ... 4 mm ² Rigid 2x 0.5 ... 2.5 mm ²
Tightening Torque	0.6 ... 0.8 N·m
Wire Stripping Length	8 mm
Recommended Screw Driver	4.5 0.8 x 4 Pozidriv 1
Mounting Position	1 ... 6
Mounting on DIN Rail	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Standards	CAN/CSA C22.2 No.14 IEC/EN 63000 IEC/EN 60255-27 IEC/EN 61000-6-2 IEC/EN 61000-6-3 UL 508

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Output Circuit 300 V AC
Contact Rating UL/CSA	B300
Connecting Capacity UL/CSA	Flexible 1x 18-14 AWG Flexible 2x 18-16 AWG Rigid 2x 20-14 AWG Rigid 1x 20-12 AWG
Tightening Torque UL/CSA	7.08 in·lb
Pilot Duty UL/CSA	B300
Flammability According to UL94	V-0

Environmental

Ambient Air Temperature	Operation -25 ... +60 °C Storage -40 ... +85 °C
Maximum Operating Altitude Permissible	Without Derating 2000 m

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SVD981001-4501
RoHS Information	1SVD981001-4401
RoHS Status	Following EU Directive 2011/65/EU
SCIP	ed8406db-b97c-4121-a8ab-f4c938737332 Germany (DE)
Simplified SCIP	a743da96-07b1-4512-b1a3-e8870c3c04bc Germany (DE) 596e5c42-317c-42c4-aec6-5d102e078f00 Germany (DE) bd87286b-b527-420b-aa5f-530cd58e0645 Belgium (BE) 3c13dd38-6ef6-47f8-9cab-3c5d7859ccd2 Spain (ES)

21fd10cc-8e47-4fcc-ad74-735c765c5dce France (FR)
f199a684-090d-4a18-9c09-c5f842bde5b5 Sweden (SE)
5bdcbcf8-23c5-4d0c-a82b-8803d04c8810 Sweden (SE)
8af1df27-815f-4875-87ba-1e87f6fae979 Poland (PL)
dddeb3bb3-ebe3-41b3-b02d-99e23fba9bde France (FR)
a2468177-5115-43eb-b88d-2a987faadf14 Hungary (HU)
1719eedc-510c-4e76-b162-4ada9b424a07 Belgium (BE)
504f76ac-7d6c-46cf-af26-4a5199414bb5 Netherlands (NL)
d46f6dfe-be19-4aa3-bcda-904e7a7513ba Poland (PL)
f21400b8-6000-4908-9b0f-5c719238aaad Hungary (HU)
33eec99d-5cae-47b2-b29b-ab5969a7ce86 Greece (GR)
8b35842f-9962-4c83-b0ae-de2cb0803565 Portugal (PT)
c11f42de-7049-4914-8d6e-4d5099bd0e82 Bulgaria (BG)
f6ad2335-7d96-4207-a2cc-4b2e660a867e Germany (DE)
c1eca859-ac61-4fa9-b121-bffb4de2e7d8 Italy (IT)
77105afd-4155-4212-92d3-c717e214c9d5 Estonia (EE)
180a6f4d-0e0d-4836-b89d-bda3c4fb7103 Croatia (HR)
61c288ed-d0a8-49b9-b22c-0768269c8f74 Germany (DE)
aa76cdbe-b189-4e3b-9031-27577d1ac39d Denmark (DK)
8416e21a-06ec-4b7e-ab21-d40c62540bc6 Czech Republic (CZ)
7a77d4a3-c650-4917-8c4a-f023578e0d1a Norway (NO)
65d2d722-ff32-48d7-9e6b-e25bc27806b8 Poland (PL)
b50c1051-ffb2-4f5f-acf7-8cf48e82de1e Finland (FI)

Toxic Substances
Control Act - TSCA

2CMT2023-006536

Certificates and Declarations

CB Certificate	CB_DK-27946-UL
CQC Certificate	CQC2009010303326655
cULus Certificate	cULus508_20120829-E140448
Declaration of Conformity - CCC	2020980303000197
Declaration of Conformity - CE	1SVD981014-00
Declaration of Conformity - UKCA	1SVD981014-10
DNV GL Certificate	DNV_GL_TAA000017D

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	97 mm
Package Level 1 Depth / Length	52.5 mm
Package Level 1 Height	109 mm
Package Level 1 Gross Weight	0.254 kg
Package Level 1 EAN	4016779851923

External Classifications and Standards

Object Classification Code	B
ETIM 7	EC001441 - Phase monitoring relay
ETIM 8	EC001441 - Phase monitoring relay
ETIM 9	EC001441 - Phase monitoring relay
eClass	V11.0 : 27371803
UNSPSC	39122332
E-Number (Finland)	2712266

E-Number (Norway)	4188144
E-Number (Sweden)	3860593

Categories

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Three Phase Monitors

