

# Specifications

Photo is representative

## Eaton 020484

Eaton Moeller® series T3 Multi-speed switches, T3, 32 A, flush mounting, 4 contact unit(s), Contacts: 7, 60 °, maintained, With 0 (Off) position, 0-1-2, SOND 29, Design number 47

### General specifications

|                             |                                                                                                                                                                                                                                                           |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>PRODUCT NAME</b>         | Eaton Moeller® series T3 Multi-speed switch                                                                                                                                                                                                               |
| <b>CATALOG NUMBER</b>       | 020484                                                                                                                                                                                                                                                    |
| <b>EAN</b>                  | 4015080204848                                                                                                                                                                                                                                             |
| <b>PRODUCT LENGTH/DEPTH</b> | 114 mm                                                                                                                                                                                                                                                    |
| <b>PRODUCT HEIGHT</b>       | 54 mm                                                                                                                                                                                                                                                     |
| <b>PRODUCT WIDTH</b>        | 61 mm                                                                                                                                                                                                                                                     |
| <b>PRODUCT WEIGHT</b>       | 0.252 kg                                                                                                                                                                                                                                                  |
| <b>CERTIFICATIONS</b>       | UL<br>CSA File No.: 012528<br>CE<br>CSA-C22.2 No. 60947-4-1-14<br>IEC/EN 60204<br>IEC/EN 60947<br>VDE 0660<br>CSA<br>UL 60947-4-1<br>UL Category Control No.: NLRV<br>UL File No.: E36332<br>CSA Class No.: 3211-05<br>IEC/EN 60947-3<br>CSA-C22.2 No. 94 |
| <b>CATALOG NOTES</b>        | Rated Short-time<br>Withstand Current (Icw)<br>for a time of 1 second                                                                                                                                                                                     |
| <b>MODEL CODE</b>           | T3-4-47/E                                                                                                                                                                                                                                                 |

## Features & Functions

|                             |                                                      |
|-----------------------------|------------------------------------------------------|
| <b>ENCLOSURE MATERIAL</b>   | Plastic                                              |
| <b>FITTED WITH:</b>         | 0 (off) position<br>Black thumb grip and front plate |
| <b>INSCRIPTION</b>          | 0-1-2                                                |
| <b>NUMBER OF POLES</b>      | 3                                                    |
| <b>SWITCH FUNCTION TYPE</b> | 2 speeds, 2 separate windings                        |

## General

|                                               |                                                                               |
|-----------------------------------------------|-------------------------------------------------------------------------------|
| <b>DEGREE OF PROTECTION</b>                   | NEMA 1<br>IP65<br>NEMA 12                                                     |
| <b>DEGREE OF PROTECTION (FRONT SIDE)</b>      | IP65<br>NEMA 12                                                               |
| <b>LIFESPAN, MECHANICAL</b>                   | 500,000 Operations                                                            |
| <b>MODEL</b>                                  | Pole switch                                                                   |
| <b>MOUNTING METHOD</b>                        | Flush mounting                                                                |
| <b>MOUNTING POSITION</b>                      | As required                                                                   |
| <b>NUMBER OF CONTACT UNITS</b>                | 4                                                                             |
| <b>OPERATING FREQUENCY</b>                    | 1200 Operations/h                                                             |
| <b>OVERVOLTAGE CATEGORY</b>                   | III                                                                           |
| <b>POLLUTION DEGREE</b>                       | 3                                                                             |
| <b>PRODUCT CATEGORY</b>                       | Control switches                                                              |
| <b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b> | 6000 V AC                                                                     |
| <b>SAFE ISOLATION</b>                         | 440 V AC, Between the contacts, According to EN 61140                         |
| <b>SAFETY PARAMETER (EN ISO 13849-1)</b>      | B10d values as per EN ISO 13849-1, table C.1                                  |
| <b>SHOCK RESISTANCE</b>                       | 15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms |
| <b>SUITABLE FOR</b>                           | Branch circuits, suitable as motor disconnect, (UL/CSA)<br>Front mounting     |
| <b>SWITCHING ANGLE</b>                        | 60 °                                                                          |
| <b>TYPE</b>                                   | Multi-speed switch                                                            |

## Climatic environmental conditions

|                                            |        |
|--------------------------------------------|--------|
| <b>AMBIENT OPERATING TEMPERATURE - MIN</b> | -25 °C |
|--------------------------------------------|--------|

|                                            |       |
|--------------------------------------------|-------|
| <b>AMBIENT OPERATING TEMPERATURE - MAX</b> | 50 °C |
|--------------------------------------------|-------|

|                                                       |        |
|-------------------------------------------------------|--------|
| <b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN</b> | -25 °C |
|-------------------------------------------------------|--------|

|                                                       |       |
|-------------------------------------------------------|-------|
| <b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX</b> | 40 °C |
|-------------------------------------------------------|-------|

|                          |                                                                                |
|--------------------------|--------------------------------------------------------------------------------|
| <b>CLIMATIC PROOFING</b> | Damp heat, constant, to IEC 60068-2-78<br>Damp heat, cyclic, to IEC 60068-2-30 |
|--------------------------|--------------------------------------------------------------------------------|

## Terminal capacities

|                                                  |                                                                                                                  |
|--------------------------------------------------|------------------------------------------------------------------------------------------------------------------|
| <b>TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)</b> | 1 x (0.75 - 4) mm <sup>2</sup> , ferrules to DIN 46228<br>2 x (0.75 - 4) mm <sup>2</sup> , ferrules to DIN 46228 |
|--------------------------------------------------|------------------------------------------------------------------------------------------------------------------|

|                                                            |         |
|------------------------------------------------------------|---------|
| <b>TERMINAL CAPACITY (SOLID/FLEXIBLE WITH FERRULE AWG)</b> | 14 - 10 |
|------------------------------------------------------------|---------|

|                                           |                                                            |
|-------------------------------------------|------------------------------------------------------------|
| <b>TERMINAL CAPACITY (SOLID/STRANDED)</b> | 1 x (1 - 6) mm <sup>2</sup><br>2 x (1 - 6) mm <sup>2</sup> |
|-------------------------------------------|------------------------------------------------------------|

|                   |                    |
|-------------------|--------------------|
| <b>SCREW SIZE</b> | M4, Terminal screw |
|-------------------|--------------------|

|                          |                                                        |
|--------------------------|--------------------------------------------------------|
| <b>TIGHTENING TORQUE</b> | 17.7 lb-in, Screw terminals<br>1.6 Nm, Screw terminals |
|--------------------------|--------------------------------------------------------|

## Electrical rating

**RATED BREAKING  
CAPACITY AT 220/230 V  
(COS PHI TO IEC 60947-3)** 260 A

**RATED BREAKING  
CAPACITY AT 400/415 V  
(COS PHI TO IEC 60947-3)** 260 A

**RATED BREAKING  
CAPACITY AT 500 V (COS  
PHI TO IEC 60947-3)** 240 A

**RATED BREAKING  
CAPACITY AT 660/690 V  
(COS PHI TO IEC 60947-3)** 170 A

**RATED OPERATIONAL  
CURRENT (IE)** 32 A at AC-3, 230 V star-  
delta  
25.5 A at AC-3, 690 V star-  
delta  
32 A at AC-3, 500 V star-  
delta  
32 A at AC-3, 400 V star-  
delta

**RATED OPERATIONAL  
CURRENT (IE) AT AC-3,  
220 V, 230 V, 240 V** 23.7 A

**RATED OPERATIONAL  
CURRENT (IE) AT AC-3,  
380 V, 400 V, 415 V** 23.7 A

**RATED OPERATIONAL  
CURRENT (IE) AT AC-3,  
500 V** 23.7 A

**RATED OPERATIONAL  
CURRENT (IE) AT AC-3,  
660 V, 690 V** 14.7 A

**RATED OPERATIONAL  
CURRENT (IE) AT AC-21,  
440 V** 32 A

**RATED OPERATIONAL  
CURRENT (IE) AT AC-23A,  
230 V** 32 A

**RATED OPERATIONAL  
CURRENT (IE) AT AC-23A,  
400 V, 415 V** 32 A

**RATED OPERATIONAL  
CURRENT (IE) AT AC-23A,  
500 V** 26.4 A

**RATED OPERATIONAL  
CURRENT (IE) AT AC-23A,  
690 V** 17 A

**RATED OPERATIONAL  
CURRENT (IE) AT DC-1,** 25 A

## Short-circuit rating

**RATED CONDITIONAL  
SHORT-CIRCUIT CURRENT  
(IQ)** 1 kA

**RATED SHORT-TIME  
WITHSTAND CURRENT  
(ICW)** 650 A, Contacts, 1 second

**SHORT-CIRCUIT CURRENT  
RATING (BASIC RATING)** 40A, max. Fuse, SCCR  
(UL/CSA)  
5 kA, SCCR (UL/CSA)

**SHORT-CIRCUIT CURRENT  
RATING (HIGH FAULT)** 40 A, Class J, max. Fuse,  
SCCR (UL/CSA)  
10 kA, SCCR (UL/CSA)

**SHORT-CIRCUIT  
PROTECTION RATING** 35 A gG/gL, Fuse, Contacts

---

**LOAD-BREAK SWITCHES****L/R = 1 MS**

|                                                                                          |      |
|------------------------------------------------------------------------------------------|------|
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT DC-13,<br/>CONTROL SWITCHES L/R<br/>= 50 MS</b> | 20 A |
|------------------------------------------------------------------------------------------|------|

|                                                               |     |
|---------------------------------------------------------------|-----|
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT DC-21,<br/>240 V</b> | 1 A |
|---------------------------------------------------------------|-----|

|                                                               |      |
|---------------------------------------------------------------|------|
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT DC-23A,<br/>24 V</b> | 25 A |
|---------------------------------------------------------------|------|

|                                                               |      |
|---------------------------------------------------------------|------|
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT DC-23A,<br/>48 V</b> | 25 A |
|---------------------------------------------------------------|------|

|                                                               |      |
|---------------------------------------------------------------|------|
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT DC-23A,<br/>60 V</b> | 25 A |
|---------------------------------------------------------------|------|

|                                                                |      |
|----------------------------------------------------------------|------|
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT DC-23A,<br/>120 V</b> | 12 A |
|----------------------------------------------------------------|------|

|                                                                |     |
|----------------------------------------------------------------|-----|
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT DC-23A,<br/>240 V</b> | 5 A |
|----------------------------------------------------------------|-----|

|                                                                  |       |
|------------------------------------------------------------------|-------|
| <b>RATED OPERATIONAL<br/>POWER AT AC-3, 380/400<br/>V, 50 HZ</b> | 12 kW |
|------------------------------------------------------------------|-------|

|                                                              |       |
|--------------------------------------------------------------|-------|
| <b>RATED OPERATIONAL<br/>POWER AT AC-3, 415 V, 50<br/>HZ</b> | 11 kW |
|--------------------------------------------------------------|-------|

|                                                              |       |
|--------------------------------------------------------------|-------|
| <b>RATED OPERATIONAL<br/>POWER AT AC-3, 690 V, 50<br/>HZ</b> | 11 kW |
|--------------------------------------------------------------|-------|

|                                                                    |        |
|--------------------------------------------------------------------|--------|
| <b>RATED OPERATIONAL<br/>POWER AT AC-23A,<br/>220/230 V, 50 HZ</b> | 7.5 kW |
|--------------------------------------------------------------------|--------|

|                                                                |       |
|----------------------------------------------------------------|-------|
| <b>RATED OPERATIONAL<br/>POWER AT AC-23A, 400 V,<br/>50 HZ</b> | 15 kW |
|----------------------------------------------------------------|-------|

|                                                                |       |
|----------------------------------------------------------------|-------|
| <b>RATED OPERATIONAL<br/>POWER AT AC-23A, 500 V,<br/>50 HZ</b> | 15 kW |
|----------------------------------------------------------------|-------|

|                                                                |       |
|----------------------------------------------------------------|-------|
| <b>RATED OPERATIONAL<br/>POWER AT AC-23A, 690 V,<br/>50 HZ</b> | 15 kW |
|----------------------------------------------------------------|-------|

|                                                                       |        |
|-----------------------------------------------------------------------|--------|
| <b>RATED OPERATIONAL<br/>POWER STAR-DELTA AT<br/>220/230 V, 50 HZ</b> | 7.5 kW |
|-----------------------------------------------------------------------|--------|

|                                                  |       |
|--------------------------------------------------|-------|
| <b>RATED OPERATIONAL<br/>POWER STAR-DELTA AT</b> | 15 kW |
|--------------------------------------------------|-------|

---

|                                                           |                                                                     |
|-----------------------------------------------------------|---------------------------------------------------------------------|
| <b>380/400 V, 50 HZ</b>                                   |                                                                     |
| <b>RATED OPERATIONAL POWER STAR-DELTA AT 500 V, 50 HZ</b> | 18.5 kW                                                             |
| <b>RATED OPERATIONAL POWER STAR-DELTA AT 690 V, 50 HZ</b> | 22 kW                                                               |
| <b>RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX</b>         | 690 V                                                               |
| <b>RATED UNINTERRUPTED CURRENT (IU)</b>                   | 32 A                                                                |
| <b>UNINTERRUPTED CURRENT</b>                              | Rated uninterrupted current Iu is specified for max. cross-section. |

## Switching capacity

|                    |                                                                               |
|--------------------|-------------------------------------------------------------------------------|
| <b>LOAD RATING</b> | 1.6 x I <sub>e</sub> (with intermittent operation class 12, 40 % duty factor) |
|                    | 2 x I <sub>e</sub> (with intermittent operation class 12, 25 % duty factor)   |
|                    | 1.3 x I <sub>e</sub> (with intermittent operation class 12, 60 % duty factor) |

### NUMBER OF CONTACTS IN SERIES AT DC-21A, 240 V

1

### NUMBER OF CONTACTS IN SERIES AT DC-23A, 24 V

1

### NUMBER OF CONTACTS IN SERIES AT DC-23A, 48 V

2

### NUMBER OF CONTACTS IN SERIES AT DC-23A, 60 V

3

### NUMBER OF CONTACTS IN SERIES AT DC-23A, 120 V

3

### NUMBER OF CONTACTS IN SERIES AT DC-23A, 240 V

5

### SWITCHING CAPACITY (MAIN CONTACTS, GENERAL USE)

25 A, Rated uninterrupted current max. (UL/CSA)

### SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)

10A, IU, (UL/CSA)

### SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)

A600 (UL/CSA)  
P600 (UL/CSA)

### RATED MAKING CAPACITY UP TO 690 V (COS PHI TO IEC/EN 60947-3)

320 A

### VOLTAGE PER CONTACT PAIR IN SERIES

60 V

## Motor rating

### ASSIGNED MOTOR

**POWER AT 115/120 V, 60 HZ, 1-PHASE** 1.5 HP

### ASSIGNED MOTOR

**POWER AT 200/208 V, 60 HZ, 1-PHASE** 3 HP

### ASSIGNED MOTOR

**POWER AT 200/208 V, 60 HZ, 3-PHASE** 3 HP

### ASSIGNED MOTOR

**POWER AT 230/240 V, 60 HZ, 1-PHASE** 3 HP

### ASSIGNED MOTOR

**POWER AT 230/240 V, 60 HZ, 3-PHASE** 3 HP

### ASSIGNED MOTOR

**POWER AT 460/480 V, 60 HZ, 3-PHASE** 7.5 HP

### ASSIGNED MOTOR

**POWER AT 575/600 V, 60 HZ, 3-PHASE** 10 HP

## Contacts

|                                        |                                                                                                  |
|----------------------------------------|--------------------------------------------------------------------------------------------------|
| <b>CONTROL CIRCUIT<br/>RELIABILITY</b> | 1 failure per 100,000<br>switching operations<br>statistically determined, at<br>24 V DC, 10 mA) |
|----------------------------------------|--------------------------------------------------------------------------------------------------|

|                                                                     |   |
|---------------------------------------------------------------------|---|
| <b>NUMBER OF AUXILIARY<br/>CONTACTS (CHANGE-<br/>OVER CONTACTS)</b> | 0 |
|---------------------------------------------------------------------|---|

|                                                                        |   |
|------------------------------------------------------------------------|---|
| <b>NUMBER OF AUXILIARY<br/>CONTACTS (NORMALLY<br/>CLOSED CONTACTS)</b> | 0 |
|------------------------------------------------------------------------|---|

|                                                                      |   |
|----------------------------------------------------------------------|---|
| <b>NUMBER OF AUXILIARY<br/>CONTACTS (NORMALLY<br/>OPEN CONTACTS)</b> | 0 |
|----------------------------------------------------------------------|---|

|                           |   |
|---------------------------|---|
| <b>NUMBER OF CONTACTS</b> | 7 |
|---------------------------|---|

## Actuator

|                          |                                     |
|--------------------------|-------------------------------------|
| <b>ACTUATOR FUNCTION</b> | Maintained<br>With 0 (Off) position |
|--------------------------|-------------------------------------|

|                      |                  |
|----------------------|------------------|
| <b>ACTUATOR TYPE</b> | Short thumb-grip |
|----------------------|------------------|

## Design verification

|                                                           |     |
|-----------------------------------------------------------|-----|
| <b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b> | 0 W |
|-----------------------------------------------------------|-----|

|                                        |     |
|----------------------------------------|-----|
| <b>HEAT DISSIPATION CAPACITY PDISS</b> | 0 W |
|----------------------------------------|-----|

|                                                          |       |
|----------------------------------------------------------|-------|
| <b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b> | 1.1 W |
|----------------------------------------------------------|-------|

|                                                                      |      |
|----------------------------------------------------------------------|------|
| <b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b> | 32 A |
|----------------------------------------------------------------------|------|

|                                                           |     |
|-----------------------------------------------------------|-----|
| <b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b> | 0 W |
|-----------------------------------------------------------|-----|

|                                    |                                            |
|------------------------------------|--------------------------------------------|
| <b>10.2.2 CORROSION RESISTANCE</b> | Meets the product standard's requirements. |
|------------------------------------|--------------------------------------------|

|                                                                 |                                            |
|-----------------------------------------------------------------|--------------------------------------------|
| <b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b> | Meets the product standard's requirements. |
|-----------------------------------------------------------------|--------------------------------------------|

|                                                                                   |                                            |
|-----------------------------------------------------------------------------------|--------------------------------------------|
| <b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b> | Meets the product standard's requirements. |
|-----------------------------------------------------------------------------------|--------------------------------------------|

|                                                                                         |                                            |
|-----------------------------------------------------------------------------------------|--------------------------------------------|
| <b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b> | Meets the product standard's requirements. |
|-----------------------------------------------------------------------------------------|--------------------------------------------|

|                                                         |                                                          |
|---------------------------------------------------------|----------------------------------------------------------|
| <b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b> | UV resistance only in connection with protective shield. |
|---------------------------------------------------------|----------------------------------------------------------|

|                       |                                                                    |
|-----------------------|--------------------------------------------------------------------|
| <b>10.2.5 LIFTING</b> | Does not apply, since the entire switchgear needs to be evaluated. |
|-----------------------|--------------------------------------------------------------------|

|                                 |                                                                    |
|---------------------------------|--------------------------------------------------------------------|
| <b>10.2.6 MECHANICAL IMPACT</b> | Does not apply, since the entire switchgear needs to be evaluated. |
|---------------------------------|--------------------------------------------------------------------|

|                            |                                            |
|----------------------------|--------------------------------------------|
| <b>10.2.7 INSCRIPTIONS</b> | Meets the product standard's requirements. |
|----------------------------|--------------------------------------------|

|                                                |                                                                    |
|------------------------------------------------|--------------------------------------------------------------------|
| <b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b> | Does not apply, since the entire switchgear needs to be evaluated. |
|------------------------------------------------|--------------------------------------------------------------------|

|                                               |                                            |
|-----------------------------------------------|--------------------------------------------|
| <b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b> | Meets the product standard's requirements. |
|-----------------------------------------------|--------------------------------------------|

|                                               |                                                                    |
|-----------------------------------------------|--------------------------------------------------------------------|
| <b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b> | Does not apply, since the entire switchgear needs to be evaluated. |
|-----------------------------------------------|--------------------------------------------------------------------|

|                                                                 |                                                                                                                                  |
|-----------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| <b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>   | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| <b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>        | Is the panel builder's responsibility.                                                                                           |
| <b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>                 | Is the panel builder's responsibility.                                                                                           |
| <b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>                 | Is the panel builder's responsibility.                                                                                           |
| <b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>                         | Is the panel builder's responsibility.                                                                                           |
| <b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b> | Is the panel builder's responsibility.                                                                                           |
| <b>10.10 TEMPERATURE RISE</b>                                   | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| <b>10.11 SHORT-CIRCUIT RATING</b>                               | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| <b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>                      | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| <b>10.13 MECHANICAL FUNCTION</b>                                | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |

## Resources

### BROCHURES

[Brochure - T Rotary Cam switch and P Switch-disconnector](#)

### CATALOGUES

[P Switch-disconnectors and T Rotary cam switches catalogue CA042001EN](#)

### DECLARATIONS OF CONFORMITY

[DA-DC-00004894.pdf](#) [DA-DC-00004923.pdf](#)

### DRAWINGS

[eaton-rotary-switches-mounting-t3-changeover-switch-dimensions.eps](#)

|                           |                                                                                                                                                                          |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                           | <a href="#">eaton-general-rotary-switch-t0-step-switch-symbol-002.eps</a><br><a href="#">eaton-rotary-switches-front-plate-t0-step-switch-symbol-006.eps</a>             |
| ECAD MODEL                | <a href="#">ETN.020484.edz</a>                                                                                                                                           |
| INSTALLATION INSTRUCTIONS | <a href="#">IL03801020Z</a>                                                                                                                                              |
| INSTALLATION VIDEOS       | <a href="#">Eaton's P Switch-disconnectors used in a factory</a>                                                                                                         |
| MCAD MODEL                | <a href="#">DA-CS-t3 4 e</a> <a href="#">DA-CD-t3 4 e</a>                                                                                                                |
| PRODUCT NOTIFICATIONS     | <a href="#">MZ008005ZU_Orderform_Customized_Switch.pdf</a><br><a href="#">MZ008006ZU_Orderform_Customized_Switch.pdf</a>                                                 |
| WIRING DIAGRAMS           | <a href="#">eaton-rotary-switches-t0-multi-speed-switch-wiring-diagram-046.eps</a><br><a href="#">eaton-rotary-switches-t0-multi-speed-switch-wiring-diagram-045.eps</a> |

|                 |
|-----------------|
| PROJECT NAME:   |
| PROJECT NUMBER: |
| PREPARED BY:    |
| DATE:           |



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

