Specifications

Eaton 206740

Eaton Moeller® series PKZ0 Clip plate, type shortened

General Specifications	
PRODUCT NAME	Eaton Moeller® series PKZ0 Accessory Clip plate
CATALOG NUMBER	206740
PRODUCT LENGTH/DEPTH	14 mm
PRODUCT HEIGHT	195 mm
PRODUCT WIDTH	44 mm
PRODUCT WEIGHT	0.069 kg
CERTIFICATIONS	according to IEC/EN 60715
EAN	4015082067403
MODEL CODE	C-PKZ0-K



Product specifications	
10.10 TEMPERATURE RISE	Not applicable.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.

Resources	
BROCHURES	eaton-motor-starters- system-xstart-brochure- br03407001en-en-us.pdf
CATALOGUES	Product Range Catalog Switching and protecting motors
	eaton-product-overview- for-machinery-catalogue- ca08103003zen-en-us.pdf
DECLARATIONS OF CONFORMITY	DA-DC-00004886.pdf
	DA-DC-00005041.pdf
	DA-DC-00004920.pdf
	DA-DC-00004915.pdf
	DA-DC-00004891.pdf
	DA-DC-00005040.pdf
	DA-DC-00004890.pdf
ECAD MODEL	ETN.206740.edz
INSTALLATION INSTRUCTIONS	IL03402001Z
INSTALLATION VIDEOS	WIN-WIN with push-in technology
MCAD MODEL	c_pkz0_k.stp_c_pkz0_k.dwg
SALES NOTES	eaton-link-module-for- motor-starters-pkz-flyer- fl034003en-en-us.pdf

10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	ls the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	ls the panel builder's responsibility.
10.9.2 POWER- FREQUENCY ELECTRIC STRENGTH	ls the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	ls the panel builder's responsibility.
STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT PVS	0 W
PRODUCT CATEGORY	Accessories
FASTENING TYPE	DIN rail (top hat rail) 15 mm
FASTENING TYPE AMBIENT OPERATING TEMPERATURE - MAX	·
AMBIENT OPERATING	mm
AMBIENT OPERATING TEMPERATURE - MAX AMBIENT OPERATING	mm 55 °C
AMBIENT OPERATING TEMPERATURE - MAX AMBIENT OPERATING TEMPERATURE - MIN EQUIPMENT HEAT DISSIPATION, CURRENT-	mm 55 °C -25 °C
AMBIENT OPERATING TEMPERATURE - MAX AMBIENT OPERATING TEMPERATURE - MIN EQUIPMENT HEAT DISSIPATION, CURRENT- DEPENDENT PVID HEAT DISSIPATION	mm 55 °C -25 °C 0 W
AMBIENT OPERATING TEMPERATURE - MAX AMBIENT OPERATING TEMPERATURE - MIN EQUIPMENT HEAT DISSIPATION, CURRENT- DEPENDENT PVID HEAT DISSIPATION CAPACITY PDISS HEAT DISSIPATION PER POLE, CURRENT-	mm 55 °C -25 °C 0 W 0 W
AMBIENT OPERATING TEMPERATURE - MAX AMBIENT OPERATING TEMPERATURE - MIN EQUIPMENT HEAT DISSIPATION, CURRENT- DEPENDENT PVID HEAT DISSIPATION CAPACITY PDISS HEAT DISSIPATION PER POLE, CURRENT- DEPENDENT PVID RATED OPERATIONAL CURRENT FOR SPECIFIED	mm 55 °C -25 °C 0 W 0 W
AMBIENT OPERATING TEMPERATURE - MAX AMBIENT OPERATING TEMPERATURE - MIN EQUIPMENT HEAT DISSIPATION, CURRENT- DEPENDENT PVID HEAT DISSIPATION CAPACITY PDISS HEAT DISSIPATION PER POLE, CURRENT- DEPENDENT PVID RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	mm 55 °C -25 °C 0 W 0 W 0 W Snap fitting
AMBIENT OPERATING TEMPERATURE - MAX AMBIENT OPERATING TEMPERATURE - MIN EQUIPMENT HEAT DISSIPATION, CURRENT- DEPENDENT PVID HEAT DISSIPATION CAPACITY PDISS HEAT DISSIPATION PER POLE, CURRENT- DEPENDENT PVID RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) MOUNTING METHOD	mm 55 °C -25 °C 0 W 0 W 0 W Snap fitting Screw fixing

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.









