

Specifications

Photo is representative

Eaton 207197

Eaton Moeller® series T3 Multi-speed switches, T3, 32 A, surface mounting, 4 contact unit(s), Contacts: 8, 60 °, maintained, With 0 (Off) position, 1-0-2, Design number 8441

General specifications

PRODUCT NAME	Eaton Moeller® series T3 Multi-speed switch
CATALOG NUMBER	207197
EAN	4015082071974
PRODUCT LENGTH/DEPTH	181 mm
PRODUCT HEIGHT	127 mm
PRODUCT WIDTH	100 mm
PRODUCT WEIGHT	0.594 kg
CERTIFICATIONS	CE IEC/EN 60947 CSA Class No.: 3211-05 CSA-C22.2 No. 94 UL CSA-C22.2 No. 60947-4-1-14 UL 60947-4-1 CSA UL File No.: E36332 IEC/EN 60947-3 VDE 0660 CSA File No.: 012528 UL Category Control No.: NLRV IEC/EN 60204
CATALOG NOTES	Rated Short-time Withstand Current (Icw) for a time of 1 second
MODEL CODE	T3-4-8441/I2

Features & Functions

ENCLOSURE MATERIAL	Plastic
FEATURES	Complete device in housing
FITTED WITH:	0 (off) position Black thumb grip and front plate
INSCRIPTION	1-0-2
NUMBER OF POLES	3
SWITCH FUNCTION TYPE	One tapped winding, 2 speeds

General

DEGREE OF PROTECTION	IP65 NEMA 12 NEMA 1
DEGREE OF PROTECTION (FRONT SIDE)	IP65 NEMA 12
LIFESPAN, MECHANICAL	500,000 Operations
MODEL	Dahlander switch
MOUNTING METHOD	Surface mounting
MOUNTING POSITION	As required
NUMBER OF CONTACT UNITS	4
OPERATING FREQUENCY	1200 Operations/h
OVERTVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Control switches
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
SAFE ISOLATION	440 V AC, Between the contacts, According to EN 61140
SAFETY PARAMETER (EN ISO 13849-1)	B10d values as per EN ISO 13849-1, table C.1
SHOCK RESISTANCE	12 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms
SUITABLE FOR	Branch circuits, suitable as motor disconnect, (UL/CSA) Ground mounting Front mounting
SWITCHING ANGLE	60 °
TYPE	Multi-speed switch

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE - MAX	40 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78

Terminal capacities

TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	1 x (0.75 - 4) mm ² , ferrules to DIN 46228 2 x (0.75 - 4) mm ² , ferrules to DIN 46228
TERMINAL CAPACITY (SOLID/FLEXIBLE WITH FERRULE AWG)	14 - 10
TERMINAL CAPACITY (SOLID/STRANDED)	1 x (1 - 6) mm ² 2 x (1 - 6) mm ²
SCREW SIZE	M4, Terminal screw
TIGHTENING TORQUE	1.6 Nm, Screw terminals 17.7 lb-in, Screw terminals

Electrical rating

RATED BREAKING

CAPACITY AT 220/230 V 260 A
(COS PHI TO IEC 60947-3)

RATED BREAKING

CAPACITY AT 400/415 V 260 A
(COS PHI TO IEC 60947-3)

RATED BREAKING

CAPACITY AT 500 V (COS PHI TO IEC 60947-3) 240 A

RATED BREAKING

CAPACITY AT 660/690 V (COS PHI TO IEC 60947-3) 170 A

32 A at AC-3, 500 V star-delta

25.5 A at AC-3, 690 V star-delta

32 A at AC-3, 230 V star-delta

32 A at AC-3, 400 V star-delta

RATED OPERATIONAL CURRENT (IE)

RATED OPERATIONAL CURRENT (IE) AT AC-3, 220 V, 230 V, 240 V

RATED OPERATIONAL CURRENT (IE) AT AC-3, 380 V, 400 V, 415 V

RATED OPERATIONAL CURRENT (IE) AT AC-3, 500 V

RATED OPERATIONAL CURRENT (IE) AT AC-3, 660 V, 690 V

RATED OPERATIONAL CURRENT (IE) AT AC-21, 440 V

RATED OPERATIONAL CURRENT (IE) AT AC-23A, 230 V

RATED OPERATIONAL CURRENT (IE) AT AC-23A, 400 V, 415 V

RATED OPERATIONAL CURRENT (IE) AT AC-23A, 500 V

RATED OPERATIONAL CURRENT (IE) AT AC-23A, 690 V

RATED OPERATIONAL CURRENT (IE) AT DC-1,

25 A

Short-circuit rating

RATED CONDITIONAL

SHORT-CIRCUIT CURRENT (IQ) 1 kA

RATED SHORT-TIME

WITHSTAND CURRENT (ICW) 650 A, Contacts, 1 second

SHORT-CIRCUIT CURRENT RATING (BASIC RATING) 5 kA, SCCR (UL/CSA)
40A, max. Fuse, SCCR (UL/CSA)

SHORT-CIRCUIT CURRENT RATING (HIGH FAULT) 10 kA, SCCR (UL/CSA)
40 A, Class J, max. Fuse, SCCR (UL/CSA)

SHORT-CIRCUIT PROTECTION RATING 35 A gG/gL, Fuse, Contacts

LOAD-BREAK SWITCHES

L/R = 1 MS

RATED OPERATIONAL

CURRENT (IE) AT DC-13,

CONTROL SWITCHES L/R

= 50 MS

20 A

RATED OPERATIONAL

CURRENT (IE) AT DC-21,

1 A

240 V

RATED OPERATIONAL

CURRENT (IE) AT DC-23A,

25 A

24 V

RATED OPERATIONAL

CURRENT (IE) AT DC-23A,

25 A

48 V

RATED OPERATIONAL

CURRENT (IE) AT DC-23A,

25 A

60 V

RATED OPERATIONAL

CURRENT (IE) AT DC-23A,

12 A

120 V

RATED OPERATIONAL

CURRENT (IE) AT DC-23A,

5 A

240 V

RATED OPERATIONAL

POWER AT AC-3, 380/400

12 kW

V, 50 Hz

RATED OPERATIONAL

POWER AT AC-3, 415 V, 50

11 kW

Hz

RATED OPERATIONAL

POWER AT AC-3, 690 V, 50

11 kW

Hz

RATED OPERATIONAL

POWER AT AC-23A,

7.5 kW

220/230 V, 50 Hz

RATED OPERATIONAL

POWER AT AC-23A, 400 V,

15 kW

50 Hz

RATED OPERATIONAL

POWER AT AC-23A, 500 V,

15 kW

50 Hz

RATED OPERATIONAL

POWER AT AC-23A, 690 V,

15 kW

50 Hz

RATED OPERATIONAL

POWER STAR-DELTA AT

7.5 kW

220/230 V, 50 Hz

RATED OPERATIONAL

POWER STAR-DELTA AT

15 kW

380/400 V, 50 HZ

**RATED OPERATIONAL
POWER STAR-DELTA AT
500 V, 50 HZ**

18.5 kW

**RATED OPERATIONAL
POWER STAR-DELTA AT
690 V, 50 HZ**

**RATED OPERATIONAL
VOLTAGE (UE) AT AC -
MAX**

690 V

**RATED UNINTERRUPTED
CURRENT (IU)**

32 A

**UNINTERRUPTED
CURRENT**

Rated uninterrupted
current I_u is specified for
max. cross-section.

Switching capacity

LOAD RATING	1.3 x I _e (with intermittent operation class 12, 60 % duty factor) 1.6 x I _e (with intermittent operation class 12, 40 % duty factor) 2 x I _e (with intermittent operation class 12, 25 % duty factor)
NUMBER OF CONTACTS IN SERIES AT DC-21A, 240 V	1
NUMBER OF CONTACTS IN SERIES AT DC-23A, 24 V	1
NUMBER OF CONTACTS IN SERIES AT DC-23A, 48 V	2
NUMBER OF CONTACTS IN SERIES AT DC-23A, 60 V	3
NUMBER OF CONTACTS IN SERIES AT DC-23A, 120 V	3
NUMBER OF CONTACTS IN SERIES AT DC-23A, 240 V	5
SWITCHING CAPACITY (MAIN CONTACTS, GENERAL USE)	25 A, Rated uninterrupted current max. (UL/CSA)
SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)	10A, IU, (UL/CSA)
SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)	P600 (UL/CSA) A600 (UL/CSA)
RATED MAKING CAPACITY UP TO 690 V (COS PHI TO IEC/EN 60947-3)	320 A
VOLTAGE PER CONTACT PAIR IN SERIES	60 V

Motor rating

ASSIGNED MOTOR POWER AT 115/120 V, 60 HZ, 1-PHASE	1.5 HP
ASSIGNED MOTOR POWER AT 200/208 V, 60 HZ, 1-PHASE	3 HP
ASSIGNED MOTOR POWER AT 200/208 V, 60 HZ, 3-PHASE	3 HP
ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 1-PHASE	3 HP
ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 3-PHASE	3 HP
ASSIGNED MOTOR POWER AT 460/480 V, 60 HZ, 3-PHASE	7.5 HP
ASSIGNED MOTOR POWER AT 575/600 V, 60 HZ, 3-PHASE	10 HP

Contacts

CONTROL CIRCUIT RELIABILITY 1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA)

NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS) 0

NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS) 0

NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS) 0

NUMBER OF CONTACTS 8

Actuator

ACTUATOR FUNCTION With 0 (Off) position
Maintained

ACTUATOR TYPE Short thumb-grip

Design verification

EQUIPMENT HEAT

DISSIPATION, CURRENT- 0 W

DEPENDENT PVID

HEAT DISSIPATION 0 W
CAPACITY PDISS

HEAT DISSIPATION PER
POLE, CURRENT- 1.1 W
DEPENDENT PVID

RATED OPERATIONAL
CURRENT FOR SPECIFIED 32 A
HEAT DISSIPATION (IN)

STATIC HEAT
DISSIPATION, NON- 0 W
CURRENT-DEPENDENT
PVS

**10.2.2 CORROSION
RESISTANCE** Meets the product
standard's requirements.

**10.2.3.1 VERIFICATION OF
THERMAL STABILITY OF
ENCLOSURES** Meets the product
standard's requirements.

**10.2.3.2 VERIFICATION OF
RESISTANCE OF
INSULATING MATERIALS
TO NORMAL HEAT** Meets the product
standard's requirements.

**10.2.3.3 RESIST. OF
INSUL. MAT. TO
ABNORMAL HEAT/FIRE
BY INTERNAL ELECT.
EFFECTS** Meets the product
standard's requirements.

**10.2.4 RESISTANCE TO
ULTRA-VIOLET (UV)
RADIATION** UV resistance only in
connection with protective
shield.

10.2.5 LIFTING Does not apply, since the
entire switchgear needs to
be evaluated.

**10.2.6 MECHANICAL
IMPACT** Does not apply, since the
entire switchgear needs to
be evaluated.

10.2.7 INSCRIPTIONS Meets the product
standard's requirements.

**10.3 DEGREE OF
PROTECTION OF
ASSEMBLIES** Does not apply, since the
entire switchgear needs to
be evaluated.

**10.4 CLEARANCES AND
CREEPAGE DISTANCES** Meets the product
standard's requirements.

**10.5 PROTECTION
AGAINST ELECTRIC
SHOCK** Does not apply, since the
entire switchgear needs to
be evaluated.

10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

BROCHURES	Brochure - T Rotary Cam switch and P Switch-disconnector
CATALOGUES	P Switch-disconnectors and T Rotary cam switches catalogue CA042001EN
DECLARATIONS OF CONFORMITY	DA-DC-00004923.pdf DA-DC-00004894.pdf
DRAWINGS	eaton-rotary-switches-dimensions-t3-main-switch-dimensions.eps

[eaton-rotary-switches-t3-changeover-switch-dimensions-002.eps](#)
[eaton-rotary-switches-front-plate-t0-changeover-switch-symbol-009.eps](#)
[eaton-general-totally-insulated-t0-main-switch-symbol.eps](#)
[eaton-rotary-switches-surface-mounting-t0-changeover-switch-3d-drawing.eps](#)
[eaton-general-rotary-switch-t0-step-switch-symbol.eps](#)

ECAD MODEL	DA-CE-ETN.T3-4-8441_I2
INSTALLATION INSTRUCTIONS	IL03801008Z2021_06.pdf
INSTALLATION VIDEOS	Eaton's P Switch-disconnectors used in a factory
MCAD MODEL	DA-CD-bauform8 DA-CS-bauform8
PRODUCT NOTIFICATIONS	MZ008006ZU_Orderform_Customized_Switch.pdf MZ008005ZU_Orderform_Customized_Switch.pdf
WIRING DIAGRAMS	eaton-rotary-switches-switch-t0-main-switch-wiring-diagram-010.eps

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
[Eaton.com](#)

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

