

Specifications

Eaton 207210

Eaton Moeller® series T3 Main switch, T3, 32 A, surface mounting, 4 contact unit(s), 6 pole, 1 N/O, 1 N/C, Emergency switching off function, With red rotary handle and yellow locking ring, Lockable in the 0 (Off) position

General specifications

PRODUCT NAME	Eaton Moeller® series T3 Main switch
CATALOG NUMBER	207210
EAN	4015082072100
PRODUCT LENGTH/DEPTH	181 mm
PRODUCT HEIGHT	135 mm
PRODUCT WIDTH	100 mm
PRODUCT WEIGHT	0.718 kg
CERTIFICATIONS	CSA IEC/EN 60204 IEC/EN 60947-3 UL UL File No.: E36332 CSA File No.: 012528 UL Category Control No.: NLRV CE CSA Class No.: 3211-05 CSA-C22.2 No. 60947-4-1-14 CSA-C22.2 No. 94 IEC/EN 60947 UL 60947-4-1 VDE 0660
CATALOG NOTES	Rated Short-time Withstand Current (Icw) for a time of 1 second
MODEL CODE	T3-4-15682/I2/SVB

Features & Functions

FEATURES	Version as maintenance- /service switch
	Version as main switch
	Version as emergency stop installation
FITTED WITH:	Red rotary handle and yellow locking ring
FUNCTIONS	Emergency switching off function
	Interlockable
LOCKING FACILITY	Lockable in the 0 (Off) position
NUMBER OF POLES	6

General

DEGREE OF PROTECTION	NEMA 12
DEGREE OF PROTECTION (FRONT SIDE)	IP65
LIFESPAN, MECHANICAL	500,000 Operations
MOUNTING METHOD	Surface mounting
MOUNTING POSITION	As required
NUMBER OF CONTACT UNITS	4
OPERATING FREQUENCY	1200 Operations/h
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Main switch
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
SAFE ISOLATION	440 V AC, Between the contacts, According to EN 61140
SAFETY PARAMETER (EN ISO 13849-1)	B10d values as per EN ISO 13849-1, table C.1
SHOCK RESISTANCE	12 g, Mechanical, According to IEC/EN 60068-2-27, Half- sinusoidal shock 20 ms
SUITABLE FOR	Branch circuits, suitable as motor disconnect, (UL/CSA) Ground mounting
SWITCHING ANGLE	90 °

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
--	--------

AMBIENT OPERATING TEMPERATURE - MAX	40 °C
--	-------

AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-25 °C
---	--------

AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
---	-------

CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
--------------------------	--

Terminal capacities

TERMINAL CAPACITY	2 x (0.75 - 4) mm ² , flexible with ferrules to DIN 46228 2 x (1 - 6) mm ² , solid or stranded 1 x (0.75 - 4) mm ² , flexible with ferrules to DIN 46228 1 x (1 - 6) mm ² , solid or stranded
--------------------------	--

SCREW SIZE	M4, Terminal screw
-------------------	--------------------

TIGHTENING TORQUE	1.6 Nm, Screw terminals 17.7 lb-in, Screw terminals
--------------------------	--

Electrical rating

**RATED BREAKING
CAPACITY AT 220/230 V** 260 A
(COS PHI TO IEC 60947-3)

**RATED BREAKING
CAPACITY AT 400/415 V** 260 A
(COS PHI TO IEC 60947-3)

**RATED BREAKING
CAPACITY AT 500 V (COS
PHI TO IEC 60947-3)** 240 A

**RATED BREAKING
CAPACITY AT 660/690 V** 170 A
(COS PHI TO IEC 60947-3)

**RATED OPERATIONAL
CURRENT (IE) AT AC-3,** 23.7 A
220 V, 230 V, 240 V

**RATED OPERATIONAL
CURRENT (IE) AT AC-3,** 23.7 A
380 V, 400 V, 415 V

**RATED OPERATIONAL
CURRENT (IE) AT AC-3,** 23.7 A
500 V

**RATED OPERATIONAL
CURRENT (IE) AT AC-3,** 14.7 A
660 V, 690 V

**RATED OPERATIONAL
CURRENT (IE) AT AC-21,** 32 A
440 V

**RATED OPERATIONAL
CURRENT (IE) AT AC-23A,** 32 A
230 V

**RATED OPERATIONAL
CURRENT (IE) AT AC-23A,** 32 A
400 V, 415 V

**RATED OPERATIONAL
CURRENT (IE) AT AC-23A,** 26.4 A
500 V

**RATED OPERATIONAL
CURRENT (IE) AT AC-23A,** 17 A
690 V

**RATED OPERATIONAL
CURRENT (IE) AT DC-1,
LOAD-BREAK SWITCHES
L/R = 1 MS** 25 A

**RATED OPERATIONAL
CURRENT (IE) AT DC-13,
CONTROL SWITCHES L/R
= 50 MS** 20 A

**RATED OPERATIONAL
CURRENT (IE) AT DC-21,** 1 A

Short-circuit rating

**RATED CONDITIONAL
SHORT-CIRCUIT CURRENT** 1 kA
(IQ)

**RATED SHORT-TIME
WITHSTAND CURRENT** 0.65 kA
(ICW) 650 A, Contacts, 1 second

**SHORT-CIRCUIT
PROTECTION RATING** 35 A gG/gL, Fuse, Contacts

240 V	
RATED OPERATIONAL CURRENT (IE) AT DC-23A, 24 V	25 A
RATED OPERATIONAL CURRENT (IE) AT DC-23A, 48 V	25 A
RATED OPERATIONAL CURRENT (IE) AT DC-23A, 60 V	25 A
RATED OPERATIONAL CURRENT (IE) AT DC-23A, 120 V	12 A
RATED OPERATIONAL CURRENT (IE) AT DC-23A, 240 V	5 A
RATED OPERATIONAL CURRENT (IE) STAR- DELTA AT AC-3, 220/230 V	32 A
RATED OPERATIONAL CURRENT (IE) STAR- DELTA AT AC-3, 380/400 V	32 A
RATED OPERATIONAL CURRENT (IE) STAR- DELTA AT AC-3, 500 V	32 A
RATED OPERATIONAL CURRENT (IE) STAR- DELTA AT AC-3, 690 V	25.5 A
RATED OPERATIONAL POWER AT AC-3, 380/400 V, 50 HZ	11 kW
RATED OPERATIONAL POWER AT AC-3, 415 V, 50 HZ	11 kW
RATED OPERATIONAL POWER AT AC-3, 690 V, 50 HZ	11 kW
RATED OPERATIONAL POWER AT AC-23A, 220/230 V, 50 HZ	7.5 kW
RATED OPERATIONAL POWER AT AC-23A, 400 V, 50 HZ	15 kW
RATED OPERATIONAL POWER AT AC-23A, 500 V, 50 HZ	15 kW
RATED OPERATIONAL POWER AT AC-23A, 690 V, 50 HZ	15 kW
RATED OPERATIONAL	7.5 kW

POWER STAR-DELTA AT 220/230 V, 50 HZ	
RATED OPERATIONAL POWER STAR-DELTA AT 380/400 V, 50 HZ	15 kW
RATED OPERATIONAL POWER STAR-DELTA AT 500 V, 50 HZ	18.5 kW
RATED OPERATIONAL POWER STAR-DELTA AT 690 V, 50 HZ	22 kW
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	690 V
RATED UNINTERRUPTED CURRENT (IU)	32 A
UNINTERRUPTED CURRENT	Rated uninterrupted current Iu is specified for max. cross-section.

Switching capacity

LOAD RATING	1.3 x I _e (with intermittent operation class 12, 60 % duty factor)
	1.6 x I _e (with intermittent operation class 12, 40 % duty factor)
	2 x I _e (with intermittent operation class 12, 25 % duty factor)

NUMBER OF CONTACTS IN SERIES AT DC-21A, 240 V

1

NUMBER OF CONTACTS IN SERIES AT DC-23A, 24 V

1

NUMBER OF CONTACTS IN SERIES AT DC-23A, 48 V

2

NUMBER OF CONTACTS IN SERIES AT DC-23A, 60 V

3

NUMBER OF CONTACTS IN SERIES AT DC-23A, 120 V

3

NUMBER OF CONTACTS IN SERIES AT DC-23A, 240 V

5

RATED MAKING CAPACITY UP TO 690 V (COS PHI TO IEC/EN 60947-3)

320 A

VOLTAGE PER CONTACT PAIR IN SERIES

60 V

Actuator

ACTUATOR COLOR Red

ACTUATOR TYPE Door coupling rotary drive

Contacts

CONTROL CIRCUIT RELIABILITY 1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA)

NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)

0

NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)

1

NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)

1

Design verification

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID 1.1 W

HEAT DISSIPATION CAPACITY PDISS 0 W

HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID 1.1 W

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) 32 A

STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS 0 W

10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	UV resistance only in connection with protective shield.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is

	responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

BROCHURES [Brochure - T Rotary Cam switch and P Switch-disconnector](#)

CATALOGUES [P Switch-disconnectors and T Rotary cam switches catalogue CA042001EN](#)

DECLARATIONS OF CONFORMITY [DA-DC-00004923.pdf](#) [DA-DC-00004894.pdf](#)

DRAWINGS

[eaton-rotary-switches-dimensions-t3-main-switch-dimensions.eps](#)

[eaton-rotary-switches-surface-mounting-t3-main-switch-dimensions-002.eps](#)

[eaton-rotary-switches-padlock-t0-main-switch-dimensions.eps](#)

[eaton-general-totally-insulated-t0-main-switch-symbol.eps](#)

[eaton-general-switch-t0-main-switch-symbol.eps](#)

[eaton-rotary-switches-t0-main-switch-symbol.eps](#)

[eaton-rotary-switches-surface-mounting-t0-main-switch-3d-drawing.eps](#)

ECAD MODEL [ETN.207210.edz](#)

INSTALLATION VIDEOS [Eaton's P Switch-disconnectors used in a factory](#)

MCAD MODEL [DA-CD-bauform7](#) [DA-CS-bauform7](#)

PRODUCT NOTIFICATIONS [MZ008005ZU Orderform Customized Switch.pdf](#)
[MZ008006ZU Orderform Customized Switch.pdf](#)

WIRING DIAGRAMS [eaton-rotary-switches-switch-t0-main-switch-wiring-diagram-003.eps](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

