

# Specifications

Photo is representative

## Eaton 208226

Eaton Moeller® series DILM Contactor, 380 V 400 V 450 kW, 2 N/O, 2 NC, RAC 500: 250 - 500 V 40 - 60 Hz/250 - 700 V DC, AC and DC operation, Screw connection

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller® series DILM Contactor
<b>CATALOG NUMBER</b>	208226
<b>MODEL CODE</b>	DILM820/22(RAC500)
<b>EAN</b>	4015082082260
<b>PRODUCT LENGTH/DEPTH</b>	232 mm
<b>PRODUCT HEIGHT</b>	296 mm
<b>PRODUCT WIDTH</b>	250 mm
<b>PRODUCT WEIGHT</b>	16.536 kg
<b>CERTIFICATIONS</b>	CSA UL Category Control No.: NLDX CE CSA File No.: 012528 CSA Class No.: 3211-04 UL UL File No.: E29096 IEC/EN 60947 UL 60947-4-1 VDE 0660 CSA-C22.2 No. 60947-4-1- 14 IEC/EN 60947-4-1
<b>CATALOG NOTES</b>	<ul style="list-style-type: none"><li>• Contacts according to EN 50012</li><li>• Also tested according to AC-3e up to 690 V.</li><li>• Also suitable for motors with efficiency class IE3.</li><li>• Conventional thermal current I<sub>th</sub> of main contacts (1-</li></ul>



Powering Business Worldwide

pole, open) at 60°

**GLOBAL CATALOG**

208226

## Product specifications

<b>ACCESSORIES</b>	Fitting options auxiliary contacts: on the side: 2 x DILM820-XHI11(V)-SI; 2 x DILM820-XHI11-SA
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.

## Resources

<b>CATALOGS</b>	<a href="#">Product Range Catalog Switching and protecting motors</a>
<b>CHARACTERISTIC CURVE</b>	<a href="#">eaton-contactors-component-dilm-characteristic-curve.eps</a> <a href="#">eaton-contactors-component-dilm-characteristic-curve-003.eps</a> <a href="#">eaton-contactors-short-time-loading-dilm-characteristic-curve-002.eps</a> <a href="#">eaton-contactors-component-dilm-characteristic-curve-002.eps</a>
<b>DECLARATIONS OF CONFORMITY</b>	<a href="#">DA-DC-00005052.pdf</a> <a href="#">DA-DC-00005043.pdf</a>
<b>DRAWINGS</b>	<a href="#">eaton-contactors-dilm-dimensions-005.eps</a> <a href="#">eaton-contactors-mounting-dilm-dimensions.eps</a> <a href="#">eaton-contactors-mounting-dilm-dimensions-002.eps</a> <a href="#">eaton-contactors-mounting-dilm-3d-drawing-002.eps</a> <a href="#">eaton-contactors-dilm-3d-drawing-006.eps</a>
<b>ECAD MODEL</b>	<a href="#">DA-CE-ETN.DILM820 22(RAC500)</a>
<b>INSTALLATION INSTRUCTIONS</b>	<a href="#">IL03407023Z2021_09.pdf</a>
<b>MCAD MODEL</b>	<a href="#">eaton-dil m580 820-3d-model.stp</a> <a href="#">eaton-dil m580 820-drawing.dwg</a>
<b>WIRING DIAGRAMS</b>	<a href="#">eaton-contactors-contact-dilm-wiring-diagram-004.eps</a>

<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>FITTED WITH:</b>	Suppressor circuit in actuating electronics
<b>OPERATING FREQUENCY</b>	1000 mechanical Operations/h (DC operated) 200 Operations/h 1000 mechanical Operations/h (AC operated)
<b>POLLUTION DEGREE</b>	3
<b>CLIMATIC PROOFING</b>	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
<b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b>	8000 V AC
<b>UTILIZATION CATEGORY</b>	AC-1: Non-inductive or slightly inductive loads, resistance furnaces AC-4: Normal AC induction motors: starting, plugging, reversing, inching AC-3: Normal AC induction motors: starting, switch off during running

<b>CONNECTION</b>	Screw terminals
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	60 °C
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-40 °C
<b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX</b>	40 °C
<b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN</b>	-40 °C
<b>AMBIENT STORAGE TEMPERATURE - MAX</b>	80 °C
<b>AMBIENT STORAGE TEMPERATURE - MIN</b>	-40 °C
<b>ASSIGNED MOTOR POWER AT 200/208 V, 60 HZ, 3-PHASE</b>	290 HP
<b>ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 3-PHASE</b>	350 HP
<b>ASSIGNED MOTOR POWER AT 460/480 V, 60 HZ, 3-PHASE</b>	700 HP
<b>ASSIGNED MOTOR POWER AT 575/600 V, 60 HZ, 3-PHASE</b>	860 HP
<b>CONVENTIONAL THERMAL CURRENT ITH AT 55°C (3-POLE, OPEN)</b>	1044 A
<b>CONVENTIONAL THERMAL CURRENT ITH OF MAIN CONTACTS (1-POLE, OPEN)</b>	2500 A
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>	0 W
<b>HEAT DISSIPATION CAPACITY PDISS</b>	0 W
<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>	21.67 W
<b>APPLICATION</b>	Contactors for Motors
<b>PRODUCT CATEGORY</b>	Contactors
<b>PROTECTION</b>	Finger and back-of-hand proof with terminal shroud or terminal block, Protection against direct contact when actuated

	from front (EN 50274)
<b>ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT</b>	Rail connection
<b>SCREWDRIVER SIZE</b>	2, Terminal screw, Control circuit cables, Pozidriv screwdriver
<b>VOLTAGE TYPE</b>	AC/DC
<b>DEGREE OF PROTECTION</b>	IP00
<b>NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)</b>	2
<b>NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)</b>	2
<b>NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)</b>	2
<b>NUMBER OF CONTACTS (NORMALLY CLOSED) AS MAIN CONTACT</b>	0
<b>NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)</b>	2
<b>NUMBER OF MAIN CONTACTS (NORMALLY OPEN CONTACT)</b>	3
<b>RATED BREAKING CAPACITY AT 1000 V</b>	5800 A
<b>RATED BREAKING CAPACITY AT 220/230 V</b>	8200 A
<b>RATED BREAKING CAPACITY AT 380/400 V</b>	8200 A
<b>RATED BREAKING CAPACITY AT 500 V</b>	8200 A
<b>RATED BREAKING CAPACITY AT 660/690 V</b>	8200 A
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX</b>	500 V
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN</b>	480 V
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX</b>	500 V
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN</b>	480 V

<b>DROP-OUT VOLTAGE</b>	AC operated: $0.2 \times U_S \text{ max}$ - $0.6 \times U_S \text{ min}$ , AC operated $0.2 \times U_S \text{ max}$ - $0.6 \times U_S$ min, DC operated
<b>OVERVOLTAGE CATEGORY</b>	III
<b>BEHAVIOR IN MARGINAL AND TRANSITIONAL CONDITIONS</b>	<p>Sealing - Voltage interruptions <math>0 - 0.2 \times U_c \text{ min}</math>) <math>&gt; 10 \text{ ms}</math>: Drop-out of the contactor</p> <p>Sealing - Voltage drops (<math>0.6 - 0.7 \times U_c \text{ min}</math>): Contactor remains switched on</p> <p>Sealing - Voltage interruptions (<math>0 - 0.2 \times U_c \text{ min} \leq 10 \text{ ms}</math>: Time is bridged successfully</p> <p>Sealing - Pick-up phase (<math>0 - 0.7 \times U_c \text{ min}</math>: Contactor does not switch on</p> <p>Sealing - Voltage drops (<math>0.2 - 0.6 \times U_c \text{ min}</math>) <math>&gt; 12 \text{ ms}</math>: Drop-out of the contactor</p> <p>Sealing - Voltage drops (<math>0.2 - 0.6 \times U_c \text{ min} \leq 12 \text{ ms}</math>: Time is bridged successfully</p> <p>Sealing - Excess voltage (<math>1.15 - 1.3 \times U_c \text{ max}</math>): Contactor remains switched on</p> <p>Sealing - Pick-up phase (<math>0.7 \times U_c \text{ min} - 1.15 \times U_c \text{ max}</math>): Contactor switches on with certainty</p>
<b>DUTY FACTOR</b>	100 %
<b>ELECTROMAGNETIC COMPATIBILITY</b>	Designed for operation in industrial environments. Its use in residential environments may cause radio-frequency interference, requiring additional noise suppression.
<b>LIFESPAN, MECHANICAL</b>	5,000,000 Operations (DC operated) 5,000,000 Operations (AC operated)
<b>PICK-UP VOLTAGE</b>	$0.7 - 1.15 \text{ V AC} \times U_S$ $0.7 - 1.15 \text{ V DC} \times U_S$
<b>POWER CONSUMPTION,</b>	800 VA, Pull-in power, Coil

<b>PICK-UP, 50 HZ</b>	in a cold state and 1.0 x Us  700 W, Pull-in power, Coil in a cold state and 1.0 x Us
<b>SAFE ISOLATION</b>	1000 V AC, Between coil and contacts, According to EN 61140
<b>POWER CONSUMPTION, PICK-UP, 60 HZ</b>	700 W, Pull-in power, Coil in a cold state and 1.0 x Us  800 VA, Pull-in power, Coil in a cold state and 1.0 x Us
<b>SCREW SIZE</b>	M12, Terminal screw, Main connections M3.5, Terminal screw, Control circuit cables
<b>POWER CONSUMPTION, SEALING, 50 HZ</b>	12.4 W, Coil in a cold state and 1.0 x Us 28.8 VA, Coil in a cold state and 1.0 x Us
<b>POWER CONSUMPTION, SEALING, 60 HZ</b>	28.8 VA, Coil in a cold state and 1.0 x Us 12.4 W, Coil in a cold state and 1.0 x Us
<b>RESISTANCE</b>	500 mΩ (Admissible transitional contact resistance - of the external control circuit device when actuating A11)
<b>RATED OPERATIONAL CURRENT (IE)</b>	463 A at up to 525 V (Individual compensation, three-phase capacitors, open) 265 A at 690 V (Individual compensation, three-phase capacitors, open)
<b>INRUSH CURRENT</b>	Max. 30 x Ie (peak)
<b>SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)</b>	1 A, 250 V DC, (UL/CSA) 15 A, 600 V AC, (UL/CSA)
<b>SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)</b>	P300, DC operated (UL/CSA) A600, AC operated (UL/CSA)
<b>LIFESPAN, ELECTRICAL</b>	100,000 Operations (at Condensor operation)
<b>TERMINAL CAPACITY (COPPER BAND)</b>	Fixing with flat cable terminal or cable terminal blocks; See terminal capacity for cable terminal blocks



<b>TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)</b>	1 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables 2 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables
<b>SHOCK RESISTANCE</b>	8 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half- sinusoidal shock 10 ms 10 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half- sinusoidal shock 10 ms 10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half- sinusoidal shock 10 ms
<b>TERMINAL CAPACITY (SOLID)</b>	2 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables 1 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables
<b>TERMINAL CAPACITY (SOLID/STRANDED AWG)</b>	18 - 14, Control circuit cables 2/0 - 500 MCM, Main cables
<b>SIGNAL LEVEL</b>	5 V - 15 V, PLC signal level (A3 - A4) to IEC/EN 61131-2 (type 2), Magnet systems
<b>TERMINAL CAPACITY (BUSBAR)</b>	60 mm width, Main connection
<b>TERMINAL CAPACITY (FLEXIBLE WITH CABLE LUG)</b>	50 - 240 mm <sup>2</sup>
<b>SWITCHING CAPACITY (MAIN CONTACTS, GENERAL USE)</b>	1225 A, Maximum motor rating (UL/CSA)
<b>TERMINAL CAPACITY (STRANDED WITH CABLE LUG)</b>	70 - 240 mm <sup>2</sup>
<b>POWER CONSUMPTION</b>	Control transformer with uk ≤ 7%
<b>TIGHTENING TORQUE</b>	35 Nm, Main cable connection screw/bolt 1.2 Nm, Screw terminals, Control circuit cables
<b>WIDTH ACROSS FLATS</b>	18 mm
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX</b>	700 V
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN</b>	250 V

<b>RATED INSULATION VOLTAGE (UI)</b>	1000 V
<b>RATED MAKING CAPACITY (COS PHI TO IEC/EN 60947)</b>	9840 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 1000 V</b>	580 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 220 V, 230 V, 240 V</b>	820 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 380 V, 400 V, 415 V</b>	820 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 440 V</b>	820 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 500 V</b>	820 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 660 V, 690 V</b>	820 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-4, 1000 V</b>	464 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-4, 220 V, 230 V, 240 V</b>	656 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-4, 400 V</b>	656 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-4, 440 V</b>	656 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-4, 500 V</b>	656 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-4, 660 V, 690 V</b>	656 A
<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	820 A
<b>RATED OPERATIONAL POWER AT AC-3, 1000 V, 50 HZ</b>	800 kW
<b>RATED OPERATIONAL POWER AT AC-3, 240 V, 50 HZ</b>	285 kW

<b>RATED OPERATIONAL POWER AT AC-3, 380/400 V, 50 HZ</b>	450 kW
<b>RATED OPERATIONAL POWER AT AC-3, 415 V, 50 HZ</b>	500 kW
<b>RATED OPERATIONAL POWER AT AC-4, 1000 V, 50 HZ</b>	678 kW
<b>RATED OPERATIONAL POWER AT AC-4, 220/230 V, 50 HZ</b>	209 kW
<b>RATED OPERATIONAL POWER AT AC-4, 240 V, 50 HZ</b>	228 kW
<b>RATED OPERATIONAL POWER AT AC-4, 380/400 V, 50 HZ</b>	355 kW
<b>RATED OPERATIONAL POWER AT AC-4, 415 V, 50 HZ</b>	394 kW
<b>RATED OPERATIONAL POWER AT AC-4, 440 V, 50 HZ</b>	418 kW
<b>RATED OPERATIONAL POWER AT AC-4, 500 V, 50 HZ</b>	474 kW
<b>RATED OPERATIONAL POWER AT AC-4, 660/690 V, 50 HZ</b>	633 kW
<b>RATED OPERATIONAL POWER (NEMA)</b>	522 kW
<b>RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX</b>	1000 V
<b>RESISTANCE PER POLE</b>	0.032 mΩ
<b>STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT PVS</b>	6.5 W
<b>SWITCHING TIME (AC OPERATED, MAKE CONTACTS, CLOSING DELAY) - MAX</b>	70 ms
<b>SWITCHING TIME (AC OPERATED, MAKE CONTACTS, OPENING DELAY) - MAX</b>	110 ms
<b>SHORT-CIRCUIT CURRENT RATING (BASIC RATING)</b>	1200 A, max. CB, SCCR (UL/CSA)

	42 kA, SCCR (UL/CSA) 2000 A, max. Fuse, SCCR (UL/CSA)
<b>SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 480 V)</b>	2000 A, max. Fuse, SCCR (UL/CSA) 1200 A, max. CB, SCCR (UL/CSA) 85 kA, CB, SCCR (UL/CSA) 85 kA, Fuse, SCCR (UL/CSA)
<b>SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 600 V)</b>	85 kA, Fuse, SCCR (UL/CSA) 1200 A, max. CB, SCCR (UL/CSA) 2000 A, max. Fuse, SCCR (UL/CSA) 85 kA, CB, SCCR (UL/CSA)
<b>SHORT-CIRCUIT PROTECTION RATING (TYPE 1 COORDINATION) AT 1000 V</b>	800 A gG/gL
<b>SHORT-CIRCUIT PROTECTION RATING (TYPE 1 COORDINATION) AT 400 V</b>	1200 A gG/gL
<b>SHORT-CIRCUIT PROTECTION RATING (TYPE 1 COORDINATION) AT 690 V</b>	1200 A gG/gL
<b>SHORT-CIRCUIT PROTECTION RATING (TYPE 2 COORDINATION) AT 1000 V</b>	630 A gG/gL
<b>SHORT-CIRCUIT PROTECTION RATING (TYPE 2 COORDINATION) AT 400 V</b>	630 A gG/gL
<b>SHORT-CIRCUIT PROTECTION RATING (TYPE 2 COORDINATION) AT 690 V</b>	630 A gG/gL
<b>SPECIAL PURPOSE RATING OF DEFINITE PURPOSE RATING</b>	900 A, FLA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA) 5400 A, LRA 600 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA) 900 A, FLA 600 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA) 5400 A, LRA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA)
<b>CONVENTIONAL</b>	1225 A

<b>THERMAL CURRENT ITH AT 40°C (3-POLE, OPEN)</b>	
<b>CONVENTIONAL THERMAL CURRENT ITH AT 50°C (3-POLE, OPEN)</b>	1095 A
<b>CONVENTIONAL THERMAL CURRENT ITH AT 60°C (3-POLE, OPEN)</b>	1000 A
<b>RATED OPERATIONAL POWER AT AC-3, 440 V, 50 HZ</b>	450 kW
<b>RATED OPERATIONAL POWER AT AC-3, 500 V, 50 HZ</b>	600 kW
<b>RATED OPERATIONAL POWER AT AC-3, 690 V, 50 HZ</b>	750 kW
<b>ACTUATING VOLTAGE</b>	RAC 500: 250 - 500 V 40 - 60 Hz/250 - 700 V DC
<b>ALTITUDE</b>	Max. 2000 m
<b>OPERATING VOLTAGE AT AC, 50 HZ - MIN</b>	250 V
<b>OPERATING VOLTAGE AT AC, 50 HZ - MAX</b>	500 V
<b>OPERATING VOLTAGE AT AC, 60 HZ - MIN</b>	250 V
<b>OPERATING VOLTAGE AT AC, 60 HZ - MAX</b>	500 V

<b>PROJECT NAME:</b>
<b>PROJECT NUMBER:</b>
<b>PREPARED BY:</b>
<b>DATE:</b>



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

